



Plagiarism Checker X - Report

Originality Assessment

Overall Similarity: **19%**

Date: Mar 29, 2022

Statistics: 1020 words Plagiarized / 5483 Total words

Remarks: Low similarity detected, check with your supervisor if changes are required.

Journal of Physics: Conference Series PAPER • OPEN ACCESS Porosity and permeability prediction using pore geometry structure method on tight carbonate reservoir To cite this article: B S Mulyanto et al 2020 J. Phys.: Conf. Ser. 1572 012052 View the article online for updates and enhancements. This content was downloaded from IP address 114.125.235.123 on 25/10/2020 at 12:22

Content from this work may be used under the terms of the Creative Commons Attribution 3.0 licence. Any further distribution of this work must maintain attribution to the

author(s) and the title of the work, journal citation and DOI. Published under licence by IOP Publishing Ltd The 9th International Conference on Theoretical and Applied Physics (ICTAP) Journal of Physics: Conference Series 1572 (2020) 012052 IOP Publishing

doi:10.1088/1742-6596/1572/1/012052 Porosity and permeability prediction using pore geometry structure method on tight carbonate reservoir B S Mulyanto¹, O Dewanto¹, A

Yuliani¹, A Yogi² and R C Wibowo^{1*} ¹ Geophysical Engineering Department,

Engineering Faculty, Universitas Lampung, Prof. Soemantri Brodjonegoro Street No.1, Bandar Lampung, Indonesia 35145 ² Geological Survey Center of the Ministry of Energy

and Mineral Resources Diponegoro Street No.57, Bandung, Indonesia 40115 Corr. Author:

rahmat.caturwibowo@eng.unila.ac.id Abstract. Porosity and Permeability is an

essential petrophysical parameter of hydrocarbon reservoirs for oil and gas production. It's

can be immediately measured using cores taken from the reservoir in the laboratory and

deal with the high cost. Many empirical, statistical, and intelligent approaches were

suggested to predict permeability in un-cored wells based on wireline logs. The main

objective of this study is to predict the porosity and permeability values in a tight carbonate

reservoir. In this study, the calculation of permeability was done using the Schlumberger,

East, Morris Biggs Oil, Morris Biggs Gas, and PGS (Pore Geometry Structure) methods

based on core, logs, and CT-Scans data. The determination of porosity values from

CTScan performed on 20 core plugs from two data cores, each core plugs was plotted as

many as 15 points. The output is the CT-Porosity value that will be used for the distribution

of predictions of PGS permeability. Based on the result, porosity and permeability range value from 5 – 11%; 0.015 – 24.5 mD and presents a poor to fair reservoir quality.

Keywords: porosity, permeability, CT-Scan, CT-Porosity

1. Introduction Determination of reservoir rock properties is very important to better understand reservoirs. Some of these rock properties are porosity and permeability. Permeability plays an important role in the early life of the oil field and in carrying out reservoir characterization and description for reservoir management purposes because production is very dependent on permeability. Permeability calculation methods can be ¹ done using the Schlumberger, East, Morris Biggs Oil, Morris Biggs Gas methods and pore geometry structure (PGS). In determining the permeability value by the log method, using some log data in the form of gamma-ray log, resistivity, and neutron porosity hydrogen index (NPHI) and density (RHOB). Based on these log data, petrophysical analysis can be done in the form of determining porosity (ϕ), water saturation (S_w), permeability (k), and shale content (Vsh). ⁶ The amount of shale content in Indonesia is very large, so it is expected that in the next few years there will be many sources of oil and gas. It takes a long time to wait for the process of changing shale material into oil and gas [3].

The 9th International Conference on Theoretical and Applied Physics (ICTAP) Journal of Physics: Conference Series 1572 (2020) 012052 IOP Publishing
doi:10.1088/1742-6596/1572/1/012052

2 Previous research by raising the theme of rock type determination and permeability prediction made by Permadi and Wibowo (2013), that the geological and reservoir engineering aspects were highly considered. Where it is known that the geometry and pore structure can be applied in rock typing as well as being the basis in calculating permeability predictions [10]. ¹ The results of this research show that there is a close relationship between the similarity of pore architecture with similar geology (lithofacies and diagenesis). Yogi (2018) said, the method used in determining rock type will greatly affect the results of permeability calculations [12]. Permeability is the result of geological processes so that each type of rock in a reservoir has a unique permeability-porosity character. Therefore, determining the rock type must be done using

the right method, so that the predicted value of the permeability will be close to the real permeability value. The method that can be used to predict the value of permeability is the PGS approach. The PGS method is very good for grouping rock types, because the geometry distribution and pore structure, where the geometry and pore structure (pore architecture) is very influential in porosity and will be related to the results of prediction of permeability. Besides, in this method, the equation is obtained from the correlation of porosity, permeability, and irreducible water saturation (S_{wirr}). The purpose **1** of this study is to determine and analyze the value of permeability using the PGS method based on CT-Scan data and compared with other methods.

2 Geology **2** The North West Java Basin consists of two areas namely onshore and offshore in the north and south of the Java island. All areas are dominated by extensional faults with very little compressional structure. The basin is dominated by rift-related to faults which several depocenter structures (half-graben), the main depocenter being the Arjuna Sub-Basin and Jatibarang Sub-Basin. Other depocenter are Ciputat Sub-Basin and Pasirputih Sub-Basin. The depositors are dominated by tertiary sequences with thicknesses exceeding 5500 m. Important structures in the basin consist of various height areas associated with faulted anticline and horst block, folds on the descending part of the main fracture, keystone folding and striking at top of basement high. Compressional structures only occur at the beginning of the formation of the pre-rift in a relatively northwest-southeast direction in the Paleogene period [1]. The basement rocks in this basin are andesitic and basaltic igneous rocks which are in the Middle Cretaceous to Upper Cretaceous and Pre-Tertiary metamorphic rocks [11].

3 Pore Geometry Structure (PGS) Well Logging is a method used to measure physical parameters in various boreholes to the depth. Petrophysical analysis can be applied to determine and evaluate the formation **1** in the form of porosity, water saturation, and permeability that will be used to determine the next stage of exploration and production [6]. Permeability is indicated by k expressed in mD (mildarcy), which is the ability to flow from formation fluids. Permeability is very dependent on the grain size of the rock [5]. In the Log data, the permeability **23** of a rock depends on the

porosity and water saturation and can be calculated using equation 1 below: (1)

where k (mD); is the effective porosity (fraction); S_w (fraction); a is a constant

(Schlumberger = 10000, Morris Biggs Gas = 6241, Morris Biggs Oil = 62500, East = 8581);

b is a constant (Schlumberger = 4.5, Morris Biggs Gas = 6, Morris Biggs Oil = 6, East =

4.4); c is a constant (Schlumberger = 2, Morris Biggs Gas = 2, Morris Biggs Oil = 2, East =

2). In the PGS method, there are 2 stages: identification of the flow unit and prediction of

permeability. According to Yogi (2018), Integration of data from routine cores, special

cores, and geological

The 7th 9th International Conference on Theoretical and Applied Physics (ICTAP) Journal of Physics: Conference Series 1572 (2020) 012052 IOP Publishing

doi:10.1088/1742-6596/1572/1/012052 3descriptions can be used to group rock types

(rock typing) [12]. Classification of rock types based on lithofacies and secondary porosity

1 is based on the correlation between lithofacies, pore geometry and pore structures

(pore architecture). Pore geometry 2 or known as the average hydraulic radius is denoted

by , while the pore structure that explains all the internal structural features of the pores is

denoted by . The relationship between pore geometry and pore structure is shown in

equation 2 below: (2) or, (3) Plotting data as the dependent variable to as an

independent variable on the log-graph will produce a straight line with a positive slope of

0.5 and $v_p/v_b = 1$. By treating porous media as capillary tubes smooth winding and has a

very small wall thickness, can be derived as Kozeny's equation. In addition, the term in the

above equation implies that the medium is treated as a single fine capillary tube having $\phi = 1$.

This condition will cause fluid to flow with flow efficiency 1, meaning that there is no

delay in fluid flow at any point in the medium. Therefore, Equation 2 can represent an ideal

model of porous media having a very simple geometry and pore structure. When dealing

with real porous rocks, the presence of micro, meso, and macropores, pore contractions,

pore differences, and pore wall roughness will make fluid flow away from the ideal situation

[4]. The speed of fluid flowing can vary significantly from one pore location to another flow

stagnation and even occurs at the dead-end if possible, under real and complex conditions.

In other words, ¹⁶ the volume of fluid flowing per unit time from one position to another will be different. Therefore, it is expected that the flow efficiency will be smaller than 1. The following is the rock type equation for the real porous rock shown in equation 4: (4) where constant a is flow efficiency and exponent b is able to represent pore complexity [10]. In addition to porosity, irreducible water saturation will also affect ¹ the results of the calculation of permeability. Where permeability will be inversely proportional to irreducible water saturation and directly proportional to porosity. Based on the relationship of the three parameters, permeability determination can be done by getting an equation between permeability and water saturation then substituted on each rock type equation. The following is a general form of the equation between permeability, porosity, and irreducible water saturation [12]:

(5) substituting equation 5 to produces: (6)

substitute equation 4 to equation 6 will be: (7) (8)

The 9th International Conference ⁷ on Theoretical and Applied Physics (ICTAP) Journal of Physics: Conference Series 1572 (2020) 012052 IOP Publishing

doi:10.1088/1742-6596/1572/1/012052 4The final equation of the relationship between porosity, permeability, and irreducible water saturation ¹ that will be used in the

calculation of permeability as PGS permeability is shown in equation 9 below: (9)

with, (10) (11) (12) 4. Methods The stages of data processing in this

study are as follows: 1) calculation of the permeability value of the log data; 2) determination of rock type based on geological description; 3) determining the final permeability equation with the PGS approach; 4) distributing PGS from CT Porosity data; and 5) analyzing ¹ the results of the permeability calculations from the log data, cores, and PGS methods. The data used in this study are: AY-7 well core rock samples of 2 cores have 54 total plugs. Core 1 has 25 plugs at a depth of 1776.00 m - 1785.80 m and Core 2 has 29 plugs at a depth of 1929.18 m - 1939.08 m; Routine core data used are porosity and permeability. While the SCAL (Special Core Analysis) data used are irreducible water saturation; CT Scan data obtained from the CT number plotting of 15 points, has a total plot point of 286 points; Log data consisting of gamma-ray log, caliper,

spontaneous potential, ¹⁰ resistivity (LLD, LLS and MSFL), neutron porosity hydrogen index (NPHI), and density (RHOB). 5. Porosity prediction Interpretation of wells carried out at well AY-7 with a depth of 1776.00 - 1785.50 m has a thickness of 9.5 m (Zone 1) and 1929.18 - 1939.18 m has a thickness of 10 m (Zone 2). The shale volume parameter used for calculations on the AY-7 Well is the gamma-ray log, where the sand baseline value is located at the GRmin value and the shale baseline value is at GRmax respectively 149.94 gAPI and 11.19 gAPI. Based on the ¹⁰ calculation of shale volume that has been done, the result of Vsh calculation in Zone 1 is 5.43 - 63.55% while in Zone 2 it is 1.60 - 14.51%. Porosity is calculated by involving pre-calculated Vsh parameters and NPHI logs. Results Calculation of total porosity (PHIT) and effective (PHIE) in Zones 1 and 2 of AY-7 wells: for Zone 1, PHIT and PHIE are 11.32% and 4.99%, respectively. Whereas for Zone 2, PHIT and PHIE were 5.08% and 3.88%, respectively. The calculation results show that the PHIT value ¹⁶ is greater than the PHIE value, this indicates that the porosity in the reservoir is not interconnected. Water resistivity is a value of the type of water resistance to electric current. Determination of ¹⁰ the value of water resistivity can use the Pickett plot method by crossing the curve between PHIE (effective porosity) and Rt (formation resistivity; reading from the LLD Log curve), then drawing a line on the collection of the most points so that the Rw value is obtained. The Rw value obtained from the LLD/PHIE cross-plot is 0.373 ohm.m, with values a, m, and n respectively 1, 1.24, and 1.9. Based on the regional geological review ¹⁰ of the study area, the constituent lithology in the research target formation is the intersection between limestone and shale and sandstone and shale interchange. This shows that ² the formation of the research target cannot be said to be a clean zone, due to shale interruption. And ¹ the results of the calculation of the volume of impurity (volume of shale) that have been done previously showed quite large results, which is 1-28%. Therefore, the calculation of water saturation is done using the Simandoux Equation. Where the parameters used are effective porosity (\emptyset

doi:10.1088/1742-6596/1572/1/012052 5eff), formation water resistivity (R_w), formation resistivity (R_t) readings from the LLD log curve, shale resistivity (R_{sh}), and shale volume. A large water saturation value is not good in a reservoir, because if **9** the water saturation is large it will indicate that the zone has a lot of water content. This will affect the economics of a reservoir. In this study, obtained the saturation value of Zone 1 water is smaller than the dominant Zone 2 value of 100%. 6. Permeability prediction Permeability is calculated not only using the PGS method, but using 4 other permeabilities (log permeability), namely **1** Schlumberger, East, Morris Biggs Oil, and Morris Biggs Gas. Of the four permeabilities and validated with core data, accurate results for Zone 1 are Morris Biggs Gas permeability and Zone 2 is Timur permeability. According to Koesoemadinata (1980), the quality of permeability in a reservoir is divided into 4 categories, namely: less than 5 mD **18** is said to be tight; 5-10 mD is said to be sufficient (fair); 10-100 mD is said to be good, 100-1000 mD is said to be very good [7]. Based on these categories, the results of permeability calculations in Zones 1 and 2 of AY-7 Well can be categorized into tight permeability where **10** the value is less than 5 mD. The final display of log permeability calculations can be seen in figures 1 and 2. Figure 1. Quantitative Interpretation results of **17** permeability in Zone 1 According to Listiyowati (2018), CT values represent similarities with gray levels. Color-coded reconstructions where darker colors can be indicated as areas of low density, and indicate pores filled with air [8]. Gray level can indicate CT value, for the dark gray level is identified as pore and has a low CT value. **24** Black image shows pore (air), gray indicates low density of solid matrix, and bright white indicates higher density of solid matrix [2]. The porosity of CT is obtained from plotting CTnumber values using VoxcelCalc Plus v8.23a software **1** as many as 15 points per one data scanning results (along 1 m). The purpose of this plotting is to obtain the porosity value of the results from CT, then correlate with the core porosity value and then analyze **9** the accuracy of the values. This CT porosity data will be used to determine the distribution of PGS at each plotting point **1** in the prediction of permeability with the PGS approach.

doi:10.1088/1742-6596/1572/1/012052 6 Figure 2. Quantitative Interpretation results of permeability in Zone 2 The CT porosity calculations results do not differ significantly, it can be said the difference is still within reasonable limits. However, there are still some points that are a little far from the core porosity value. This difference is due to the fact that when plotting zones each point is not the same size, so that if the zone is too large the porosity will be calculated too. In addition, when encircling the zone of the tube cover the top depth section. Close this depth is made of metal, if 9 at the time of the zone plot of the CT number value is large so that the calculated porosity will also be large. 6.1. PGS approaches In permeability prediction, the empirical correlation obtained is the same as the theoretical derived equation for capillary tube models except the strength of the pore hydraulic diameter of less than 2. Based on this, it can be seen that the capillary model can 15 be used as an approach to characterize pore geometry and pore structure because the effective hydraulic diameter (pore geometry) derived can reflect the structure of the pore system. This model can also be used to identify rock types [9]. 1 In this study, the grouping of rocks was carried out using the PGS method and was based on the use of the PGS rock type curve. Rock type curve is obtained from the correlation between geological description, pore geometry and pore structure in log-log charts. This will show the character of rocks in each rock type, where the greater the geometric value and pore structure, the quality of a rock will be better. figure 3 is a plot result curve between geometry and pore structure. The figure shows the classification results based on rock texture or grain size. Can be seen in the figure, the grain size classification shows a complex distribution. There are 2 main divisions of grouping of rocks, namely: the first group that is in a green circle, shows that these rocks have the same characteristics, namely shaly limestone. Group 2, which is in a blue circle, shows similar characteristics, namely shaly limestone with stylolite. Seen in each circle there are several points that are outside the area or not the area (deviating from the group), for data that are in a green

circle due to that point there is no stylolite. While the data which is in the blue circle is caused because at that point there are stylolite and fractures. Next, determine the final rock type in the PGS curve. 3 Of the 2 groups of rock types, they are grouped again with their geological description characteristics such as rock names, grain size, and mineral types. The results of determining the rock type on the PGS curve are shown in figure 4.

The 7 9th International Conference on Theoretical and Applied Physics (ICTAP) Journal of Physics: Conference Series 1572 (2020) 012052 IOP Publishing

doi:10.1088/1742-6596/1572/1/012052 7 Figure 3. Item Size Plots on the PGS Curve

Figure 4. 3 Final Rock Type in the PGS Curve Based on the plot results from the geometry and pore structure in figure 5, the final rock type is obtained on the PGS curve with 4 groups.

Rock Type (RT) 1, dominated by shaly limestone with stylolite, coloured from light-dark grey and grain size from very fine to coarse. RT 2, dominated by shaly limestone with stylolite, dark-light grey, fine to very fine, and carbonated. RT 3, 3 dominated by shaly limestone with stylolite, dark-light grey, fine to very fine, and contains quartz minerals. RT 4, dominated by shaly limestone, dark-light grey, and fine-grained. RT 1 has the highest exponent value of 0.49 and decreases to the lowest value of 0.22 for RT 4. This exponent value represents the form factor and pore size distribution, while the constant does not represent anything. Table 1 is the result of PGS rock type classification and geological description. To determine the equation between permeability, 17 porosity, and irreducible water saturation it is necessary to substitute the equation between permeability and irreducible water saturation (Swirr) for each RT equation. By plotting the Swirr value against k on the semi log curve, the values m and n (constants and exponents) will be obtained.

5 The 9th International Conference on Theoretical and Applied Physics (ICTAP) Journal of Physics: Conference Series 1572 (2020) 012052 IOP Publishing

doi:10.1088/1742-6596/1572/1/012052 8Table 1. Classification of Rock Type and

Geological Descriptions PGS Rock Type Equation Geological Description PGS-1

RT-1 Dominated by shaly limestone with stylolite, coloured from light-dark grey and grain

size from very fine to coarse. PGS-2 RT-2 Dominated by shaly limestone with stylolite, dark-light grey, fine to very fine, and carbonated. PGS-3 RT-3 Dominated by shaly limestone with stylolite, dark-light grey, fine to very fine, and contains quartz minerals. PGS-4 RT-4 Dominated by shaly limestone, dark-light grey, and fine-grained. Based on semilog regression on the curve, the value of M (constant) is 0.59 and n (exponent) is 0.14. Previously, the results of the plot size of the grain on the PGS curve produced constants and exponents (a and b) for each rock type. These M, n, a, and b values will be used to calculate the values of A, B, and c using Equations 10, 11, and 12. These values A, B, and c will be used as constants and exponents in the PGS permeability equation. Table 2 is the result of calculating the values of A, B, and c for each rock type.

Rock Type	Equation	Swirr	vs k	M	n	a	b	A	B	c
RT-1	$Swirr = 0.5936 k^{-0.145}$	0.594	0.145	0.117	0.492	1.983	7.013	2.880		
RT-2	$Swirr = 0.5936 k^{-0.145}$	0.594	0.145	0.439	0.255	1.039	13.523	1.479		
RT-3	$Swirr = 0.5936 k^{-0.145}$	0.594	0.145	0.344	0.230	0.828	14.979	2.091		
RT-4	$Swirr = 0.5936 k^{-0.145}$	0.190	0.226	0.784	15.285	3.864				

Furthermore, to get the final equation the permeability prediction can use Equation 9. The permeability equation which is a function of the porosity and saturation of water is shown in table 3.

Permeability Prediction	Rock Type	Final Equation
	RT-1	
	RT-2	
	RT-3	
	RT-4	

The 9th International Conference on Theoretical and Applied Physics (ICTAP) Journal of Physics: Conference Series 1572 (2020) 012052 IOP Publishing
doi:10.1088/1742-6596/1572/1/012052 To get permeability prediction equations that can be applied to wells, PGS distribution can be done using Interactive Petrophysic software based on predetermined CT Porosity data. Using the fuzzy logic principle, with input data in the form of CT porosity data and 4 Rock Type groups, namely PGS-1 (RT1) to PGS-4 (RT-4). In the principle of fuzzy logic, there is a part that needs attention: the number of bins. In this study, the author tries number of bins 5, 10, and 15. The actual approach is bin 5. The results of the PGS distribution are then stored in ASCII format, to be used in calculating the PGS permeability of each CT depth data. The results of the

distribution of PGS for Zones 1 and 2 of AY-7 wells are shown in figure 5.

(a) (b) Figure 5. Results of PGS Distribution of AY-7 Well Data: (a) In Zone 1; and (b) in Zone 2 The PGS distribution that has been done is adjusted to the PGS permeability equation for each rock type. Calculation of PGS permeability can be done using the final equation of PGS permeability prediction. ¹ The results of the PGS permeability calculation for Zone 1 and 2 AY-7 wells are shown in Table 4. Based on table 4, the results of the PGS permeability calculation do not differ much or approach the core permeability values. The difference is still within reasonable limits. ²¹ However, there are

still some points that are a little far from the core permeability value. Table 4. Results of PGS Permeability Calculation Results in AY-7 Well

ZONE 1		ZONE 2	
Depth (m)	PGS (mD)	Depth (m)	PGS (mD)
1779.42	0.898	1782.4	0.072
1934.99	0.137	1779.63	0.063
0.047	0.042	1782.6	0.212
0.047	0.196	1932.44	3.091
0.41	1935.36	0.249	0.066
1779.9	0.127	0.024	1782.9
3.038	3	1932.54	1.587
0.578	1935.59	0.94	0.528
1780.1	0.154	0.062	1783.24
1.242	1.517	1932.63	24.148
24.161	1935.94	0.135	0.051
1780.4	0.058	0.054	1783.51
0.049	0.063	1932.94	0.033
0.957	1936.26	0.126	0.129
1780.63	6.082	6.069	1783.6
0.29	0.251	1933.01	0.022
2.541	1936.51	0.102	0.097
1780.87	0.226	0.284	1783.86
0.083	0.042	1933.07	0.229
0.15	1936.64	0.768	0.133
1781.3	0.461	0.497	1784.15
0.043	0.032	1933.13	1.431
0.567	1936.82	0.106	0.138
1781.4	0.03	0.031	1784.27
0.019	0.037	1933.49	0.064
0.118	1936.92	0.27	0.515
1781.66	0.021	0.039	1784.4
0.066	0.045	1933.64	0.035
0.085	1938.01	0.152	0.202
1781.9	0.026	0.041	1784.55
0.073	0.062	1933.83	0.061
0.121	1938.12	0.122	0.199
1781.95	0.086	0.07	1785.44
0.032	0.056	1934.4	0.015
0.26	1938.38	0.098	0.206

The ⁷ 9th International Conference on Theoretical and Applied Physics (ICTAP) Journal of Physics: Conference Series 1572 (2020) 012052 IOP Publishing
 doi:10.1088/1742-6596/1572/1/012052 ¹⁰After obtaining the results of Core, Log, and PGS permeability calculations, the next step is to compare the results of these calculations. The parameters used are ¹⁰ porosity and water saturation. For comparison of

porosity of CT computation results with core rock data (core) shown in figure 6a, it can be seen that the picture has a pretty good correlation. By performing a regression of the CT and Core porosity data, an equation with an R2 of 0.90 is obtained. Whereas the correlation between log porosity and core rock porosity 15 is shown in Figure 6b. It can be seen that there are still a lot of log data in the curve away from the core rock value, where the core rock porosity value is used as a reference in validating 9 the accuracy of the calculation results. By performing a log and core porosity data regression plot, an equation with R2 of 0.63 is obtained. Furthermore, the correlation between log porosity and CT porosity 15 is shown in figure 6c. It can be seen that there are still a lot of log porosity and CT porosity data in the curve. By doing a regression of Log and Core porosity data, an equation with a smaller R2 value compared to the previous two curves is 0.68.

(a) (b) (c) Figure 6. Comparison of Porosity Results in AY-7 Well: (a) Porosity CT vs Porosity Core; (b) Porosity log vs Porosity Core; and (c) Porosity log to Porosity CT Based on the 3 porosity comparison curves (Figure 6), the porosity value that is close to the calculation results from the laboratory (core data) is CT porosity which shows a good correlation and has a R2 value that 16 is greater than the curve equation of core porosity to log and porosity of log to CT. This vast difference in value can be caused due to 10 the calculation of the log results, the value taken is the average software calculation results. Whereas in core rocks, data is obtained from the calculation of each rock sample. 3 In the CT calculation results are more specifically obtained by plotting the zones in every 15 points on the core with a length of 1 m. This porosity value will affect 1 the calculation of permeability, where porosity is directly proportional to permeability. A comparison of the permeability of PGS predictions to core permeability is shown in figure 7a. Can be seen in the figure, the comparison between predicted permeability with core permeability has a good

The 7 9th International Conference on Theoretical and Applied Physics (ICTAP) Journal of Physics: Conference Series 1572 (2020) 012052 IOP Publishing

doi:10.1088/1742-6596/1572/1/012052 11correlation. The closer the data to the gradient is

worth one, the closer the predicted permeability value to **1 the permeability of the** core rocks. However, there are some points that move away from one or deviating gradient lines. Obtained R2 value on the core log permeability regression curve data with PGS permeability is 0.91. Figure 7b is a log permeability comparison curve to PGS permeability. Can be seen, the comparison between log permeability to PGS permeability has a pretty good correlation. **21 However, there is still** a lot of data that moves away from one or distorted gradient lines. The value of R2 obtained is 0.64. Next, figure 7c is the log permeability comparison curve to **1 the permeability of the** core rock. Can be seen in the picture below, the comparison between log permeability and core permeability has a correlation that is not good enough. Where there is still a lot of data scattered away from the gradient line with a value of one. R2 value obtained is small that is equal to

0.84. (a)

(b) (c) Figure 7. Comparison of Permeability

Results in AY-7 Wells: (a) PGS Permeability vs Permeability core; (b) Permeability log vs Permeability core; and (c) Permeability log vs **1 PGS Permeability Based on the** three permeability comparison curves (figure 7), the permeability value close to **the results of the** calculation of core rock is the PGS permeability shown by good correlation results, the R2 value is quite large compared to the curve equation of the core permeability to log and log permeability to PGS. Figures 8 and 9 show the final display of the log and PGS permeability calculations.

5 The 9th International Conference on Theoretical and Applied Physics (ICTAP) Journal of Physics: Conference Series 1572 (2020) 012052 IOP Publishing

doi:10.1088/1742-6596/1572/1/012052 12 Figure 8. Porosity and permeability comparison of CT, Core, PGS and Log on zone 1 for AY-7 Well Figure 9. Porosity and permeability comparison of CT, Core, PGS and Log on zone 2 for AY-7 Well 7. Conclusion The conclusions of this research are: 1) The value of permeability of Core Well AY-7 in this study is an average value of 0.86 mD, with a minimum value of 0.024 mD and a maximum value of 24,16 mD. The average permeability value of PGS AY-7 is 0.89 mD, with a minimum value of 0.01 mD and a maximum value of 24.15 mD. The log permeability value

of the AY-7 Well in this study was an average of 0.59 mD, with a minimum value of 0.002 mD and a maximum value of 5,57 mD. Permeability calculation results show that permeability is classified as tight; 2) **1** Based on the results of core, log, and PGS

permeability calculations, the permeability values close to the results of calculations from the laboratory (core data) are PGS permeability. 8. References [1] **2** Darman, H. dan

Sidi, F. H. 2000. *An Outline of The Geology of Indonesia*. Makalah Ikatan Ahli Geologi

Indonesia (IAGI). Vol 20th. Indonesia. [2] Demir, M. dan **4** Demiral, B. 2001. Effect of

Pore Size Distribution On Porosity Measurement By Computerized Tomography. Paper Society of Core Analysis. SCA 2001-49.

20 The 9th International Conference on Theoretical and Applied Physics (ICTAP) Journal of Physics: Conference Series 1572 (2020) 012052 IOP Publishing

doi:10.1088/1742-6596/1572/1/012052 13[3] Dewanto, O., Mulyatno, B.S., Rustadi and

Wibowo, R.C. 2017. **6** Determining the Temperature of Shale Material Conversion Into

Crude Oil Based on Organic Clay and Organic Carbonate Test Outside

Reservoir. International Journal of Mechanical and Mechatronics Engineering, IJMME.

Vol:17 No:05. ISSN: 2077-124X (Online), 2227-2771 (Print). Page: 84-89. [4] Gardner,

W.R., 1958. Some Steady State Solutions Of The Unsaturated Moisture Flow Equation With Application To Evaporation From A Water Table. Soil Science. 85: 228232.

[5] Harsono, A., 1994. Teknik Evaluasi Log. IATMI. Schlumberger Data Services.

Jakarta. [6] Irawan, D. dan Utama, W., **11** 2009. Analisis Data Well Log (Porositas,

Saturasi Air, dan Permeabilitas) untuk Menentukan Zona Hidrokarbon, Studi Kasus:

Lapangan "ITS" Daerah Cekungan Jawa Barat Utara. Jurnal Fisika dan Aplikasinya vol. 5,

No.1. Surabaya: Institut Teknologi Sepuluh November. [7] Koesoemadinata, R.P., 1980.

Geologi Minyak dan Gas Bumi. Bandung: Institut Teknologi Bandung. 296 p. [8]

Listiyowati, L.N., 2018. Perbandingan Analisis Porositas Porites Menggunakan Teknik

MicroCT dan Optik. Riset Geologi dan Pertambangan, vol. 28, No.1 (91-100). Bandung. [9]

Permadi, P., and Susilo, A. 2009. **4** Permeability Prediction and Characteristics of Pore

Structure and Geometry as Inferred from Core Data. Paper Society Petroleum Engineers

(SPE) 125350-PP. Abu Dhabi. [10] Permadi, P. dan Wibowo, A.S., 2013. Kozeny's Equation For Better Core Analysis. Paper Society of Core Analysis (SCA) 2013-048. International Symposium of The Society of Core Analysis. Napa Valley, California. [11]

Sinclair, S., Gresko, M., and Sunia, C., 1995. 12 Basin Evolution of the Ardjuna Rift System and its Implications for Hydrocarbon Exploration, Offshore Northwest Java, Indonesia. Indonesian Petroleum Association (IPA) Proceedings, 24th , hal 147162.

Annual Convention, Jakarta. [12] Yogi, A. 2018. Estimasi Permeabilitas dengan Beberapa Metode Karakterisasi Reservoar Untuk Formasi Talang Akar. Jurnal Lembaga Publikasi Minyak dan Gas Bumi, Vol. 52 No.1, April 2018 : 3-5. Jakarta Selatan: PPPTMGB

LEMIGAS. Acknowledgment The author would like 22 to thank all those who have helped by providing useful direction, discussion and support during the course of this research.

Sources

1	https://www.academia.edu/Documents/in/Porosity_and_Permeability_in_Reservoirs INTERNET 6%
2	https://sciencetechnology3583.blogspot.com/2019/04/north-west-java-basin.html INTERNET 2%
3	https://www.coursehero.com/file/pkoc409/Next-determine-the-final-rock-type-in-the-PGS-curve-Of-the-2-groups-of-rock/ INTERNET 2%
4	https://iopscience.iop.org/article/10.1088/1742-6596/1572/1/012052 INTERNET 2%
5	https://iopscience.iop.org/article/10.1088/1742-6596/1572/1/012046/pdf INTERNET 1%
6	https://www.academia.edu/67307630/Determining_the_Temperature_of_Shale_Material_Conversion_Into_Crude_Oil_Based_on_Organic_Clay_and_Organic_Carbonate_Test_Outside_Reservoir INTERNET 1%
7	https://appliedphysics.physicsmeeting.com/ INTERNET 1%
8	https://iopscience.iop.org/article/10.1088/1742-6596/1572/1/012052/pdf INTERNET 1%
9	https://petrowiki.spe.org/Water_saturation_determination INTERNET 1%
10	https://link.springer.com/article/10.1007/s42452-020-3100-x INTERNET 1%
11	http://ejournal.mgi.esdm.go.id/index.php/bomg/article/view/659 INTERNET <1%
12	https://iopscience.iop.org/article/10.1088/1742-6596/1572/1/012052/meta INTERNET <1%
13	https://iopscience.iop.org/article/10.1088/1742-6596/1222/1/012010/pdf INTERNET <1%
14	https://www.apem-journal.org/ INTERNET <1%

- 15 https://wiki.aapg.org/Well_log_analysis_for_reservoir_characterization
INTERNET
<1%
-
- 16 <https://openstax.org/books/university-physics-volume-1/pages/14-5-fluid-dynamics>
INTERNET
<1%
-
- 17 <https://www.netl.doe.gov/sites/default/files/2018-02/FE00006821-Appendix-D---Horizontal%20and%20Vertical%20Permeability.pdf>
INTERNET
<1%
-
- 18 <https://byjus.com/physics/fluid-flow/>
INTERNET
<1%
-
- 19 <https://iopscience.iop.org/issue/1742-6596/1572/1>
INTERNET
<1%
-
- 20 <https://iopscience.iop.org/year/1742-6596/Y2020>
INTERNET
<1%
-
- 21 <https://courses.lumenlearning.com/geo/chapter/reading-porosity-and-permeability/>
INTERNET
<1%
-
- 22 <https://elc.polyu.edu.hk/fyp/html/ack.htm>
INTERNET
<1%
-
- 23 <https://wgnhs.wisc.edu/maps-data/data/rock-properties/understanding-porosity-density/>
INTERNET
<1%
-
- 24 <https://iopscience.iop.org/article/10.1088/1755-1315/62/1/012022/pdf>
INTERNET
<1%
-