Summary

PAPER	NAME

IOP_Conf._Optimization of matrix comp ositions.pdf

AUTHOR

Jamiatul Akmal

WORD COUNT 2324 Words	CHARACTER COUNT 11186 Characters
PAGE COUNT	FILE SIZE
8 Pages	855.3KB
SUBMISSION DATE	REPORT DATE
Sep 22, 2022 9:38 PM GMT+7	Sep 22, 2022 9:39 PM GMT+7

• 18% Overall Similarity

The combined total of all matches, including overlapping sources, for each database.

- 7% Internet database
- Crossref database
- 7% Submitted Works database

• Excluded from Similarity Report

• Manually excluded sources

Crossref Posted Content database

16% Publications database

Manually excluded text blocks

PAPER • OPEN ACCESS

Optimization of matrix compositions of AI_2O_3 , SiO_2 , Caolin, and CaO on the mechanical properties of a geopolymer composite with short carbon fiber

To cite this article: J Akmal et al 2019 IOP Conf. Ser.: Mater. Sci. Eng. 602 012079

View the article online for updates and enhancements.

Optimization of matrix compositions of Al₂O₃, SiO₂, Caolin, and CaO on the mechanical properties of a geopolymer composite with short carbon fiber

J Akmal¹, M Badaruddin¹, M K Ismoyo¹, and S D Yuwono²

¹Department of Mechanical Engineering University of Lampung ²Department of Chemical Science, University of Lampung Jalan Prof. Soemantri Brodjonegoro No.1 Bandar Lampung, 35145, Indonesia

E-mail: jamiatulakmal@gmail.com

Abstract. Geopolymer is a material synthesized from a base material with a large amount of silica and alumina. Geopolymer can be used as an affordable alternative as a substitute for Portland cement, reducing pollution, and resistant to fire under certain conditions. But ³ ure geopolymer has not been widely used in industrial areas because overall it has ³ ow toughness and mechanical properties when compared to metals or ceramics. This research was conducted to produce geopolymer composite material with good mechanical properties and can be applied as a material in making environmentally friendly pipes, by identifying the influence of the composition of the geopolymer base material using the Taguchi method. Generate Geopolymer composites with the addition of Silica Powder and random short carbon fiber have good mechanical properties, from the results of the experiment produced the best flexural strength in T9 specimens with details of the composition of Silica Powder (27 g), Kaolin (55 g), CaO (6 g), and Carbon Fiber (13 gr) with a flexural strength of 41.46924655 MPa and flexural modulus 6 GPa.

1. Introduction

Geopolymer is a material synthesized from a base material with a large amount of silica and alumina. Geopolymer can be used as an affordable alternative as a substitute for Portland cement, reducing pollution, and resistant to fire under certain conditions. But our geopolymer has not been widely used in industrial areas because overall it has row toughness and mechanical properties when compared to metals or ceramics.

Many studies reveal that geopolymers can be used as composite matrices 3. improve their mechanical properties. According to Shaikh., (2013) geopolymers that are used as a matrix reinforced with short fibers have flexural strength and good tensile strength without regard to the type of fiber [1]. This was strengthened by a study conducted by Jingkun et al. (2015) that geopolymers reinforced with 5 mm SiC fibers had accural strength and fracture work which was 5.6 and 63 times higher than pure geopolymers [2]. Also, According to Mukhallad et al., 2018 The addition of fiber increases the strength characteristics of geopolymer composites, for example, the presence of steel fibers and polyvinyl alcohol fibers increases the flexural strength of geopolymer composites of 31.45% (11.116 MPa) and 39.84% (11.825 MPa, respectively) [3].

Content from this work may be used under the terms of the Creative Commons Attribution 3.0 licence. Any further distribution of this work must maintain attribution to the author(s) and the title of the work, journal citation and DOI. Published under licence by IOP Publishing Ltd 1 So far, geopolymer composites are usually used only for building materials, instead of Ordinary Portland Cement (OPC). This research was conducted to produce geopolymer composite material with good mechanical properties and can be applied as a material in making environmentally friendly pipes, by replacing sand/coral with reinforcing fibers. Identifying the influence of the composition of the geopolymer base material using the Taguchi method.

Materials and Experiment

2.1. Materials

Materials used in the manufacture of geopolymers are kaolin, silica powder, CaO, carbon fiber, and activators. The chemical composition of K is investigated by XRF (X-Ray Florence) testing, and the respective content is shown in **Table 1**. Another material is commercial silica powder, carbon fiber type medium (1.56 kg / m3), Calcium Oxide (CaO) and activator Sodium Hydroxide (NaOH).

Table 1. Chemical Composition (70) of Kaohin[4]												
Sampel	Si	Al	Fe	Ti	Zr	Mn	Sb	Zn	Sn	Ni	Pb	Ga
Kaolin	57,6	37,2	3,82	1,23	0,1	-	-	0,04	-	0,04	-	0,02

Table 1. Chemical Composition (%) of Kaolin[4]

2.2. Preparation of Geopolymer Composite

In geopolymer composite preparation, several steps must be prepared. The first step is to prepare a solution of Sodium Hydroxide (NaOH) 14 M, Sodium Hydroxide (NaOH) in the form of dissolved crystals by mixing it with Aquades solution. The next step is to prepare geopolymer forming materials such as Silica Powder (Si), Caolin, Calcium Oxide (CaO), and Carbon Fiber(CF) as seen in **Table 2**. In this study, we used the Taguchi experimental design as seen in **Table 3** to determine the composition of the geopolymer.

Level	Si(g) (A)	Caolin (g) (B)	CaO(g) (D)	CF(g) (E)
1	23	60	4	13
2	25	55	6	15
3	27	50	9	18

Table 2. Matrix compositions used in present research

The nine samples prepared in this study were made with a variety of different compositions referring to Table 2. The orthogonal matrix for the nine samples is shown in Table 3. The samples are symbolized by T1, T2, etc. shown in Table 3.

Mix	2	В	С	D
T1	1	1	1	1
T2	1	2	2	2
Т3	1	3	3	3
T4	2	1	2	3
T5	2	2	3	1
T6	2	3	1	2
T7	3	1	3	2
T 8	3	2	1	3
Т9	3	3	2	1

Table 3. Experimental design taguchi Orthogonal matrix L9(3⁴)

The lext step is mixing the powder materials: Silica Powder, kaolin, CaO, and CF until evenly distributed. Then add activator solution, with the ratio of powder to the activator solution is 30% After stirring evenly, put the mixture into an 80x6x8 mm mold and press at 1200 Psi for about 30 minutes. Geopolymer material is then cured with temperature 30-35 °C for \geq 28 days.

2.3. Experiment Testing

Rectangular bars with size (80x6x8) mm subjected to the three-point bending test(based on ASTM C1161)to determine the strength and flexural modulus[5], as shown in Fig. 1. The test machine used is MTS Landmark (capacity 100kN) with loading speed of $\frac{1}{2}.0 \text{ mm}$ / min. Flexural strength can be determined by Eq. (1).

$$\sigma_f = \frac{3.P_m.S}{2.W.D^2} \tag{1}$$

IOP Publishing

Where σ_{jis} dexural strength (MPa), P_m is ultimate load (N), S is the span of the sample, W is the specimen with and D is the specimen thickness. The flexural modulus was computed using the initial slope of the load-displacement curve, $\left(\frac{\Delta P}{\Delta x}\right)$, using the Eq. (2)



Figure 1. The threepoint bend test

3. Results and discussion

There were nine samples tested, and each sample consisted of three specimens, as seen in **Table 4**. **Figure 2** and **Figure 3** show the best composition (Flexural Strength) is on the composition of T9 which is 41.48 MPa with an average modulus of elasticity of 6 GPa. Composition with the second best value (Flexural Strength) is at T4 which is 32.11 MPa with ⁷/₄ modulus of elasticity of 3 GPa Furthermore, the third best composition with Flexural Strength is at T6 which is 29.67 MPa with ⁷/₄ modulus of elasticity of 4 GPa.

Table ¹³ . Flexural Strength Test Results							
					Average Flexural Strength		
Eks	Silica	Kaolin	CaO	Carbon Fiber	(MPa)		
T1	23	60	4	13	18,54		
T2	23	50	6	15	18,26		
T3	23	55	9	18	15,37		
T4	25	60	6	18	32,11		
T5	25	50	9	13	28,26		
T6	25	55	4	15	29,66		
T7	27	60	9	15	24,75		
T8	27	50	4	18	19,53		
Т9	27	55	6	13	41,47		



Figure 2. Graph of the results of flexural strength testing



Figure 3. The lexural modulus of the geopolymer composite

Figure 4 is a graph of the effect of each composition on the mechanical properties of geopolymer composites, which in this graph can see the effect of composition based on the average results of geopolymer flexural strength and standard deviation.



Figure 4. Graph of the effect of each composition on the flexural strength of geopolymer composites (a) Silica Powder, (b) Kaolin, (c) CaO, (d) Carbon Fiber

Level	Silica	Kaolin	CaO	Carbon Fiber
1	24,03	25,71	25,96	28,12
2	29,13	28,22	28,78	26,81
3	27,53	26,77	25,96	25,76
Delta	5,11	2,52	2,82	2,35
Rank	1	3	2	4

Table 5. Value of the response S / N ratio Larger the better

To see the Rank value of each composition of the geopolymer flexural strength can be seen in **TABLE 5.** Silica has the highest influence on the flexural strength of geopolymer composites at level 2, namely on silica with a weight of 25 g, then CaO (Calcium oxide) at level 2 with a weight of CaO

of 6gr, then Kaolin at level 2 with a weight of 55 gr, and the last one is carbon fiber at level 1 with a weight of 13 gr.

The SEM-EDX analysis was used to evaluate the surface morphology of Synthesized geopolymer, focusing on particle shape. FIGURE 5 and TABLE 6 respectively show the surface morphology of the geo-polymer with a carbon fiber content of 0 and 15%. EDS analysis in the white particle (shown in "B" letter) shows that an element of O, Na, and Si are a large number of compositions.

Secondary electron image (SEI) on surface geopolymer composite from sample T9 is shown in Fig. Xa. Cavities are seen clearly in the image of SEI of Fig. Xa. The carbon fiber shows the low bonding with the matrix. The matrix compromises of Al, Si, Ca oxides is evident with EDX results in the Table. Xa. Also, small particles are attributed to the sodium and calcium oxides, which do not interact with the matrix. These particles are cause debonding carbon fiber in geopolymer composite. To investigation of surface fracture of composite geopolymer, a similar sample T9 is appropriately considered to elucidate the morphology surface fracture of material. The SEI of surface fracture of T9 sample is displayed in Fig. Xb. It can be observed in Fig. Xb that debonding of fiber and cavities are responsible for the weakness of strength composite.



Figure 5. SEI images of (a) surface morphology of the geopolymer composite from sample T9 with EDX results and (b) fractography of sample T9 after the flexural test.

El	AN	Series	unn. C [wt.%]	norm. C [wt.%]	Atom. C [at.%]	Error	(1 Sigma) [wt.%]
0	8	K-series	25.89	29.87	47.42		4.07
Au	79	M-series	20.20	23.31	3.01		0.86
Si	14	K-series	12.00	13.85	12.53		0.56
Al	13	K-series	9.51	10.98	10.33		0.50
Ca	20	K-series	6.92	7.99	5.06		0.30
Na	11	K-series	6.81	7.86	8.68		0.49
С	6	K-series	5.32	6.14	12.98		1.47
		Total:	86.65	100.00	100.00		

Table 6. Geo-polymer with carbon fiber content

4. Conclusion

Geopolymer composites with the addition of Silica Powder and random short carbon fiber have good mechanical properties, from the results of the experiment produced the best flexural strength in T9 specimens with details of the composition of Silica Powder (27 g), Kaolin (55 g), CaO (6 g), and Carbon Fiber (13 gr) with a flexural strength of 41.47 MPa.

References

- [1] ASTM C1161 1990 Standard Test Method for Flexural Strength of Advanced Ceramics at Ambient Temperature, Annual Book of ASTM Standards 15 333-339.
- Jingkun Y. Peigang H. Dechang J. Xu L. Shu Y. Delong C. Zhihua Y. Xiaoming D. Shengjin W. Yu Z. 2015 SiC fiber reinforced geopolymer composites, part1: short SiC fiber, Jurnal Ceramics International. http://dx.doi.org/10.1016/j.ceramint.12.067.
- [3] Mukhallad M. Al-mashhadani Orhan C. Yurdakul A. Mucteba U. Savas E. 2018 Mechanical and microstructural characterization of fiber reinforced fly ash based geopolymer composites. Journal Construction and Building Materials **167** 505–513.7
- [4] Zaheer M. Nazir K. Yifei H. Hong H. Faiz U. Ahmed S. Kewei L. 2018 *Mechanical properties* of ambient cured high-strength plain and hybrid fiber reinforced geopolymer composites from triaxial compressive tests. Journal Construction and Building Materials **185** 338–353.
- [5] Shaikh F. Uddin A. 2013 *Review of mechanical properties of short fiber reinforced geopolymer composites*. Journal Construction and Building Materials **43** 37–49.
- [6] Suwanto E. K. 2018 Effect of Addition of Calcium Oxide and Carbon Fiber to the Mechanical Properties of Geopolymer Composites. Thesis, Faculty of Engineering, LAMPUNG UNIVERSITY, Bandar Lampung.

• 18% Overall Similarity

Top sources found in the following databases:

- 7% Internet database
- Crossref database
- 7% Submitted Works database
- Crossref Posted Content database

• 16% Publications database

TOP SOURCES

The sources with the highest number of matches within the submission. Overlapping sources will not be displayed.

e3s-conference	es.org
Dechang Jia, Pe Crossref	eigang He, Meirong Wang, Shu Yan. "Geopolymer and G
Jingkun Yuan, F Crossref	Peigang He, Dechang Jia, Shu Yan, Delong Cai, Lanlan X
tandfonline.con	n
scribd.com	
University of Wa	ales Swansea on 2010-04-26

9	etd.uasd.edu Internet	<1%
10	chalcogen.ro Internet	<1%
11	Kennesaw State University on 2006-09-15 Submitted works	<1%
12	downloads.hindawi.com Internet	<1%
13	Eastern Mediterranean University on 2011-10-17 Submitted works	<1%

Excluded from Similarity Report	
 Manually excluded sources 	 Manually excluded text blocks
EXCLUDED SOURCES	
J Akmal, M Badaruddin, M K Ismoyo, S D Y ^{Crossref}	uwono. " Optimization of matrix co 71%
Universitas Muhammadiyah Surakarta on 2 Submitted works	2018-10-18 66%
repository.lppm.unila.ac.id	15%
digilib.unila.ac.id Internet	6%
repo.unand.ac.id	<1%
N Doğan-Sağlamtimur, H Öznur Öz, A Bilgil ^{Crossref}	, T Vural, E Süzgeç. "The effect of a <1%
M Szechyńska-Hebda, J Marczyk, C Ziejew ^{Crossref}	ska, N Hordyńska, J Mikuła, M Heb <1%
EXCLUDED TEXT BLOCKS	

IOP Conference Series: Materials Science and EngineeringPAPER • OPEN ACCESS...

J Akmal, M Badaruddin, M K Ismoyo, S D Yuwono. " Optimization of matrix compositions of Al 0 , Si0 , Cao...

of Mechanical Engineering University of Lampung

A Su'udi, J Akmal, N Tanti, Arizon. "Using Geopolymer Composites for Heat and Corrosion Resistant Pipes", ...

University of Lampung Jalan Prof. Soemantri

R A Kausar, Buhani, Suharso, A Setiawan. "Synthesis and characterization exopolysaccharide from algae S...

ASTM C1161

Aksel, C.. "Fracture behaviour of magnesia and magnesia-spinel composites before and after thermal sho...

SiC fiber reinforced geopolymer composites

Jingkun Yuan, Peigang He, Dechang Jia, Shu Yan, Delong Cai, Lanlan Xu, Zhihua Yang, Xiaoming Duan, Shen...

Ceramics International. http://dx.doi.org/10.1016/j.ceramint

coek.info

Mukhallad M. Al-mashhadani Orhan

Alaa M. Rashad. "Effect of steel fibers on geopolymer properties - The best synopsis for civil engineer", Con...

2018 Mechanicaland microstructural characterization of fiber reinforced fly ash ba...

Nawar Ali, Orhan Canpolat, Yurdakul Aygörmez, Mukhallad M. Al-Mashhadani. "Evaluation of the 12-24 mm ...

2018 Mechanical properties of ambient cured high-strength plain and hybrid fiber r...

research.curtin.edu.au

A. 2013 Review of mechanical properties of short fiber reinforced geopolymercom...

Universiti Putra Malaysia on 2019-02-14

Suwanto E. K. 2018 Effect of Addition of Calcium Oxide and Carbon Fiber to the M...

A Su'udi, J Akmal, N Tanti, Arizon. "Using Geopolymer Composites for Heat and Corrosion Resistant Pipes", ...

Caolin, and CaO onthe mechanical properties of a geopolymer composite with sho... A Su'udi, J Akmal, N Tanti, Arizon. "Using Geopolymer Composites for Heat and Corrosion Resistant Pipes", ...

To cite this article

sipeg.univpancasila.ac.id

Conference on Innovation in Technology and Engineering ScienceIOP PublishingIO...

University of California, Merced on 2020-12-12

Caolin, and CaO on the mechanical properties of a geopolymercomposite with shor...

A Su'udi, J Akmal, N Tanti, Arizon. "Using Geopolymer Composites for Heat and Corrosion Resistant Pipes", ...

3].Content from this work may be used under the terms of the Creative Commons ...

www.scribd.com

to determine the strength and flexural modulus

A Su'udi, J Akmal, N Tanti, Arizon. "Using Geopolymer Composites for Heat and Corrosion Resistant Pipes", ...

1. Chemical Composition (%) of Kaolin

docplayer.info

The addition of

avesis.yildiz.edu.tr