KORESPONDENSI THE INTERNATIONAL CONFERENCE ON THEORETICAL AND APPLIED PHYSICS 2019 (ICTAP2019)

1. [ICTAP2019]Your paper has been uploaded



Identification of biogenic gas reservoir zone using log, petrophysics and geochemical data in S-1 well of Nias basin, north Sumatera

O Dewanto¹, Maulina¹, and **T** B Nainggolan²

¹ Geophysics Engineering, Engineering Faculty, University of Lampung, Bandar Lampung 35145, Indonesia

² Marine Geological Research and Development Center, Jalan Dr. Djunjunan No.236, Bandung 40174, Indonesia

E-mail: ordas.dewanto@eng.unila.ac.id

Abstract. The fore-arc basin has been become a target of reservoir searching for a long time based on previous expert studies, where the indications of Late-Miocene carbonate age that could act as a hydrocarbon reservoir was found. S-1 Well located in the Nias Basin, one of the fore-arc basin located in West of Sumatera. As the object of this study, it is hoped that the hydrocarbon reservoir in the fore-arc basin is expected to be discovered and to identify the characteristics of rocks that potential to become hydrocarbon reservoirs. Geochemical data becomes supporting data regarding the presence of gases that are identified as biogenic gases because of the content of methane as the main composition. Identification of the existence of reservoir zones and source rock is done by qualitative interpretation of log data from the S-1 well. Then, the petrophysical parameters are analyzed in the form of shale volume (Vsh), effective porosity, resistivity water (Rw), and water saturation (Sw) to determine the type of reservoir's fluid. The results of the interpretation indicated that the presence of biogenic gase was detected in Late-Miocene with limestone lithology with Sw value 39.90 - 41.51 %.

Keywords: petrophysical, shale volume, effective porosity, water saturation

1. Introduction

The existence of shale material in Indonesia is indeed quite a lot, so it is estimated that in the next few years there will be many sources of oil and gas [4]. However, the process of changing material into oil and gas requires a very long time [4] so that using oil and gas is increasingly rare and difficult to do. This makes biogenic gas become a solution as an alternative energy source to replace the using of oil and natural gas. Biogenic gas is an environmentally friendly type of fuel because it produces less carbon dioxide than other types of fuel. In addition, the investment costs of biogenic gas are cheaper than non-conventional gas because of its more general existence of 1,000 m on the sea bed, so researchers are now more focused on biogenic gas research that is more profitable to do.

Biogenic gas is a flammable hydrocarbon gas, has the shortest carbon chain (C1) so it is the lightest gas, which is about 0.7 lighter than air [14]. Therefore, if used as an energy source, biogenic gas is a type of fuel that is environmentally friendly. Biogenic gas is a gas with a methane content> 98% and has a low S and CO2 content and can be detected in the presence of the carbon isotope δ 13C CH4

1

Comment [u1]: Must be alphabetic

IOP Publishing	Journal Title
Journal XX (XXXX) XXXXXX	https://doi.org/XXXX/XXXX

which is -62 to -66% [8]. Biogenic gas contained in this earth almost reaches 20% of all natural gas sources [14] but its presence is spread in small gas bags of various sizes and at varying depths [10].

The formation of this gas occurs in the diagenetic phase where in this phase forms the source rock which is thermally immature. Methane gas is formed with the following main processes [15]:

- 1. Acetate bacterial fermentation in the chemical-rich sedimentary layer (gas charged sediment) chemically: $CH_3COOH \rightarrow CH_4 + CO_2$.
- 2. The process of reducing CO2 by bacteria from naturally occurring volcanic or magmatic rocks: $CO_2 + 2H_2O \rightarrow CH_4$.

The Nias Basin, a fore arc basin, characterizes a cool basin with a smaller geothermal gradient up to the average [8]. This affects the process of maturation of existing host rock. Because the geothermal gradient or heat flow is low, the heat received by the rocks is also small so that the Miocene-aged parent rock in this basin is generally immature. However, in older or deep-buried rocks it might reach maturity. Temperature can affect organic substances contained in sediments where an increase in temperature will convert heavy petroleum into light petroleum, then condensate and finally only gas [4].

Determination and analysis of reservoir parameters can be done by two methods, namely core analysis in the laboratory and interpretation of log data [11]. As for this research, a log data interpretation in the form of a quick-look qualitative interpretation and a quantitative interpretation in the form of petrophysical analysis is carried out in an effort to determine the detailed conditions of a petroleum system. Petrophysical analysis itself is a process that is carried out to validate the hydrocarbon density and determine the characteristics of the hydrocarbon reservoir and source rock.

2. Research Method

2.1 Reservoir Qualitative Interpretation

Qualitative reservoir interpretation is done by lithology zoning and hydrocarbon prospect area analysis using gamma ray, resistivity, RHOB and NPHI logs. First, a quick-look reservoir zone identification is based on NPHI and RHOB log separations. This separation indicates the existence of a reservoir where the reservoir has the characteristics of a low NPHI and RHOB values. Then the existence of a hydrocarbon reservoir is also characterized by a medium resistivity (Rt) value for oil and a high resistivity value for gas. In addition, the value of gamma ray is also important in identifying the quantity of clay found in rocks. The gamma ray log records the gamma ray radiation of rocks which shows the radioactive intensity in it. Clay minerals contain a large quantity of radioactivity and high clay content is found in claystone or shale lithology.

2.2 Reservoir Quantitative Interpretation

Once the hydrocarbon reservoir zone is identified through a quick-look analysis, a full-analysis is carried out in the form of petrophysical analysis through quantitative interpretation. To conduct petrophysical analysis, the shale content of rocks in the study area is a parameter whose value must first be determined. Calculation of clay content in S-1 Wells uses the Larionov tertiary equation because the age of the rock is relatively young based on the stratigraphy of the existing Nias Basin as follows [1]:

$$Vs = 0.08336 \left(2^{3.7} x^{\text{IGR}} - 1\right) \tag{1}$$

Then porosity (\emptyset) calculation using the equation as follows [15]:

$$\phi_e = \sqrt{\frac{\phi_{Ncor}^2 + \phi_{Dcor}^2}{2}} \quad (2)$$

Resistivity water (Rw) determination by plotting pickett plots in the software Interactive Petrophysics in areas filled with water (Sw=1). This zone is characterized by a very low resistivity

Journal Title https://doi.org/XXXX/XXXX

(Rt) value and coinciding with the NPHI and RHOB log curves. Then calculating water saturation (Sw) using the Indonesian Sw equation so that it does not neglect the presence of impurities contained in rock formations as follows:

$$\frac{1}{\sqrt{R_t}} = \left(\sqrt{\frac{\phi e^m}{a \times R_w}} + \frac{V_{sh}^{1-0.5V_{sh}}}{\sqrt{R_{sh}}}\right) \times S_w^{\frac{n}{2}}$$
(3)

2.3 Source Rock Qualitative Interpretation

For qualitative interpretation of source rock, gamma ray logs, resistivity logs and sonic logs are used. Based on the separation form of the sonic and resistivity log curves, the source rock type and its presence can be known in the well. This bedrock is usually in shale or siltstone lithology which has impermeable rock characteristics with high GR values, very high sonic log values and low value of resistivity logs.

The resistivity and sonic logs are overlaid to make it easier to see the shape of the separation. The first rule that needs to be known is when the GR (or SP) deflection to the left means the zone is clean and reservoir rock can be indicated. When the GR is deflected to the right, it indicates shale lithology (not characteristic of reservoir rocks). Then, the second rule is the porosity log (in this case the sonic log) is set on a high to low scale. Then the third rule is the resistivity log set on a low to high scale. High resistivity indicates the presence of hydrocarbons or low porosity, while low resistivity indicates an indication of shale or water zone [2].

The separation between resistivity log and DT log shows anomaly. When separation is formed to the right of the baseline it can be estimated that the separation shows the existence of source rock, and the rock is mature (mature). Whereas the separation formed to the left of the baseline shows that the depth is estimated as source rock, but immature, or as coal, and other non-source rock. Mature source rock has characteristics of high resistivity value, and high sonic log, while immature source rock has characteristic value with low resistivity value and not too high sonic log. Large log resistivity and sonic log separations are called Δ LogR [7].

2.4 Distribution Area of Biogenic Gas Reservoirs Modelling

Qualitative interpretation of source rock zones based on the overlay of DT and resistivity logs, and the biogenic gas reservoir based on quantitative interpretation and model of S-1 well can be identified.

3. Result and Discussion

3.1 Result of Reservoir Zone Identification

S-1 well has a total depth of 6990 ft. The presence of gas can be identified using qualitative log interpretation using gamma ray log, resistivity log, and separation between RHOB and NPHI logs as shown in **Figure 1** and **Figure 2**. In this well, reservoirs were identified in two zones, at depths of 5026-5130 ft, and 5198-5216 ft.

This is also evidenced by the small gamma ray log response in the both zones, namely in the range of 20 - 73 API, then the NPHI value has a range of 8 - 20 % and RHOB 2.13 - 2.45 g/cc. The resistivity log has a range a large enough value that is 0.5 - 66.8 ohm.m, so it does not support interpretation. The presence of th gas is also verified by geochemical data that explains the presence of gas with high methane composition, which is valued at 98.96% at depths of 5034 - 5090 ft and 98.95% at depths of 5198 - 5216 ft as listed on **Table 1** below.

Based on S-1 well biostratigraphic data (Figure 3) it is known that in the both zones has Late Miocene age which according to the Nias Basin stratigraphy that the growth of reef limestone at that time is intensive in the depositional environment bathyal to the outer shelf environment.

Comment [u2]: Your discussion does not yet appear explicitly, which must be followed by a reference for each discussion of results

3

Journal Title https://doi.org/XXXX/XXXX



Figure 1. Reservoir Zone 1 based on Qualitative Interpretation.



4



Figure 2. Reservoir Zone 2 based on Qualitative Interpretation.

Figure 3. S-1 Well Stratigraphy Columnar Section (Union Oil Company of Indonesia) [12].

xxxx-xxxx/xx/xxxxx

Journal Title https://doi.org/XXXX/XXXX

	S	-1
	Water	Depth
Componente	DST 2	DST 3
Components	5198 FT – 5216 FT	5034 FT – 5090 FT
	Late Miocene	Late Miocene
	%	%
Hydrogen	-	-
Helium	-	-
Carbon Monoxide	-	-
Hydrogen Sulphide	-	-
Carbon Dioxide	0.29	0.23
Oxygen	-	-
Nitrogen	0.56	0.61
Methane	98.95	98.96
Ethane	0.18	0.19
Propane	0.02	0.01
Iso-Butane	-	-
n-Butane	-	-
Iso Pentane	-	-
n-Pentane	-	-
Hexanes	-	-
Hexanes Plus	-	-
Total Percentage	100	100
Molecular Weight	16.222	16.209
Gravity	0.56	0.5595

Table 1. Geochemical Data of S-1 Well (Union Oil Company of Indonesia, 1978).

Table 2. Indicated Fluid based on Quantitative Interpretation.

Zone	Depth	Vsh (%)	PHIE (%)	Rw	Sw Indo (%)	Fluid
1	5026 - 5130	21.25	16.89	0.04	41.51	Biogenic Gas
2	5198 - 5216	21.23	17.18	0.04	39.90	Biogenic Gas

A good formation as a reservoir is a formation with little shale content because the presence of large amounts of shale can inhibit rocks from flowing fluid. This type of formation is important to calculate, to know the type of Sw equation that will be used later. Based on **Table 2**, it is known that in the S-1 Well, there is an impurity content of 21.25%

The large porosity allows rocks to hold more hydrocarbon fluids. The porosity calculation is performed until an effective porosity value is obtained, that is the porosity which is not influenced by the clay content. This is done to avoid errors in interpretation where clay content can bind large amounts of formation water so that the calculation will be unrepresentative. It can be seen in **Table 2** that the total porosity value of the reservoir zone in the S-1 Well is greater than the effective porosity. This difference in value is not too large at around 0.5%. The effective porosity value itself is good according to scale of determining whether or not the quality of the porosity value of a reservoir rock [9].

The water-bearing zone in the S-1 Well is at a depth of 5230 - 5242 ft where the response curve of the log can be seen in **Figure 4**.

Journal Title https://doi.org/XXXX/XXXX

 DEPTH (FT)
 0
 GR (API)
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0
 0.0





Rw in well S-1 as we can see on **Figure 5** above, shows a value of Rw 0.0359 ohm.m where this value is plotted in areas with low log resistivity values below 10 ohms.m and indicates the presence of water bearing zone.

Formation water saturation is the ratio of the pore volume filled by water to the total porosity volume [6]. The water saturation (Sw) value represents the water content in a rock formation. The greater the value of Sw, it is indicated that the formation contains only a small amount of hydrocarbon fluid and is dominated by water. Sw in S-1 well was identified to contain hydrocarbon fluid in the form of biogenic gas based on its average Sw value of 40.71%. The determination of the type of content in the reservoir (gas, oil and water) is obtained from the calculation of the formation water saturation (Sw) in the result of general limits of Sw prices for unknown fields where the average range

IOP Publishing	Journal Title
Journal XX (XXXX) XXXXXX	https://doi.org/XXXX/XXXX

of Sw values for gas is < 50%, the average range of Sw values for oil and gas is <60%, the average range of Sw values for oil is around 50% - 70%, and for water is> 70% [3].

Biogenic gas itself is identified based on existing geochemical data regarding the presence of methane gas in the S-1 Well. This methane gas was identified as biogenic gas because of its almost 100% methane composition and its presence in the low arc basin of the island of Sumatra. Therefore, in the reservoir zone contained in this well there is indicated hydrocarbons in the form of oil and biogenic gas.

Biogenic gas is formed at temperatures that are not too high and at depths that are not too deep. In the S-1 well, biogenic gas was identified at a depth of 5034 - 5090 ft and 5198 - 5216 ft in rocks of Late Miocene age. In S-1 well, it is known that the rocks that act as reservoirs are limestone with 98.95 - 98.96% methane gas content. The formation of this gas occurs in the diagenetic phase wherein this phase forms the source rock which is thermally immature.

The difference between biogenic gas and thermogenic gas usually lies in the diagenetic process and temperature. Biogenic gases are formed by the activity of methanogenic bacteria at low temperatures. Temperature can affect organic substances contained in sediments where an increase in temperature will convert heavy petroleum into light petroleum, then condensate and finally only gas [4].

3.2 Result of Source Rock Identification

Based on the results of qualitative interpretation according to Crain (Figure 6) on the S-1 well, identified source rock is identified in two zones, namely at depths of 6379 - 6388 ft, and 6524 - 6558 ft as shown in Figure 7 and Figure 8.



Figure 6. Interpretation of Immature Source Rock on S-1 well [2].

z

Journal Title https://doi.org/XXXX/XXXX



Figure 7. Source Rock Zone 1 of S-1 well.

Figure 8. Source Rock Zone 2 of S-1 well.

Based on biostratigraphic data, it is known that in these two zones also located in Late Miocene age. Main rocks of Middle and Late Miocene age indicate immature maturity. The cross between the DT and resistivity curves according to Crain (2010) in **Figure 6** also shows the immature source rock form. Deposition environment in this zone according to biostratigraphic data is the inner shelf.

The response of gamma ray log is low - middle value in the first SR zone which shows the lithology of the rock is limestone dominated clay. Then the low-high GR log response in the second zone validating the stratigraphic data that the area at this depth has lithology of claystone interbedded with sandstones.

The gamma ray log response is small in both zones, namely in the range of 20-73 API, then the NPHI value has a range of 8-20% and RHOB 2.13 - 2.45 g / cc. For the resistivity log has a range of values large enough that is 0.5 - 66.8 ohm.m,

The Nias Basin's position in the fore-arc region between Sumatra Island and the Indian Ocean results in a relatively low geothermal gradient and heat flow in this basin, which is around 1.2 HFU on average [13]. This low heatflow and geothermal gradient are ideal for biogenic gas formation. The temperature value in a rock chamber, is one of the important parameters in the process of determining the maturity of organic matter, to predict the maturity of hydrocarbons in sedimentary rocks [5].

3.3. Reservoir and Source Rock Distribution Area

Correlation of the reservoir area of five well in the Nias Basin is done to determine the existence of source rock and reservoir distribution contained in the S-1 well. It can be seen in **Figure 9** and **Table 3**, that in this study area immature source rock and biogenic gas reservoirs in identified.

8

IOP Publishing

Journal XX (XXXX) XXXXXX

Journal Title https://doi.org/XXXX/XXXX



Figure 9. Reservoir and Source Rock Distribution Area Model.

Depth 1 (ft)	Depth 2 (ft)	Age	Lithology	Petroleum System
5026	5216	Late Miocene	Limestone	Biogenic Gas Reservoir
6379	6558	Late Miocene	Clay	Immature Source Rock

 Table 3. Reservoir and source rock existence in S-1 well.

The biogenic gas reservoir in S-1 well has limestone lithology of Late Miocene age and immature source rock in the lithology of silty clay on a Late Miocene rocks. It can be seen that the study area is dominated by Late-Miocene rocks where at this age the limestone growth in the Nias Basin is very intensive due to the quiet period and lack of material supply from the mainland so that these rocks are the main target in the search for reservoirs.

4. Conclusions

Based on the outcome of this research, it can be concluded that:

- 1. Biogenic gas reservoir zones in the S-1 Well were identified as being in two zones at depths of 5026-5130 ft and 5198-5216 ft which were qualitatively shown in permeable layers (small value GR) and the separation between NPHI and RHOB, but qualitative interpretation less supportive because of the low resistivity value in the interest zone. While quantitative interpretation is very supportive based on PHIE value 16.89 17.18 ohm.m and Sw is around 39.90 41.51%.
- 2. The immature source rock layer is qualitatively determined by the separation form of the sonic and resistive log curves with a range of sonic log values of 101-120 us/ft and resistivity logs of 2.15 2.39 ohm.m on silty clay lithology of Late Miocene rocks.

9

Comment [u3]: Make the conclusion in paragraph.

XXXX-XXXX/XX/XXXXXX

Journal Title https://doi.org/XXXX/XXXX

References

- [1] Asquith G B and Gibson C R 1982 *Basic Well Log Analysis for Geologists* American Association of Petroleum Geologists USA
- [2] Crain E R 2010 Crain's Petrophysical Handbook www.spec2000.net/ (access on 5 March 2019)
- [3] Dewanto O 2016 *Petrofisika Log* Universitas Lampung CV Anugrah Utama Raharja ISBN: 978-602-6238-88-7
- [4] Dewanto O, Mulyanto B S, Rustadi and Wibowo R C 2017 Determining the Temperature of Shale Material Conversion Into Crude Oil Based on Organic Clay and Organic Carbonate Test Outside Reservoir International Journal of Mechanical and Mechatronics Engineering, IJMME 17 No:05 ISSN: 2077-124X (Online) 2227-2771 (Print) 84-892
- [5] Dewanto O, Rizky S, Mulyanto B S and Rustadi 2019 The Maturity Estimation of Material Organic in CaCO3 with Determining Tmax and Energy Activation Using Pyrolysis Method *Journal of Computational and Theoretical Nanoscience* 16, No.1–12
- [6] Harsono A 1997 Evaluasi Formasi dan Aplikasi Log Schlumberger Oilfield Services Jakarta
- [7] Karlina D A dan Santosa B J 2016 Prediksi Log TOC dan S2 dengan Menggunakan Teknik ΔLog Resistivity Jurnal Sains dan Seni ITS 5/2 20-24
- [8] Katz B 1995 Biogenic Gas -Its Formation and Economic Significance *Proceedings of Indonesia Petroleum Association 24th Annual Convention*
- [9] Koesoemadinata R P 1980 Geologi Minyak dan Gas Bumi Jilid 1 dan 2 Institut Teknologi Bandung
- [10] Lubis S 2015 Prospeksi Gas Methan Biogenic Perairan Dangkal: Sumber Gas Non Konvensional Short Course on SM IAGI UNPAD Jatinangor
- [11] Mulyanto B S, Dewanto O and Rizky S 2018 Determining Layer Oil Shale as New Alternative Energy Sources Using Core Analysis and Well Log Method International Journal of Engineering & Technology ISSN: 2227524X 7 No:4.36 941-949
- [12] Phoa R, Bradley K, and Camp Q V 1973 Laporan Penelitian Gas Biogenik Cekungan Nias Bandung Union Oil Company
- [13] Pusat Penelitian dan Pengembangan Geologi Kelautan (PPPGL) 2018 Laporan Penelitian Gas Biogenik Cekungan Nias Bandung
- [14] Rice D D and Claypool G E 1981 Generation, Accumulation, and Resources Potential of Biogenic Gas American Association of Petroleum Geologists Bulletin 65 No.1 5-25
- [15] Schlumberger 1989 Log Interpretation Principles/Application, Seventh Printing Texas
- [16] Schoell M 1988 Multiple Origin of Methane in the Earth Chemical Geology 71 1-10

Comment [u4]: The order of bibliography must be adjusted according to the order of references in the text. For example (Dewanto et al, 2017) must be placed in order number 1 on the bibliography. Therefore, technically, (Dewantoro, 2017) is replaced by [1], and the same method for the next reference



INTERNATIONAL CONFERENCE ON THEORETICAL AND APPLIED PHYSICS (ICTAP) 2019 SIMPOSIUM FISIKA NASIONAL (SFN) XXXII PHYSICAL SOCIETY OF INDONESIA (PSI) CABANG LAMPUNG Alamat: Jl. Prof. Sumantri Brodjonegoro, Jurusan Fisika FMIPA, Universitas Lampung



Based on the results of the review, the International Conference on Theoretical and Applied Physics (ICTAP) Committee decided to **accept your article** with the title is "Identification of Biogenic Gas Reservoir Zone using Log, Petrophysics, and Geochemical Data in S-1 Well of Nias Basin, North Sumatera" to be presented at the conference on $26^{th} - 27^{th}$ September 2019. Therefore, the you can immediately make a payment through BNI account number 0796397645 (swift code: BNINIDJABDL) on behalf of Leni Rumiyanti. If you pay at the early bird limit (on 30^{th} August 2019), you get the discount of the payment. Please upload the proof of your payment through the link bit.ly/Registration_ICTAP2019.

Best regards.

Bandarlampung, 24th August, 2019

Chairman of committee



Question Regarding Joining in Field Trip & Reminder The Quality of Your Article



🚷 mail.g	oogle.com	× M Question Re	garding Joining in Field Trip X 📝 Hasil Cari Yahoo untuk google translate X 🖓 Google Translate X 🕇	✓ - □ X
$\leftarrow \rightarrow$	C 🔒 mail.google	e.com/mail/u/0/#sea	ch/ictap2019/FMfcgxwDqxRmnZvkXTHclJhsfKtSbPlZ	* 🖻 🖈 🖬 🌍 🗄
=	M Gmail		Q ictap2019 X ₹ Active ▼ ⑦	🤹 🏭 Google 🌍
99+ Mail	0 Compose			6 of 9 < > 📷 🕶
	Inbox	1,600	We would also remind you in writing your article. Please pay attention to the issues of similarity (normally not more than 20%), language and using the template of IOP.	
0	☆ Starred ③ Snoozed		Thank you for your attention.	
Spaces	∑ Important▷ Sent		Best regards,	
Meet	Drafts	11	The Organizing Committe	
	Categories Social	323	THE 9th INTERNATIONAL CONFERENCE ON THEORETICAL AND APPLIED PHYSICS (ICTAP) Secretariat:	
	 Updates 	181	Department of Physics Faculty of Mathematics and Natural Sciences	
	📮 Forums	77	University of Lampung Address: Jl. Prof. Dr. Soemantri Brodjonegoro No.1, Bandar Lampung	
	 Promotion More 	s 244	35145, Indonesia Email: <u>lampung@fisika.or.id</u> Website: <u>https://conference.fisika.or.id/Events/detailread/8/38</u>	<
1 24_	Accepted Letter (Ipdf	∧ ICTAP_Dew Removed	into_UNILA.docx	Show all
ρ	H C F	 Section 1 	🧭 29°C Sebagi	an cerah へ 🌀 亞 🎝 🗉 🕬 13:16 30/03/2023

🚷 mail.	google.com	;	X N Question I	egarding Joining in Field Trip 🗙 📝 Hasil Cari Yahoo untuk google translate 🗙 🎯 Google Translate 🗙 🕂	~ — 🗆 X
$\leftarrow \rightarrow$	C 🔒	mail.google.co	m/mail/u/0/#se	irch/ictap2019/FMfcgxwDqxRmnZvkXTHclJhsfKtSbPlZ	* 🖻 🖈 🖬 🌍 🗄
=	M	Gmail		Q ictap2019 × ☶ ● Active ▼ ?) 🕸 🏭 Google 🌍
Mail	0	Compose			6 of 9 < > 📼 -
Chat		Inbox Starred	1,600	Dear Presenter/Participant, In accordance with the information from ICTAP-SFN website. We take pleasure in participating you into a field trip to geotracking tourism	
Spaces	© D	Snoozed		around the geothermal Ulubelu area. If you are interested, please inform us (your name & your institution) no later than 7th September 2019 via this email and transfer the payment Rp 250.000,-/person no later than	
D. Meet		Sent		7th September <mark>2019</mark> as well. You will get facilities such as transportation Bandar Lampung-Ulubelu, t-shirt, snack (2 times) and lunch. This field trip will be done if the total of participant 35- 40	
Meet	ن - D	Drafts Categories	11	persons for every bus. We will inform you and give back your money at the conference arena if the field trip is canceled.	
	De	Social	323	We would also remind you in writing your article. Please pay attention to the issues of similarity (normally not more than 20%), language and	
	(i)	Updates	181	using the template of IOP.	
	믹	Forums	77	Thank you for your attention.	
	\bigcirc	Promotions	244		
	~	More		Best regards,	*
			1		
124	_Accepted Le	tter (lpdf 🔨 🔨	Removed	anto_UNILA.docx	Show all X
P	Ħł (0 = =		🧭 29°C S	ebagian cerah ^ 📀 🖗 🗗 다 다) 13:18 30/03/2023

🌏 mail.c	google.com	× M (no subject) - or	das.dewanto@eng.unile 🗙 📝 Hasil Cari Yahoo untuk google translate 🗙 🏻 🤧 Google Translate	× + ~ - □ ×
$\leftarrow \rightarrow$	C 🔒 mail.google.	.com/mail/u/0/#search	n/ictap2019/KtbxLrjZnDMCMwFlXcDtRkwGVmfSnjhZWg	* 🖻 🖈 🗖 🌍 🗄
■	M Gmail	C	k ictap2019 X 荘	• Active • ⑦ 🕄 🏭 Google 🌍
Mail	Compose	÷		5 of 9 < > 📼 🕶
	🕞 Inbox	1,600	(no subject) D	8 C
Chat	☆ Starred	6	ORDAS DEWANTO <ordas.dewanto@eng.unila.ac.id></ordas.dewanto@eng.unila.ac.id>	📼 Fri, Sep 6, 2019, 11:47 PM 🕁 🕤 🗄
Spaces	Snoozed ∑ Important		to Agus 👻	
œ	► Sent		2 Attachments • Scanned by Gmail 🗊	<u>₹</u> @ ₁
Meet	Drafts	11	(6)/C ***** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** **** ***** **** **** **** **** **** **** **** ***** **** **** **** **** **** **** **** ***** **** ***** ***** ***** ***** ***** ***** ***** ***** ***** ***** ***** ******	
	은 Conceptions	323	apring and appropriate appropriote appropriate appropriate appropriate appropriate appropriat	
	 Updates 	181	Manuscript ICTA	
	Forums	77		
	 More 	• 244	← Reply → Forward	
				(
POF 124	_Accepted Letter (Ipdf	ICTAP_Dewanto	o_UNILA.docx	Show all
9	Hi C ≓ (s 💿 🔹		そ 30°C Sebagian cerah へ 6 ② 歩 ■ 印 33:19 30/03/202

Manuscript ICTAP 2019 (Dr. ORDAS DEWANTO) dan Bukti Pembayaran

Identification of biogenic gas reservoir zone using log, petrophysics and geochemical data in S-1 well of Nias basin, north Sumatera

O Dewanto^{1,2}, Maulina¹, and T B Nainggolan³

- ¹ Geophysics Engineering, Engineering Faculty, University of Lampung, Bandar Lampung 35145, Indonesia
- ² ordas.dewanto@eng.unila.ac.id
- ³ Marine Geological Research and Development Center, Jalan Dr. Djunjunan No.236, Bandung 40174, Indonesia

Abstract. The fore-arc basin has been become a target of reservoir searching for a long time based on previous expert studies, where the indications of Late-Miocene carbonate age that could act as a hydrocarbon reservoir was found. S-1 Well located in the Nias Basin, one of the fore-arc basin located in West of Sumatera. As the object of this study, it is hoped that the hydrocarbon reservoir in the fore-arc basin is expected to be discovered and to identify the characteristics of rocks that potential to become hydrocarbon reservoirs. Geochemical data becomes supporting data regarding the presence of gases that are identified as biogenic gases because of the content of methane as the main composition. Identification of the existence of reservoir zones and source rock is done by qualitative interpretation of log data from the S-1 well. Then, the petrophysical parameters are analyzed in the form of shale volume (Vsh), effective porosity, resistivity water (Rw), and water saturation (Sw) to determine the type of reservoir's fluid. The results of the interpretation indicated that the presence of biogenic gase was detected in Late-Miocene with limestone lithology with Sw value 39.90 - 41.51 %.

Keywords: petrophysical, shale volume, effective porosity, water saturation

1. Introduction

The existence of shale material in Indonesia is indeed quite a lot, so it is estimated that in the next few years there will be many sources of oil and gas (Dewanto et al, 2017). However, the process of changing material into oil and gas requires a very long time (Dewanto et al, 2017) so that using oil and gas is increasingly rare and difficult to do. This makes biogenic gas become a solution as an alternative energy source to replace the using of oil and natural gas. Biogenic gas is an environmentally friendly type of fuel because it produces less carbon dioxide than other types of fuel. In addition, the investment costs of biogenic gas are cheaper than non-conventional gas because of its more general existence of 1,000 m on the sea bed, so researchers are now more focused on biogenic gas research that is more profitable to do.

Biogenic gas is a flammable hydrocarbon gas, has the shortest carbon chain (C1) so it is the lightest gas, which is about 0.7 lighter than air (Rice and Claypool, 1981). Therefore, if used as an energy source, biogenic gas is a type of fuel that is environmentally friendly. Biogenic gas is a gas with a methane content> 98% and has a low S and CO2 content and can be detected in the presence of the carbon isotope &13C CH4 which is -62 to -66% (Katz, 1995). Biogenic gas contained in this earth almost reaches 20% of all natural gas sources (Rice and Claypool, 1981) but its presence is spread in small gas bags of various sizes and at varying depths (Lubis, 2015).

The formation of this gas occurs in the diagenetic phase where in this phase forms the source rock which is thermally immature. According to Schoell (1988), methane gas is formed with the following

main processes:

- 1. Acetate bacterial fermentation in the chemical-rich sedimentary layer (gas charged sediment) chemically: CH₃COOH → CH₄ + CO₂.
- 2. The process of reducing CO2 by bacteria from naturally occurring volcanic or magmatic rocks: $CO_2 + 2H_2O \rightarrow CH_4$.

The Nias Basin, a fore arc basin, characterizes a cool basin with a smaller geothermal gradient up to the average (Katz, 1995 in PPPGL, 2018). This affects the process of maturation of existing host rock. Because the geothermal gradient or heat flow is low, the heat received by the rocks is also small so that the Miocene-aged parent rock in this basin is generally immature. However, in older or deepburied rocks it might reach maturity. Temperature can affect organic substances contained in sediments where an increase in temperature will convert heavy petroleum into light petroleum, then condensate and finally only gas (Dewanto et al, 2017).

Determination and analysis of reservoir parameters can be done by two methods, namely core analysis in the laboratory and interpretation of log data (Mulyanto et al, 2018). As for this research, a log data interpretation in the form of a quick-look qualitative interpretation and a quantitative interpretation in the form of petrophysical analysis is carried out in an effort to determine the detailed conditions of a petroleum system. Petrophysical analysis itself is a process that is carried out to validate the hydrocarbon density and determine the characteristics of the hydrocarbon reservoir and source rock.

2. Research Method

2.1 Reservoir Qualitative Interpretation

Qualitative reservoir interpretation is done by lithology zoning and hydrocarbon prospect area analysis using gamma ray, resistivity, RHOB and NPHI logs. First, a quick-look reservoir zone identification is based on NPHI and RHOB log separations. This separation indicates the existence of a reservoir where the reservoir has the characteristics of a low NPHI and RHOB values. Then the existence of a hydrocarbon reservoir is also characterized by a medium resistivity (Rt) value for oil and a high resistivity value for gas. In addition, the value of gamma ray is also important in identifying the quantity of clay found in rocks. The gamma ray log records the gamma ray radiation of rocks which shows the radioactive intensity in it. Clay minerals contain a large quantity of radioactivity and high clay content is found in claystone or shale lithology.

2.2 Reservoir Quantitative Interpretation

Once the hydrocarbon reservoir zone is identified through a quick-look analysis, a full-analysis is carried out in the form of petrophysical analysis through quantitative interpretation. To conduct petrophysical analysis, the shale content of rocks in the study area is a parameter whose value must first be determined. Calculation of clay content in S-1 Wells uses the Larionov tertiary equation because the age of the rock is relatively young based on the stratigraphy of the existing Nias Basin as follows (Asquith dan Gibson, 1982):

$$Vs = 0.08336 \left(2^{3.7} x^{\text{IGR}} - 1\right) \tag{1}$$

Then porosity (Ø) calculation using the equation as follows (Schlumberger, 1989):

$$\boldsymbol{\varPhi}_{\boldsymbol{\sigma}} = \sqrt{\frac{\boldsymbol{\varPhi}_{Ncor}^2 + \boldsymbol{\varPhi}_{Dcor}^2}{2}} \tag{2}$$

Resistivity water (Rw) determination by plotting pickett plots in the software Interactive Petrophysics in areas filled with water (Sw=1). This zone is characterized by a very low resistivity (Rt) value and coinciding with the NPHI and RHOB log curves. Then calculating water saturation (Sw) using the Indonesian Sw equation so that it does not neglect the presence of impurities contained in rock formations as follows:

$$\frac{1}{\sqrt{R_{\rm f}}} = \left(\sqrt{\frac{\varphi_{\theta}^{\rm m}}{a \times R_{\rm W}}} + \frac{V_{sh}^{1-0.5V_{sh}}}{\sqrt{R_{sh}}}\right) \times S_{\rm W}^{\frac{n}{2}} \tag{3}$$

2.3 Source Rock Qualitative Interpretation

For qualitative interpretation of source rock, gamma ray logs, resistivity logs and sonic logs are used. Based on the separation form of the sonic and resistivity log curves, the source rock type and its presence can be known in the well. This bedrock is usually in shale or siltstone lithology which has impermeable rock characteristics with high GR values, very high sonic log values and low value of resistivity logs.

The resistivity and sonic logs are overlaid to make it easier to see the shape of the separation. The first rule that needs to be known is when the GR (or SP) deflection to the left means the zone is clean and reservoir rock can be indicated. When the GR is deflected to the right, it indicates shale lithology (not characteristic of reservoir rocks). Then, the second rule is the porosity log (in this case the sonic log) is set on a high to low scale. Then the third rule is the resistivity log set on a low to high scale. High resistivity indicates the presence of hydrocarbons or low porosity, while low resistivity indicates an indication of shale or water zone (Crain, 2010).

The separation between resistivity log and DT log shows anomaly. When separation is formed to the right of the baseline it can be estimated that the separation shows the existence of source rock, and the rock is mature (mature). Whereas the separation formed to the left of the baseline shows that the depth is estimated as source rock, but immature, or as coal, and other non-source rock. Mature source rock has characteristics of high resistivity value, and high sonic log, while immature source rock has characteristic value with low resistivity value and not too high sonic log. Large log resistivity and sonic log separations are called Δ LogR (Karlina and Santosa, 2016).

2.4 Distribution Area of Biogenic Gas Reservoirs Modelling

Qualitative interpretation of source rock zones based on the overlay of DT and resistivity logs, and the biogenic gas reservoir based on quantitative interpretation and model of S-1 well can be identified.

3. Result and Discussion

3.1 Result of Reservoir Zone Identification

S-1 well has a total depth of 6990 ft. The presence of gas can be identified using qualitative log interpretation using gamma ray log, resistivity log, and separation between RHOB and NPHI logs as shown in **Figure 1** and **Figure 2**. In this well, reservoirs were identified in two zones, at depths of 5026-5130 ft, and 5198-5216 ft.

This is also evidenced by the small gamma ray log response in the both zones, namely in the range of 20 - 73 API, then the NPHI value has a range of 8 - 20 % and RHOB 2.13 - 2.45 g/cc. The resistivity log has a range a large enough value that is 0.5 - 66.8 ohm.m, so it does not support interpretation. The presence of th gas is also verified by geochemical data that explains the presence of gas with high methane composition, which is valued at 98.96% at depths of 5034 - 5090 ft and 98.95% at depths of 5198 - 5216 ft as listed on **Table 1** below.

Based on S-1 well biostratigraphic data (Figure 3) it is known that in the both zones has Late Miocene age which according to the Nias Basin stratigraphy that the growth of reef limestone at that time is intensive in the depositional environment bathyal to the outer shelf environment.



Figure 1. Reservoir Zone 1 based on Qualitative Interpretation.



Figure 2. Reservoir Zone 2 based on Qualitative Interpretation.



Figure 3. S-1 Well Stratigraphy Columnar Section (Union Oil Company of Indonesia) (Phoa et al, 1973).

	S	-1
-	Water	Depth
Componenta	DST 2	DST 3
Components	5198 FT – 5216 FT	5034 FT – 5090 FT
-	Late Miocene	Late Miocene
-	0⁄0	%
Hydrogen	-	-
Helium	-	-
Carbon Monoxide	-	-
Hydrogen Sulphide	-	-
Carbon Dioxide	0.29	0.23
Oxygen	-	-
Nitrogen	0.56	0.61
Methane	98.95	98.96
Ethane	0.18	0.19
Propane	0.02	0.01
Iso-Butane	-	-
n-Butane	-	-
Iso Pentane	-	-
n-Pentane	-	-
Hexanes	-	-
Hexanes Plus	-	-
Total Percentage	100	100
Molecular Weight	16.222	16.209
Gravity	0.56	0.5595

Table 1. Geochemical Data of S-1 Well (Union Oil Company of Indonesia, 1978).

Table 2. Indicated Fluid based on Quantitative Interpretation.

Zone	Depth	Vsh (%)	PHIE (%)	Rw	Sw Indo (%)	Fluid
1	5026 - 5130	21.25	16.89	0.04	41.51	Biogenic Gas
2	5198 - 5216	21.23	17.18	0.04	39.90	Biogenic Gas

A good formation as a reservoir is a formation with little shale content because the presence of large amounts of shale can inhibit rocks from flowing fluid. This type of formation is important to calculate, to know the type of Sw equation that will be used later. Based on **Table 2**, it is known that in the S-1 Well, there is an impurity content of 21.25%

The large porosity allows rocks to hold more hydrocarbon fluids. The porosity calculation is performed until an effective porosity value is obtained, that is the porosity which is not influenced by the clay content. This is done to avoid errors in interpretation where clay content can bind large amounts of formation water so that the calculation will be unrepresentative. It can be seen in **Table 2** that the total porosity value of the reservoir zone in the S-1 Well is greater than the effective porosity. This difference in value is not too large at around 0.5%. The effective porosity value itself is good according to scale of determining whether or not the quality of the porosity value of a reservoir rock by Koesoemadinata (1980).

The water-bearing zone in the S-1 Well is at a depth of 5230 - 5242 ft where the response curve of the log can be seen in **Figure 4**.



Figure 4. Water bearing zone in S-1 well.



Figure 5. Rw on S-1 Well.

Rw in well S-1 as we can see on **Figure 5** above, shows a value of Rw 0.0359 ohm.m where this value is plotted in areas with low log resistivity values below 10 ohms.m and indicates the presence of water bearing zone.

Formation water saturation is the ratio of the pore volume filled by water to the total porosity volume (Harsono, 1997). The water saturation (Sw) value represents the water content in a rock formation. The greater the value of Sw, it is indicated that the formation contains only a small amount of hydrocarbon fluid and is dominated by water. Sw in S-1 well was identified to contain hydrocarbon fluid in the form of biogenic gas based on its average Sw value of 40.71%. According to Dewanto in 2016, the determination of the type of content in the reservoir (gas, oil and water) is obtained from the calculation of the formation water saturation (Sw) in the result of general limits of Sw prices for

unknown fields where the average range of Sw values for gas is < 50%, the average range of Sw values for oil and gas is <60%, the average range of Sw values for oil is around 50% - 70%, and for water is > 70%.

Biogenic gas itself is identified based on existing geochemical data regarding the presence of methane gas in the S-1 Well. This methane gas was identified as biogenic gas because of its almost 100% methane composition and its presence in the low arc basin of the island of Sumatra. Therefore, in the reservoir zone contained in this well there is indicated hydrocarbons in the form of oil and biogenic gas.

Biogenic gas is formed at temperatures that are not too high and at depths that are not too deep. In the S-1 well, biogenic gas was identified at a depth of 5034 - 5090 ft and 5198 - 5216 ft in rocks of Late Miocene age. In S-1 well, it is known that the rocks that act as reservoirs are limestone with 98.95 - 98.96% methane gas content. The formation of this gas occurs in the diagenetic phase wherein this phase forms the source rock which is thermally immature.

The difference between biogenic gas and thermogenic gas usually lies in the diagenetic process and temperature. Biogenic gases are formed by the activity of methanogenic bacteria at low temperatures. Temperature can affect organic substances contained in sediments where an increase in temperature will convert heavy petroleum into light petroleum, then condensate and finally only gas (Dewanto et al, 2017).

3.2 Result of Source Rock Identification

Based on the results of qualitative interpretation according to Crain (Figure 6) on the S-1 well, identified source rock is identified in two zones, namely at depths of 6379 - 6388 ft, and 6524 - 6558 ft as shown in Figure 7 and Figure 8.



Figure 6. Interpretation of Immature Source Rock on S-1 well (Crain, 2010).



Figure 7. Source Rock Zone 1 of S-1 well.

Figure 8. Source Rock Zone 2 of S-1 well.

Based on biostratigraphic data, it is known that in these two zones also located in Late Miocene age. Main rocks of Middle and Late Miocene age indicate immature maturity. The cross between the DT and resistivity curves according to Crain (2010) in **Figure 6** also shows the immature source rock form. Deposition environment in this zone according to biostratigraphic data is the inner shelf.

The response of gamma ray log is low - middle value in the first SR zone which shows the lithology of the rock is limestone dominated clay. Then the low-high GR log response in the second zone validating the stratigraphic data that the area at this depth has lithology of claystone interbedded with sandstones.

The Nias Basin's position in the fore-arc region between Sumatra Island and the Indian Ocean results in a relatively low geothermal gradient and heat flow in this basin, which is around 1.2 HFU on average (Thamrin and Mey, 1987 in PPPGL, 2018). This low heatflow and geothermal gradient are ideal for biogenic gas formation. The temperature value in a rock chamber, is one of the important parameters in the process of determining the maturity of organic matter, to predict the maturity of hydrocarbons in sedimentary rocks (Dewanto et al, 2019).

3.3. Reservoir and Source Rock Distribution Area

Correlation of the reservoir area is done to determine the existence of source rock and reservoir contained in the S-1 well. It can be seen in **Figure 9** and **Table 3**, that in this study area immature source rock and biogenic gas reservoirs in identified.



Figure 9. Reservoir and Source Rock Distribution Area Model.

Depth 1 (ft)	Depth 2 (ft)	Age	Lithology	Petroleum System
5026	5216	Late Miocene	Limestone	Biogenic Gas Reservoir
6379	6558	Late Miocene	Clay	Immature Source Rock

Table 3. Reservoir and source rock existence in S-1 well.

The biogenic gas reservoir in S-1 well has limestone lithology of Late Miocene age and immature source rock in the lithology of silty clay on a Late Miocene rocks. It can be seen that the study area is dominated by Late-Miocene rocks where at this age the limestone growth in the Nias Basin is very intensive due to the quiet period and lack of material supply from the mainland so that these rocks are the main target in the search for reservoirs.

4. Conclusion

Based on the outcome of this research, it can be concluded that:

- Biogenic gas reservoir zones in the S-1 Well were identified as being in two zones at depths of 5026-5130 ft and 5198-5216 ft which were qualitatively shown in permeable layers (small value GR) and the separation between NPHI and RHOB, but qualitative interpretation less supportive because of the low resistivity value in the interest zone. While quantitative interpretation is very supportive based on PHIE value 16.89 17.18 ohm.m and Sw is around 39.90 41.51%.
- The immature source rock layer is qualitatively determined by the separation form of the sonic and resistive log curves with a range of sonic log values of 101-120 us/ft and resistivity logs of 2.15 - 2.39 ohm.m on silty clay lithology of Late Miocene rocks.

References

- [1] Asquith G.B. and Gibson C.R. 1982. *Basic Well Log Analysis for Geologists*. American Association of Petroleum Geologists. USA.
- [2] Crain E.R. 2010. Crain's Petrophysical Handbook. www.spec2000.net/(access on 5 March 2019).

- [3] Dewanto O. 2016. *Petrofisika Log.* Universitas Lampung. CV Anugrah Utama Raharja. ISBN: 978-602-6238-88-7.
- [4] Dewanto O., Mulyanto B.S., Rustadi and Wibowo R.C. 2017. Determining the Temperature of Shale Material Conversion Into Crude Oil Based on Organic Clay and Organic Carbonate Test Outside Reservoir *International Journal of Mechanical and Mechatronics Engineering, IJMME* 17 No:05 ISSN: 2077-124X (Online) 2227-2771 (Print) 84-892.
- [5] Dewanto O., Rizky S., Mulyanto B.S. and Rustadi. 2019. The Maturity Estimation of Material Organic in CaCO3 with Determining Tmax and Energy Activation Using Pyrolysis Method *Journal of Computational and Theoretical Nanoscience* 16, No.1–12.
- [6] Harsono A. 1997. Evaluasi Formasi dan Aplikasi Log. Schlumberger Oilfield Services Jakarta.
- [7] Karlina D.A. dan Santosa B.J. 2016. Prediksi Log TOC dan S2 dengan Menggunakan Teknik ΔLog Resistivity Jurnal Sains dan Seni ITS 5/2 20-24.
- [8] Katz B. 1995. Biogenic Gas -Its Formation and Economic Significance. Proceedings of Indonesia Petroleum Association 24th Annual Convention.
- [9] Koesoemadinata R.P. 1980 Geologi Minyak dan Gas Bumi Jilid 1 dan 2. Institut Teknologi Bandung.
- [10] Lubis S. 2015. Prospeksi Gas Methan Biogenic Perairan Dangkal: Sumber Gas Non Konvensional Short Course on SM IAGI UNPAD Jatinangor.
- [11] Mulyanto B.S., Dewanto O. and Rizky S. 2018. Determining Layer Oil Shale as New Alternative Energy Sources Using Core Analysis and Well Log Method. *International Journal of Engineering & Technology*. ISSN: 2227524X 7 No:4.36 941-949.
- [12] Phoa R, Bradley K, and Camp Q.V. 1973. *Laporan Penelitian Gas Biogenik Cekungan Nias* Bandung Union Oil Company.
- [13] Pusat Penelitian dan Pengembangan Geologi Kelautan (PPPGL). 2018. Laporan Penelitian Gas Biogenik Cekungan Nias Bandung.
- [14] Rice D.D. and Claypool G.E. 1981. Generation, Accumulation, and Resources Potential of Biogenic Gas. American Association of Petroleum Geologists Bulletin. 65 No.1 5-25
- [15] Schoell M. 1988. Multiple Origin of Methane in the Earth. Chemical Geology. 71 1-10

-	1.500.000	자			Ĩ	JUML A
	RUMI YANT I	EN	SDR	MA:	PENERI	NAMA
		97645	07963		UJUAN	REK.T
	DEWANTO	RDAS	SPK O	M :	PENGIR	NAMA
			2601	ORD	O. REK	7
			34455	4230	***221	*
	LAMPUNG	UNIV.	CAPEM	-		
	1EBDL02EX	S	19:50	60	3/09/1	0
	L					
				-		
		ALL NOT				

SEBAGAI BUKTI TRANSAKSI YANG SAH SIMPAN RESI INI BERITA

Progress letter of your article

🕑 mail.g	google.com	Progress letter of	your article - ordas.de 🗙 📝 Hasil Cari Yahoo untuk google translate 🗙 🛛 🥱 Google Translate	× + ~ - • ×
$\leftarrow \rightarrow$	C 🔒 mail.google.co	m/mail/u/0/#search/	ictap2019/FMfcgxwHMGDWKKsTCTdQfDdKLwlBfpDx	* 🖻 🖈 🗖 🌍 🗄
=	M Gmail	Q	ictap2019 × 로	• Active • ⑦ 🔅 🏭 Google 🌍
Mail	🖉 Compose	÷		3 of 9 < > 📖 🕶
	🖵 Inbox	1,600	Progress letter of your article $(External) > Inbox \times$	母 亿
Chat	☆ Starred③ Snoozed		ICTAP 2019 <ictap2019@gmail.com> to me •</ictap2019@gmail.com>	📼 Wed, Mar 4, 2020, 10:55 AM 🕁 🕤 🗄
Spaces	D Important		Dear Author,	
⊡ • Meet	SentDrafts	11	By this email, ould send you the Progress Letter of your article at ICTAE	<u>,</u>
	Categories Social	323	Best regards,	
	(i) Updates	181	The ICTAP's Committee	
	Forums Promotions	77 244	One attachment • Scanned by Gmail ()	@+
	✓ More		PS1 mouth water or proposition limit (called limit) water of the call of the called limit (called limit) Basic Lange (c) houry (20)	(<
por Buk	ti Pembayaran ICTApdf 🛛 🔨	Manuscript ICTA Removed	P 201doc 124_Accepted Letter (Ipdf ICTAP_Dewanto_UNILA Removed Removed	.docx Show all X
	H C H S			









INTERNATIONAL CONFERENCE ON THEORETICAL AND APPLIED PHYSICS (ICTAP) 2019 SIMPOSIUM FISIKA NASIONAL (SFN) XXXII PHYSICAL SOCIETY OF INDONESIA (PSI) CABANG LAMPUNG Sekretariat: Jl. Prof. Dr. Sumantri Brodjonegoro No.1, Jurusan Fisika FMIPA, Universitas Lampung

Bandar Lampung, 21st January 2020

Dear Authors,

On the behalf of the 9th International Conference on Theoretical and Applied Physics (ICTAP) committee, we are pleased to inform that your paper with the title:

"Identification of biogenic gas reservoir zone using log, petrophysics and geochemical data in S-1 well of Nias basin, north Sumatera" has been finished for the review process and will be proceed for submission to IOP.

We congratulate for your achievement. Thank you very much for participating in our event.

Kindest Regards,

nat. Roniyus Marjunus, S.Si., M.Si

Identification of biogenic gas reservoir zone using log, petrophysics and geochemical data in S-1 well of Nias basin, north Sumatera

O Dewanto¹, Maulina¹, and **T** B Nainggolan²

¹ Geophysics Engineering, Engineering Faculty, University of Lampung, Bandar Lampung 35145, Indonesia

² Marine Geological Research and Development Center, Jalan Dr. Djunjunan No.236, Bandung 40174, Indonesia

*ordas.dewanto@eng.unila.ac.id

Abstract. The fore-arc basin has been become a target of reservoir searching for a long time based on previous expert studies, where the indications of Late-Miocene carbonate age that could act as a hydrocarbon reservoir was found. S-1 Well located in the Nias Basin, one of the fore-arc basin located in West of Sumatera. As the object of this study, it is hoped that the hydrocarbon reservoir in the fore-arc basin is expected to be discovered and to identify the characteristics of rocks that potential to become hydrocarbon reservoirs. Geochemical data becomes supporting data regarding the presence of gases that are identified as biogenic gases because of the content of methane as the main composition. Identification of the existence of reservoir zones and source rock is done by qualitative interpretation of log data from the S-1 well. Then, the petrophysical parameters are analyzed in the form of shale volume (Vsh), effective porosity, resistivity water (Rw), and water saturation (Sw) to determine the type of reservoir's fluid. The results of the interpretation indicated that the presence of biogenic gase was detected in Late-Miocene with limestone lithology with Sw value 39.90 - 41.51 %.

Keywords: effective porosity, petrophysical, shale volume, water saturation.

1. Introduction

The existence of shale material in Indonesia is indeed quite a lot, so it is estimated that in the next few years there will be many sources of oil and gas [4]. However, the process of changing material into oil and gas requires a very long time [4] so that using oil and gas is increasingly rare and difficult to do. This makes biogenic gas become a solution as an alternative energy source to replace the using of oil and natural gas. Biogenic gas is an environmentally friendly type of fuel because it produces less carbon dioxide than other types of fuel. In addition, the investment costs of biogenic gas are cheaper than non-conventional gas because of its more general existence of 1,000 m on the sea bed, so researchers are now more focused on biogenic gas research that is more profitable to do.

Biogenic gas is a flammable hydrocarbon gas, has the shortest carbon chain (C1) so it is the lightest gas, which is about 0.7 lighter than air [14]. Therefore, if used as an energy source, biogenic gas is a type of fuel that is environmentally friendly. Biogenic gas is a gas with a methane content> 98% and has a low S and CO2 content and can be detected in the presence of the carbon isotope δ 13C CH4 which is -62 to -66% [8]. Biogenic gas contained in this earth almost reaches 20% of all natural gas sources [14] but its presence is spread in small gas bags of various sizes and at varying depths [10].

The formation of this gas occurs in the diagenetic phase where in this phase forms the source rock which is thermally immature. Methane gas is formed with the following main processes [15]:

- 1. Acetate bacterial fermentation in the chemical-rich sedimentary layer (gas charged sediment) chemically: $CH_3COOH \rightarrow CH_4 + CO_2$.
- 2. The process of reducing CO2 by bacteria from naturally occurring volcanic or magmatic rocks: $CO_2 + 2H_2O \rightarrow CH_4$.

The Nias Basin, a fore arc basin, characterizes a cool basin with a smaller geothermal gradient up to the average [8]. This affects the process of maturation of existing host rock. Because the geothermal gradient or heat flow is low, the heat received by the rocks is also small so that the Miocene-aged parent rock in this basin is generally immature. However, in older or deep-buried rocks it might reach maturity. Temperature can affect organic substances contained in sediments where an increase in temperature will convert heavy petroleum into light petroleum, then condensate and finally only gas [4].

Determination and analysis of reservoir parameters can be done by two methods, namely core analysis in the laboratory and interpretation of log data [11]. As for this research, a log data interpretation in the form of a quick-look qualitative interpretation and a quantitative interpretation in the form of petrophysical analysis is carried out in an effort to determine the detailed conditions of a petroleum system. Petrophysical analysis itself is a process that is carried out to validate the hydrocarbon density and determine the characteristics of the hydrocarbon reservoir and source rock.

2. Method

2.1 Reservoir Qualitative Interpretation

Qualitative reservoir interpretation is done by lithology zoning and hydrocarbon prospect area analysis using gamma ray, resistivity, RHOB and NPHI logs. First, a quick-look reservoir zone identification is based on NPHI and RHOB log separations. This separation indicates the existence of a reservoir where the reservoir has the characteristics of a low NPHI and RHOB values. Then the existence of a hydrocarbon reservoir is also characterized by a medium resistivity (Rt) value for oil and a high resistivity value for gas. In addition, the value of gamma ray is also important in identifying the quantity of clay found in rocks. The gamma ray log records the gamma ray radiation of rocks which shows the radioactive intensity in it. Clay minerals contain a large quantity of radioactivity and high clay content is found in claystone or shale lithology.

2.2 Reservoir Quantitative Interpretation

Once the hydrocarbon reservoir zone is identified through a quick-look analysis, a full-analysis is carried out in the form of petrophysical analysis through quantitative interpretation. To conduct petrophysical analysis, the shale content of rocks in the study area is a parameter whose value must first be determined. Calculation of clay content in S-1 Wells uses the Larionov tertiary equation

because the age of the rock is relatively young based on the stratigraphy of the existing Nias Basin as follows [1]:

$$Vs = 0.08336 \left(2^{3.7} x^{IGR} - 1\right) \tag{1}$$

Then porosity (\emptyset) calculation using the equation as follows [15]:

$$\phi_e = \sqrt{\frac{\phi_{Ncor}^2 + \phi_{Dcor}^2}{2}} \tag{2}$$

Resistivity water (Rw) determination by plotting pickett plots in the software Interactive Petrophysics in areas filled with water (Sw=1). This zone is characterized by a very low resistivity (Rt) value and coinciding with the NPHI and RHOB log curves. Then calculating water saturation (Sw) using the Indonesian Sw equation so that it does not neglect the presence of impurities contained in rock formations as follows:

$$\frac{1}{\sqrt{R_t}} = \left(\sqrt{\frac{\phi e^m}{a \times R_w}} + \frac{V_{sh}^{1-0.5V_{sh}}}{\sqrt{R_{sh}}}\right) \times S_w^{\frac{n}{2}}$$
(3)

2.3 Source Rock Qualitative Interpretation

For qualitative interpretation of source rock, gamma ray logs, resistivity logs and sonic logs are used. Based on the separation form of the sonic and resistivity log curves, the source rock type and its presence can be known in the well. This bedrock is usually in shale or siltstone lithology which has impermeable rock characteristics with high GR values, very high sonic log values and low value of resistivity logs.

The resistivity and sonic logs are overlaid to make it easier to see the shape of the separation. The first rule that needs to be known is when the GR (or SP) deflection to the left means the zone is clean and reservoir rock can be indicated. When the GR is deflected to the right, it indicates shale lithology (not characteristic of reservoir rocks). Then, the second rule is the porosity log (in this case the sonic log) is set on a high to low scale. Then the third rule is the resistivity log set on a low to high scale. High resistivity indicates the presence of hydrocarbons or low porosity, while low resistivity indicates an indication of shale or water zone [2].

The separation between resistivity log and DT log shows anomaly. When separation is formed to the right of the baseline it can be estimated that the separation shows the existence of source rock, and the rock is mature (mature). Whereas the separation formed to the left of the baseline shows that the depth is estimated as source rock, but immature, or as coal, and other non-source rock. Mature source rock has characteristics of high resistivity value, and high sonic log, while immature source rock has characteristic value with low resistivity value and not too high sonic log. Large log resistivity and sonic log separations are called Δ LogR [7].

2.4 Distribution Area of Biogenic Gas Reservoirs Modelling

Qualitative interpretation of source rock zones based on the overlay of DT and resistivity logs, and the biogenic gas reservoir based on quantitative interpretation and model of S-1 well can be identified.

3. Result and Discussion

3.1 Result of Reservoir Zone Identification

S-1 well has a total depth of 6990 ft. The presence of gas can be identified using qualitative log interpretation using gamma ray log, resistivity log, and separation between RHOB and NPHI logs as shown in Figure 1 and Figure 2. In this well, reservoirs were identified in two zones, at depths of 5026-5130 ft, and 5198-5216 ft.



Figure 1. Reservoir Zone 1 based on Qualitative Interpretation.



Figure 1. Reservoir Zone 1 based on Qualitative Interpretation.



Figure 3. S-1 Well Stratigraphy Columnar Section (Union Oil Company of Indonesia) [12].

Based on S-1 well biostratigraphic data (**Figure 3**) it is known that in the both zones have Late Miocene age which according to the Nias Basin stratigraphy that the growth of reef limestone at that time is intensive in the depositional environment bathyal to the outer shelf environment.

This is also evidenced by the small gamma ray log response in the both zones, namely in the range of 20 - 73 API, then the NPHI value has a range of 8 - 20 % and RHOB 2.13 - 2.45 g/cc. The resistivity log has a range a large enough value that is 0.5 - 66.8 ohm.m, so it does not support interpretation. The presence of th gas is also verified by geochemical data that explains the presence of gas with high methane composition, which is valued at 98.96% at depths of 5034 - 5090 ft and 98.95% at depths of 5198 - 5216 ft as listed on **Table 1** below.

	S-1				
	Water Depth				
Components	DST 2	DST 3			
Components	5198 FT – 5216 FT	5034 FT – 5090 FT			
	Late Miocene	Late Miocene			
	%	%			
Hydrogen	-	-			
Helium	-	-			
Carbon Monoxide	-	-			
Hydrogen Sulphide	-	-			
Carbon Dioxide	0.29	0.23			
Oxygen	-	-			
Nitrogen	0.56	0.61			
Methane	98.95	98.96			
Ethane	0.18	0.19			
Propane	0.02	0.01			
Iso-Butane	-	-			
n-Butane	-	-			
Iso Pentane	-	-			
n-Pentane	-	-			
Hexanes	-	-			
Hexanes Plus	-	-			
Total Percentage	100	100			
Molecular Weight	16.222	16.209			
Gravity	0.56	0.5595			

Table 2. Indicated Fluid based on Quantitative Interpretation

Zone	Depth	Vsh (%)	PHIE (%)	Rw	Sw Indo (%)	Fluid
1	5026 - 5130	21.25	16.89	0.04	41.51	Biogenic Gas
2	5198 - 5216	21.25	17.18	0.04	39.90	Biogenic Gas

A good formation as a reservoir is a formation with little shale content because the presence of large amounts of shale can inhibit rocks from flowing fluid. This type of formation is important to calculate, to know the type of Sw equation that will be used later. Based on **Table 2**, it is known that in the S-1 Well, there is an impurity content of 21.25%

The large porosity allows rocks to hold more hydrocarbon fluids. The porosity calculation is performed until an effective porosity value is obtained, that is the porosity which is not influenced by the clay content. This is done to avoid errors in interpretation where clay content can bind large amounts of formation water so that the calculation will be unrepresentative. It can be seen in **Table 2** that the total porosity value of the reservoir zone in the S-1 Well is greater than the effective porosity. This difference in value is not too large at around 0.5%. The effective porosity value itself is good according to scale of determining whether or not the quality of the porosity value of a reservoir rock [9].

The water-bearing zone in the S-1 Well is at a depth of 5230 - 5242 ft where the response curve of the log can be seen in **Figure 4**.



Figure 5. Rw on S-1 Well.

Rw in well S-1 as we can see on **Figure 5** above, shows a value of Rw 0.0359 ohm.m where this value is plotted in areas with low log resistivity values below 10 ohms.m and indicates the presence of water bearing zone.

Formation water saturation is the ratio of the pore volume filled by water to the total porosity volume [6]. The water saturation (Sw) value represents the water content in a rock formation. The greater the value of Sw, it is indicated that the formation contains only a small amount of hydrocarbon fluid and is dominated by water. Sw in S-1 well was identified to contain hydrocarbon fluid in the form of biogenic gas based on its average Sw value of 40.71%. The determination of the type of content in the reservoir (gas, oil and water) is obtained from the calculation of the formation water saturation (Sw) in the result of general limits of Sw prices for unknown fields where the average range of Sw values for gas is < 50%, the average range of Sw values for oil and gas is <60%, the average range of Sw values for oil is around 50% - 70%, and for water is> 70% [3].

Biogenic gas itself is identified based on existing geochemical data regarding the presence of methane gas in the S-1 Well. This methane gas was identified as biogenic gas because of its almost 100% methane composition and its presence in the low arc basin of the island of Sumatra. Therefore, in the reservoir zone contained in this well there is indicated hydrocarbons in the form of oil and biogenic gas.

Biogenic gas is formed at temperatures that are not too high and at depths that are not too deep. In the S-1 well, biogenic gas was identified at a depth of 5034 - 5090 ft and 5198 - 5216 ft in rocks of Late Miocene age. In S-1 well, it is known that the rocks that act as reservoirs are limestone with 98.95 - 98.96% methane gas content. The formation of this gas occurs in the diagenetic phase wherein this phase forms the source rock which is thermally immature.

The difference between biogenic gas and thermogenic gas usually lies in the diagenetic process and temperature. Biogenic gases are formed by the activity of methanogenic bacteria at low temperatures. Temperature can affect organic substances contained in sediments where an increase in temperature will convert heavy petroleum into light petroleum, then condensate and finally only gas [4].

3.2 Result of Source Rock Identification

Based on the results of qualitative interpretation according to Crain (Figure 6) on the S-1 well, identified source rock is identified in two zones, namely at depths of 6379 - 6388 ft, and 6524 - 6558 ft as shown in Figure 7 and Figure 8.



Figure 6. Interpretation of Immature Source Rock on S-1 well [2].



Figure 7. Source Rock Zone 1 of S-1 well. Figure 8. Source Rock Zone 2 of S-1 well.

Based on biostratigraphic data, it is known that in these two zones also located in Late Miocene age. Main rocks of Middle and Late Miocene age indicate immature maturity. The cross between the DT and resistivity curves according to Crain (2010) in **Figure 6** also shows the immature source rock form. Deposition environment in this zone according to biostratigraphic data is the inner shelf.

The response of gamma ray log is low - middle value in the first SR zone which shows the lithology of the rock is limestone dominated clay. Then the low-high GR log response in the second zone validating the stratigraphic data that the area at this depth has lithology of claystone interbedded with sandstones.

The gamma ray log response is small in both zones, namely in the range of 20-73 API, then the NPHI value has a range of 8-20% and RHOB 2.13 - 2.45 g / cc. For the resistivity log has a range of values large enough that is 0.5 - 66.8 ohm.m,

The Nias Basin's position in the fore-arc region between Sumatra Island and the Indian Ocean results in a relatively low geothermal gradient and heat flow in this basin, which is around 1.2 HFU on average [13]. This low heatflow and geothermal gradient are ideal for biogenic gas formation. The temperature value in a rock chamber, is one of the important parameters in the process of determining the maturity of organic matter, to predict the maturity of hydrocarbons in sedimentary rocks [5].

3. Reservoir and Source Rock Distribution Area

Correlation of the reservoir area of five well in the Nias Basin is done to determine the existence of source rock and reservoir distribution contained in the S-1 well. It can be seen in **Figure 9** and **Table 3**, that in this study area immature source rock and biogenic gas reservoirs in identified.



Figure 9. Reservoir and Source Rock Distribution Area Model.

Depth 1 (ft)	Depth 2 (ft)	Age	Lithology	Petroleum System
5026	5216	Late Miocene	Limestone	Biogenic Gas Reservoir
6379	6558	Late Miocene	Clay	Immature Source Rock

 Table 3. Reservoir and source rock existence in S-1 well.

The biogenic gas reservoir in S-1 well has limestone lithology of Late Miocene age and immature source rock in the lithology of silty clay on a Late Miocene rocks. It can be seen that the study area is dominated by Late-Miocene rocks where at this age the limestone growth in the Nias Basin is very intensive due to the quiet period and lack of material supply from the mainland so that these rocks are the main target in the search for reservoirs.

4. Conclusions

Based on the outcome of this research, it can be concluded that:

Biogenic gas reservoir zones in the S-1 Well were identified as being in two zones at depths of 5026-5130 ft and 5198-5216 ft which were qualitatively shown in permeable layers (small value GR) and the separation between NPHI and RHOB, but qualitative interpretation less supportive because of the low resistivity value in the interest zone. While quantitative interpretation is very supportive based on PHIE value 16.89 - 17.18 ohm.m and Sw is around 39.90 - 41.51%. The immature source rock layer is qualitatively determined by the separation form of the sonic and resistive log curves with a range of sonic log values of 101-120 us/ft and resistivity logs of 2.15 - 2.39 ohm.m on silty clay lithology of Late Miocene rocks.

References

- [1] Asquith G B and Gibson C R 1982 *Basic Well Log Analysis for Geologists* American Association of Petroleum Geologists USA.
- [2] Crain E R 2010 Crain's Petrophysical Handbook www.spec2000.net/ (access on 5 March 2019)
- [3] Dewanto O 2016 *Petrofisika Log* Universitas Lampung CV Anugrah Utama Raharja ISBN: 978-602-6238-88-7.
- [4] Dewanto O, Mulyanto B S, Rustadi and Wibowo R C 2017 Determining the Temperature of Shale Material Conversion Into Crude Oil Based on Organic Clay and Organic Carbonate Test Outside Reservoir *International Journal of Mechanical and Mechatronics Engineering, IJMME* 17 No:05 ISSN: 2077-124X (Online) 2227-2771 (Print) 84-892.
- [5] Dewanto O, Rizky S, Mulyanto B S and Rustadi 2019 The Maturity Estimation of Material Organic in CaCO3 with Determining Tmax and Energy Activation Using Pyrolysis Method *Journal of Computational and Theoretical Nanoscience* 16, No.1–12.
- [6] Harsono A 1997 Evaluasi Formasi dan Aplikasi Log Schlumberger Oilfield Services Jakarta.
- [7] Karlina D A dan Santosa B J 2016 Prediksi Log TOC dan S2 dengan Menggunakan Teknik ΔLog Resistivity Jurnal Sains dan Seni ITS 5/2 20-24.
- [8] Katz B 1995 Biogenic Gas -Its Formation and Economic Significance *Proceedings of Indonesia Petroleum Association 24th Annual Convention.*
- [9] Koesoemadinata R P 1980 Geologi Minyak dan Gas Bumi Jilid 1 dan 2 Institut Teknologi Bandung.
- [10] Lubis S 2015 Prospeksi Gas Methan Biogenic Perairan Dangkal: Sumber Gas Non Konvensional Short Course on SM IAGI UNPAD Jatinangor.
- [11] Mulyanto B S, Dewanto O and Rizky S 2018 Determining Layer Oil Shale as New Alternative Energy Sources Using Core Analysis and Well Log Method International Journal of Engineering & Technology ISSN: 2227524X 7 No:4.36 941-949.
- [12] Phoa R, Bradley K, and Camp Q V 1973 Laporan Penelitian Gas Biogenik Cekungan Nias Bandung Union Oil Company.
- [13] Pusat Penelitian dan Pengembangan Geologi Kelautan (PPPGL) 2018 Laporan Penelitian GasBiogenik Cekungan Nias Bandung.
- [14] Rice D D and Claypool G E 1981 Generation, Accumulation, and Resources Potential of Biogenic Gas American Association of Petroleum Geologists Bulletin 65 No.1 5-25.
- [15] Schlumberger 1989 Log Interpretation Principles/Application, Seventh Printing Texas.
- [16] Schoell M 1988 Multiple Origin of Methane in the Earth Chemical Geology 71 1-10.

Your final check of Your ICTAP's Article (Article No. 21)

\bigcirc mail. \leftarrow \rightarrow	google.com × M Your fina C A mail.google.com/mail/u/0/#s	al check of Your ICTAP's Article (X 📝 Hasil Cari Yahoo untuk google translate X 🤧 Google Translate X + V - D X search/ictap2019/FMfcgxwHMjvMfVzjLmGkCkLImzHjkmJB & & & + D 😵 :
=	M Gmail	Q ictap2019 × ☶ • Active ▼ ⑦ ✿ ☷ Google 🌍
Mail	Compose	← I I I C C C C C C C C C C C C C C C C
Chat Chat Spaces	 ➢ Important ➢ Sent ☑ Drafts 11 	ICTAP 2019 <ictap2019@gmail.com> to me ↓ Dear Authors,</ictap2019@gmail.com>
Meet	Categories Categories Social 323 Updates 181	Congratulation that your article is ready to be submitted to the IOP soon. In order to be sure that your article will be accepted and then be published by the IOP, we ask you to check again at least these items: 1. Does your article already obey the IOP Template?
	□ Forums 77 ▷ Promotions 244 ∨ More	2. Is the similarity of your article very low (there is no maximum limit of the similarity percentage from the IOP, but we think you should press the similarity of your article is lower than 20%, hopefully it is enough based on the IOP' standard)? 3. Did you already do the proofread-check e.g. with Grammarly?
	Labels +	We ask at least those items, because you are responsible to your article when it is accepted or rejected by the IOP. We would inform you: 1. If vour article is accepted by the IOP. vou don't need to pay anything to IOP. because your payment for ICTAP is
ord	las dewanto.pdf	Show all

🚷 mail.	google.com × M Y	ur final check of Your ICTAP's Article 🗙 🗹 Hasil Cari Yahoo untuk google translate 🗙 Soogle Translate 🗙 + V - D X
$\leftarrow \rightarrow$	C a mail.google.com/mail/u	′0/#search/ictap2019/FMfcgxwHMjvMfVzjLmGkCkLlmzHjkmJB 🛛 🛞 🖻 🛠 🖈 🗖 🌍 🗄
=	M Gmail	Q ictap2019 × ☵ • Active ▼ ⑦ ‡ Hi Google 🌍
(99+) Mail	Compose	← ① ÎI ①
Chat Chat Spaces Meet	♥ Snoozed ▶ Important ▶ Sent □ Drafts • ○ Categories 32 ③ Updates 1 □ Forums 24 ∨ More 4 Labels . .	 We ask at least those items, because you are responsible to your article when it is accepted or rejected by the IOP. We would inform you: If your article is accepted by the IOP, you don't need to pay anything to IOP, because your payment for ICTAP is already included for publishing in IOP. We (the ICTAP's Organizing Committee) will pay it to the IOP. If your article is rejected by the IOP, we (the ICTAP's Organizing Committee) still should pay it to the IOP. It means, you cannot withdraw your money from us (The ICTAP's Organizing Committee) when your article is rejected by the IOP. We would also inform you, please don't put any footer or header in your article. Please also don't change the title/subject of this email. We are waiting the final version of your article maximum 7 days after you receive this email. If you don't reply this email or if you don't send the final version of your article after 7 seven days since you received this email, we will submit the last version of your article which we have. Thank you very much for your cooperation.
		The ICTAP's Organizing Committee
ror ord	as dewanto.pdf	Show all X
	H C 🖬 🕏 🚱	w UV sangat tinggi へ 🔞 😳 吟 🗉 印 🗤 13:28 30/03/2023



🚷 mail.	google.com X 🗙 Your fir	al check of Your ICTAP's Article 🗙 📝 Hasil Cari Yahoo untuk google translate 🗙 😋 Google Translate 🗙 + 🗸 - 🗆 X
$\leftarrow \rightarrow$	C mail.google.com/mail/u/0/#	search/ictap2019/FMfcgxwHMjvMfVzjLmGkCkLlmzHjkmJB 🛛 🕸 🔂 🛊 🗖 🌍 🗄
=	M Gmail	Q ictap2019 × ☵ • Active ▼ ⑦ ۞ ⅲ Google 🌍
Mail Chat Spaces	 Compose Snoozed Important Sent Drafts 11 Categories 	 ✓ Image: Construction of the con
CH Meet	Social 323 ③ Updates 181 ➡ Forums 77 ♥ Promotions 244 ✓ More	We would also inform you, please don't put any footer or header in your article. Please also don't change the title/subject of this email. We are waiting the final version of your article maximum 7 days after you receive this email. If you don't reply this email or if you don't send the final version of your article after 7 seven days since you received this email, we will submit the last version of your article which we have. Then have many for your article after 7 seven days since you received this email, we will
	Labels +	Best regards, The ICTAP's Organizing Committee
	AP_Ordas Dewantdocx AP_ORdas Dewantdo	العسمادة.pdf 30°C Sebagian cerah へ الح التي التي التي التي التي التي التي التي

PAPER • OPEN ACCESS

Identification of biogenic gas reservoir zone using log, petrophysics and geochemical data in S-1 well of Nias basin, North Sumatera

To cite this article: O Dewanto et al 2020 J. Phys.: Conf. Ser. 1572 012037

View the article online for updates and enhancements.



IOP ebooks[™]

Bringing together innovative digital publishing with leading authors from the global scientific community.

Start exploring the collection-download the first chapter of every title for free.

This content was downloaded from IP address 114.125.251.239 on 25/10/2020 at 12:09

Identification of biogenic gas reservoir zone using log, petrophysics and geochemical data in S-1 well of Nias basin, **North Sumatera**

O Dewanto^{1*}, Maulina¹ and T B Nainggolan²

¹Geophysics Engineering, Engineering Faculty, University of Lampung, Bandar Lampung 35145, Indonesia

² Marine Geological Research and Development Center, Jalan Dr. Djunjunan No.236, Bandung 40174, Indonesia

*ordas.dewanto@eng.unila.ac.id

Abstract. The fore-arc basin has been become a target of reservoir searching for a long time based on previous expert studies, where the indications of Late-Miocene carbonate age that could act as a hydrocarbon reservoir was found. S-1 Well located in the Nias Basin, one of the fore-arc basin located in West of Sumatera. As the object of this study, it is hoped that the hydrocarbon reservoir in the fore-arc basin is expected to be discovered and to identify the characteristics of rocks that potential to become hydrocarbon reservoirs. Geochemical data becomes supporting data regarding the presence of gases that are identified as biogenic gases because of the content of methane as the main composition. Identification of the existence of reservoir zones and source rock is done by qualitative interpretation of log data from the S-1 well. Then, the petrophysical parameters are analyzed in the form of shale volume (Vsh), effective porosity, resistivity water (Rw), and water saturation (Sw) to determine the type of reservoir's fluid. The results of the interpretation indicated that the presence of biogenic gas was detected in Late-Miocene with limestone lithology with Sw value 39.90 - 41.51 %.

Keywords: petrophysical, shale volume, effective porosity, water saturation

1. Introduction

The existence of shale material in Indonesia is indeed quite a lot, so it is estimated that in the next few years there will be many sources of oil and gas [4]. However, the process of changing material into oil and gas requires a very long time [4] so that using oil and gas is increasingly rare and difficult to do. This makes biogenic gas become a solution as an alternative energy source to replace the using of oil and natural gas. Biogenic gas is an environmentally friendly type of fuel because it produces less carbon dioxide than other types of fuel. In addition, the investment costs of biogenic gas are cheaper than non-conventional gas because of its more general existence of 1,000 m on the sea bed, so researchers are now more focused on biogenic gas research that is more profitable to do.

Biogenic gas is a flammable hydrocarbon gas, has the shortest carbon chain (C1) so it is the lightest gas, which is about 0.7 lighter than air [14]. Therefore, if used as an energy source, biogenic gas is a

Content from this work may be used under the terms of the Creative Commons Attribution 3.0 licence. Any further distribution of this work must maintain attribution to the author(s) and the title of the work, journal citation and DOI. Published under licence by IOP Publishing Ltd 1

type of fuel that is environmentally friendly. Biogenic gas is a gas with a methane content> 98% and has a low S and CO2 content and can be detected in the presence of the carbon isotope δ 13C CH4 which is -62 to -66% [8]. Biogenic gas contained in this earth almost reaches 20% of all natural gas sources [14] but its presence is spread in small gas bags of various sizes and at varying depths [10].

The formation of this gas occurs in the diagenetic phase where in this phase forms the source rock which is thermally immature. Methane gas is formed with the following main processes [15]:

- 1. Acetate bacterial fermentation in the chemical-rich sedimentary layer (gas charged sediment) chemically: $CH_3COOH \rightarrow CH_4 + CO_2$.
- 2. The process of reducing CO2 by bacteria from naturally occurring volcanic or magmatic rocks: $CO_2 + 2H_2O \rightarrow CH_4$.

The Nias Basin, a fore arc basin, characterizes a cool basin with a smaller geothermal gradient up to the average [8]. This affects the process of maturation of existing host rock. Because the geothermal gradient or heat flow is low, the heat received by the rocks is also small so that the Miocene-aged parent rock in this basin is generally immature. However, in older or deep-buried rocks it might reach maturity. Temperature can affect organic substances contained in sediments where an increase in temperature will convert heavy petroleum into light petroleum, then condensate and finally only gas [4].

Determination and analysis of reservoir parameters can be done by two methods, namely core analysis in the laboratory and interpretation of log data [11]. As for this research, a log data interpretation in the form of a quick-look qualitative interpretation and a quantitative interpretation in the form of petrophysical analysis is carried out in an effort to determine the detailed conditions of a petroleum system. Petrophysical analysis itself is a process that is carried out to validate the hydrocarbon density and determine the characteristics of the hydrocarbon reservoir and source rock.

2. Research Method

2.1 Reservoir Qualitative Interpretation

Qualitative reservoir interpretation is done by lithology zoning and hydrocarbon prospect area analysis using gamma ray, resistivity, RHOB and NPHI logs. First, a quick-look reservoir zone identification is based on NPHI and RHOB log separations. This separation indicates the existence of a reservoir where the reservoir has the characteristics of a low NPHI and RHOB values. Then the existence of a hydrocarbon reservoir is also characterized by a medium resistivity (Rt) value for oil and a high resistivity value for gas. In addition, the value of gamma ray is also important in identifying the quantity of clay found in rocks. The gamma ray log records the gamma ray radiation of rocks which shows the radioactive intensity in it. Clay minerals contain a large quantity of radioactivity and high clay content is found in claystone or shale lithology.

2.2 Reservoir Quantitative Interpretation

Once the hydrocarbon reservoir zone is identified through a quick-look analysis, a full-analysis is carried out in the form of petrophysical analysis through quantitative interpretation. To conduct petrophysical analysis, the shale content of rocks in the study area is a parameter whose value must first be determined. Calculation of clay content in S-1 Wells uses the Larionov tertiary equation because the age of the rock is relatively young based on the stratigraphy of the existing Nias Basin as follows [1]:

$$Vs = 0.08336 \left(2^{3.7 x \, \text{IGR}} - 1\right) \tag{1}$$

Then porosity (\emptyset) calculation using the equation as follows [15]:

$$\emptyset_{e} = \sqrt{\frac{\emptyset_{Ncor}^{2} + \emptyset_{Dcor}^{2}}{2}} \tag{2}$$

Resistivity water (Rw) determination by plotting pickett plots in the software Interactive Petrophysics in areas filled with water (Sw=1). This zone is characterized by a very low resistivity (Rt) value and coinciding with the NPHI and RHOB log curves. Then calculating water saturation (Sw) using the Indonesian Sw equation so that it does not neglect the presence of impurities contained in rock formations as follows:

$$\frac{1}{\sqrt{R_t}} = \left(\sqrt{\frac{\varphi_{\theta}^m}{a \times R_w}} + \frac{v_{sh}^{1-0,5}v_{sh}}{\sqrt{R_{sh}}}\right) \times S_w^{\frac{n}{2}}$$
(3)

2.3 Source Rock Qualitative Interpretation

For qualitative interpretation of source rock, gamma ray logs, resistivity logs and sonic logs are used. Based on the separation form of the sonic and resistivity log curves, the source rock type and its presence can be known in the well. This bedrock is usually in shale or siltstone lithology which has impermeable rock characteristics with high GR values, very high sonic log values and low value of resistivity logs.

The resistivity and sonic logs are overlaid to make it easier to see the shape of the separation. The first rule that needs to be known is when the GR (or SP) deflection to the left means the zone is clean and reservoir rock can be indicated. When the GR is deflected to the right, it indicates shale lithology (not characteristic of reservoir rocks). Then, the second rule is the porosity log (in this case the sonic log) is set on a high to low scale. Then the third rule is the resistivity log set on a low to high scale. High resistivity indicates the presence of hydrocarbons or low porosity, while low resistivity indicates an indication of shale or water zone [2].

The separation between resistivity log and DT log shows anomaly. When separation is formed to the right of the baseline it can be estimated that the separation shows the existence of source rock, and the rock is mature (mature). Whereas the separation formed to the left of the baseline shows that the depth is estimated as source rock, but immature, or as coal, and other non-source rock. Mature source rock has characteristics of high resistivity value, and high sonic log, while immature source rock has characteristic value with low resistivity value and not too high sonic log. Large log resistivity and sonic log separations are called $\Delta LogR$ [7].

2.4 Distribution Area of Biogenic Gas Reservoirs Modelling

Qualitative interpretation of source rock zones based on the overlay of DT and resistivity logs, and the biogenic gas reservoir based on quantitative interpretation and model of S-1 well can be identified.

3. Result and Discussion

3.1 Result of Reservoir Zone Identification

S-1 well has a total depth of 6990 ft. The presence of gas can be identified using qualitative log interpretation using gamma ray log, resistivity log, and separation between RHOB and NPHI logs as shown in **Figure 1** and **Figure 2**. In this well, reservoirs were identified in two zones, at depths of 5026-5130 ft, and 5198-5216 ft.

This is also evidenced by the small gamma ray log response in the both zones, namely in the range of 20 - 73 API, then the NPHI value has a range of 8 - 20 % and RHOB 2.13 - 2.45 g/cc. The resistivity log has a range a large enough value that is 0.5 - 66.8 ohm.m, so it does not support interpretation. The presence of th gas is also verified by geochemical data that explains the presence of gas with high methane composition, which is valued at 98.96% at depths of 5034 - 5090 ft and 98.95% at depths of 5198 - 5216 ft as listed on **Table 1** below.

Based on S-1 well biostratigraphic data (Figure 3) it is known that in the both zones has Late Miocene age which according to the Nias Basin stratigraphy that the growth of reef limestone at that time is intensive in the depositional environment bathyal to the outer shelf environment.







Figure 2. Reservoir Zone 2 based on Qualitative Interpretation.

Figure 3. S-1 Well Stratigraphy Columnar Section (Union Oil Company of Indonesia) [12].

	S-1			
	Water	Depth		
Components	DST 2	DST 3		
Components	5198 FT – 5216 FT	5034 FT – 5090 FT		
	Late Miocene	Late Miocene		
	%	%		
Hydrogen	-	-		
Helium	-	-		
Carbon Monoxide	-	-		
Hydrogen Sulphide	-	-		
Carbon Dioxide	0.29	0.23		
Oxygen	-	-		
Nitrogen	0.56	0.61		
Methane	98.95	98.96		
Ethane	0.18	0.19		
Propane	0.02	0.01		
Iso-Butane	-	-		
n-Butane	-	-		
Iso Pentane	-	-		
n-Pentane	-	-		
Hexanes	-	-		
Hexanes Plus	-	-		
Total Percentage	100	100		
Molecular Weight	16.222	16.209		
Gravity	0.56	0.5595		

Table 1. Geochemical Data of S-1 Well	(Union Oil Company of Indonesia,	1978).
---------------------------------------	----------------------------------	--------

Table 2. Indicated Fluid based on Quantitative Interpretation.

Zone	Depth	Vsh (%)	PHIE (%)	Rw	Sw Indo (%)	Fluid
1	5026 - 5130	21.25	16.89	0.04	41.51	Biogenic Gas
2	5198 - 5216	21.25	17.18	0.04	39.90	Biogenic Gas

A good formation as a reservoir is a formation with little shale content because the presence of large amounts of shale can inhibit rocks from flowing fluid. This type of formation is important to calculate, to know the type of Sw equation that will be used later. Based on **Table 2**, it is known that in the S-1 Well, there is an impurity content of 21.25%

The large porosity allows rocks to hold more hydrocarbon fluids. The porosity calculation is performed until an effective porosity value is obtained, that is the porosity which is not influenced by the clay content. This is done to avoid errors in interpretation where clay content can bind large amounts of formation water so that the calculation will be unrepresentative. It can be seen in **Table 2** that the total porosity value of the reservoir zone in the S-1 Well is greater than the effective porosity. This difference in value is not too large at around 0.5%. The effective porosity value itself is good according to scale of determining whether or not the quality of the porosity value of a reservoir rock [9].

The water-bearing zone in the S-1 Well is at a depth of 5230 - 5242 ft where the response curve of the log can be seen in Figure 4.

Figure 4. Water bearing zone in S-1 well.

Figure 5. Rw on S-1 Well.

Rw in well S-1 as we can see on Figure 5 above, shows a value of Rw 0.0359 ohm.m where this value is plotted in areas with low log resistivity values below 10 ohms.m and indicates the presence of water bearing zone.

Formation water saturation is the ratio of the pore volume filled by water to the total porosity volume [6]. The water saturation (Sw) value represents the water content in a rock formation. The greater the value of Sw, it is indicated that the formation contains only a small amount of hydrocarbon fluid and is dominated by water. Sw in S-1 well was identified to contain hydrocarbon fluid in the

The 9th International Conference on Theoretic	al and Applied Physics (IC	CTAP)	IOP Publishing
Journal of Physics: Conference Series	1572 (2020) 012037	doi:10.1088/1742	-6596/1572/1/012037

form of biogenic gas based on its average Sw value of 40.71%. The determination of the type of content in the reservoir (gas, oil and water) is obtained from the calculation of the formation water saturation (Sw) in the result of general limits of Sw prices for unknown fields where the average range of Sw values for gas is < 50%, the average range of Sw values for oil and gas is <60%, the average range of Sw values for oil is around 50% - 70%, and for water is >70% [3].

Biogenic gas itself is identified based on existing geochemical data regarding the presence of methane gas in the S-1 Well. This methane gas was identified as biogenic gas because of its almost 100% methane composition and its presence in the low arc basin of the island of Sumatra. Therefore, in the reservoir zone contained in this well there is indicated hydrocarbons in the form of oil and biogenic gas.

Biogenic gas is formed at temperatures that are not too high and at depths that are not too deep. In the S-1 well, biogenic gas was identified at a depth of 5034 - 5090 ft and 5198 - 5216 ft in rocks of Late Miocene age. In S-1 well, it is known that the rocks that act as reservoirs are limestone with 98.95 - 98.96% methane gas content. The formation of this gas occurs in the diagenetic phase wherein this phase forms the source rock which is thermally immature.

The difference between biogenic gas and thermogenic gas usually lies in the diagenetic process and temperature. Biogenic gases are formed by the activity of methanogenic bacteria at low temperatures. Temperature can affect organic substances contained in sediments where an increase in temperature will convert heavy petroleum into light petroleum, then condensate and finally only gas [4].

3.2 Result of Source Rock Identification

Based on the results of qualitative interpretation according to Crain (Figure 6) on the S-1 well, identified source rock is identified in two zones, namely at depths of 6379 - 6388 ft, and 6524 - 6558 ft as shown in Figure 7 and Figure 8.

Figure 6. Interpretation of Immature Source Rock on S-1 well [2].

Figure 8. Source Rock Zone 2 of S-1 well.

Based on biostratigraphic data, it is known that in these two zones also located in Late Miocene age. Main rocks of Middle and Late Miocene age indicate immature maturity. The cross between the DT and resistivity curves according to Crain (2010) in **Figure 6** also shows the immature source rock form. Deposition environment in this zone according to biostratigraphic data is the inner shelf.

The response of gamma ray log is low - middle value in the first SR zone which shows the lithology of the rock is limestone dominated clay. Then the low-high GR log response in the second zone validating the stratigraphic data that the area at this depth has lithology of claystone interbedded with sandstones.

The gamma ray log response is small in both zones, namely in the range of 20-73 API, then the NPHI value has a range of 8-20% and RHOB 2.13 - 2.45 g / cc. For the resistivity log has a range of values large enough that is 0.5 - 66.8 ohm.m,

The Nias Basin's position in the fore-arc region between Sumatra Island and the Indian Ocean results in a relatively low geothermal gradient and heat flow in this basin, which is around 1.2 HFU on average [13]. This low heatflow and geothermal gradient are ideal for biogenic gas formation. The temperature value in a rock chamber, is one of the important parameters in the process of determining the maturity of organic matter, to predict the maturity of hydrocarbons in sedimentary rocks [5].

3.3. Reservoir and Source Rock Distribution Area

Correlation of the reservoir area of five well in the Nias Basin is done to determine the existence of source rock and reservoir distribution contained in the S-1 well. It can be seen in **Figure 9** and **Table 3**, that in this study area immature source rock and biogenic gas reservoirs in identified.

1572 (2020) 012037 doi:10.1088/1742-6596/1572/1/012037

Figure 9. Reservoir and Source Rock Distribution Area Model.

Depth 1 (ft)	Depth 2 (ft)	Age	Lithology	Petroleum System
5026	5216	Late Miocene	Limestone	Biogenic Gas Reservoir
6379	6558	Late Miocene	Clay	Immature Source Rock

Table 3. Reservoir and source rock existence in S-1 well.

The biogenic gas reservoir in S-1 well has limestone lithology of Late Miocene age and immature source rock in the lithology of silty clay on a Late Miocene rocks. It can be seen that the study area is dominated by Late-Miocene rocks where at this age the limestone growth in the Nias Basin is very intensive due to the quiet period and lack of material supply from the mainland so that these rocks are the main target in the search for reservoirs.

4. Conclusions

Based on the outcome of this research, it can be concluded that:

- 1. Biogenic gas reservoir zones in the S-1 Well were identified as being in two zones at depths of 5026-5130 ft and 5198-5216 ft which were qualitatively shown in permeable layers (small value GR) and the separation between NPHI and RHOB, but qualitative interpretation less supportive because of the low resistivity value in the interest zone. While quantitative interpretation is very supportive based on PHIE value 16.89 - 17.18 ohm.m and Sw is around 39.90 - 41.51%.
- 2. The immature source rock layer is qualitatively determined by the separation form of the sonic and resistive log curves with a range of sonic log values of 101-120 us/ft and resistivity logs of 2.15 -2.39 ohm.m on silty clay lithology of Late Miocene rocks.

Journal of Physics: Conference Series

5. References

- [1] Asquith G B and Gibson C R 1982 *Basic Well Log Analysis for Geologists* American Association of Petroleum Geologists USA.
- [2] Crain E R 2010 Crain's Petrophysical Handbook www.spec2000.net/ (access on 5 March 2019)
- [3] Dewanto O 2016 *Petrofisika Log* Universitas Lampung CV Anugrah Utama Raharja ISBN: 978-602-6238-88-7.
- [4] Dewanto O, Mulyanto B S, Rustadi and Wibowo R C 2017 Determining the Temperature of Shale Material Conversion Into Crude Oil Based on Organic Clay and Organic Carbonate Test Outside Reservoir International Journal of Mechanical and Mechatronics Engineering, IJMME 17 No:05 ISSN: 2077-124X (Online) 2227-2771 (Print) 84-892.
- [5] Dewanto O, Rizky S, Mulyanto B S and Rustadi 2019 The Maturity Estimation of Material Organic in CaCO3 with Determining Tmax and Energy Activation using Pyrolysis Method *Journal of Computational and Theoretical Nanoscience* **16**, No.1–12.
- [6] Harsono A 1997 Evaluasi Formasi dan Aplikasi Log Schlumberger Oilfield Services Jakarta.
- [7] Karlina D A dan Santosa B J 2016 Prediksi Log TOC dan S2 dengan Menggunakan Teknik ΔLog Resistivity Jurnal Sains dan Seni ITS 5/2 20-24.
- [8] Katz B 1995 Biogenic Gas -Its Formation and Economic Significance *Proceedings of Indonesia Petroleum Association 24th Annual Convention.*
- [9] Koesoemadinata R P 1980 Geologi Minyak dan Gas Bumi Jilid 1 dan 2 Institut Teknologi Bandung.
- [10] Lubis S 2015 Prospeksi Gas Methan Biogenic Perairan Dangkal: Sumber Gas Non Konvensional Short Course on SM IAGI UNPAD Jatinangor.
- [11] Mulyanto B S, Dewanto O and Rizky S 2018 Determining Layer Oil Shale as New Alternative Energy Sources Using Core Analysis and Well Log Method International Journal of Engineering & Technology ISSN: 2227524X 7 No:4.36 941-949.
- [12] Phoa R, Bradley K, and Camp Q V 1973 Laporan Penelitian Gas Biogenik Cekungan Nias Bandung Union Oil Company.
- [13] Pusat Penelitian dan Pengembangan Geologi Kelautan (PPPGL) 2018 Laporan Penelitian Gas Biogenik Cekungan Nias Bandung.
- [14] Rice D D and Claypool G E 1981 Generation, Accumulation, and Resources Potential of Biogenic Gas American Association of Petroleum Geologists Bulletin 65 No.1 5-25.
- [15] Schlumberger 1989 Log Interpretation Principles/Application, Seventh Printing Texas.
- [16] Schoell M 1988 Multiple Origin of Methane in the Earth Chemical Geology 71 1-10.