

PAPER • OPEN ACCESS

Preface

To cite this article: 2019 *J. Phys.: Conf. Ser.* **1338** 011001

View the [article online](#) for updates and enhancements.


You may also like

- [Development of a sinusoidal phase-shifting self-mixing interferometer for real-time displacement measurement with nanometer accuracy](#)
Wei Xia, Zhenyu Yang, Qiang Liu et al.
- [International Workshop on Statistical-Mechanical Informatics 2008 \(IW-SMI 2008\)](#)
Masahito Hayashi, Jun-ichi Inoue, Yoshiyuki Kabashima et al.
- [A new profile roughness measurement approach for involute helical gears](#)
G Koulin, J Zhang, R C Frazer et al.



Free the Science Week 2023 April 2–9

Accelerating discovery through
open access!

 www.ecsdl.org [Discover more!](#)

The banner features a dark blue background with a futuristic, glowing blue interface. A hand is shown pointing at a central circular element that contains a white padlock icon, symbolizing open access. The text is in white and light blue, with the ECS logo and website URL in white.

Preface

The International Conference on Applied Sciences Mathematics and Informatics (ICASMI) is an annual conference hosted by University of Lampung that brings together academics, scholars and researchers from around the world to meet and exchange the latest ideas and discuss issues concerning all fields of sciences, mathematics, informatics and their application. It also allows representatives of industry, government employers and postgraduate students to have an opportunity to discuss with experts on some issues they concern.

The theme for ICASMI 2018: “The Contribution of Sciences on Sustainable Valorization of Natural Resources” is to highlight the role of sciences tackling problems and creating synergies with other fields on sustainable valorization of natural resources. The conference will provide researchers and scientists from mathematics and computer science, researchers from various application areas such as physics, chemistry, life sciences, and engineering, as well as in education and social fields, to discuss problems and solutions in the area, to identify new issues, and to shape future directions for research.

We would like to acknowledge all of those who have supported ICASMI 2018. Each individual and institutional help were very important for the success of this conference. Especially we would like to thank the organizing committee for their valuable advices in the organization and helpful peer review of the papers.

We hope that ICASMI 2018 will be a forum for excellent discussions that will put forward new ideas and promote collaborative researches. We are sure that the proceedings will serve as an important research source of references and the knowledge, which will lead to not only scientific and engineering progress but also other new products and processes.

Dr. Junaidi, M.Sc.



Table of contents

Volume 1338

2019

◀ Previous issue Next issue ▶

The 2nd International Conference on Applied Sciences Mathematics and Informatics 9–11 August 2018, Bandar Lampung, Indonesia

Accepted papers received: 29 August 2019

Published online: 01 October 2019

Open all abstracts

Preface

OPEN ACCESS 011001

Preface

+ Open abstract  View article  PDF

OPEN ACCESS 011002

Peer review statement

+ Open abstract  View article  PDF

Papers

Chemistry

OPEN ACCESS 012001

Difference in Characteristic of Concentrate Powder of Corn (*Zea mays var. indentata*) Fermented by *Bifidobacterium brevis* as Natural Folic Acid Fortificant

Aspiyanto, A Susilowati, P D Lotulung and Y Maryati

+ Open abstract  View article  PDF

OPEN ACCESS 012002

Characteristic of Biomass of Corn (*Zea Mays Identata*) Fermented by *Lactobacillus Acidophilus* and *Bifidobacterium Brevis* as Source of Natural Folic Acid

A Susilowati, Y Maryati, Aspiyanto and P D N Lotulung

+ Open abstract  View article  PDF

This site uses cookies. By continuing to use this site you agree to our use of cookies. To find out more, see our Privacy and Cookies policy.

OPEN ACCESS 012003
Screening of Marine Microalgae Collected from Wakatobi as Anti-Tyrosinase



S Raharjo, V N Fatanah, D Susilaningsih, M Kasim, P E Susilawati, Muzuni, D Y Rahman and Tien

[+ Open abstract](#) [View article](#) [PDF](#)

OPEN ACCESS

012004

Copoly Eugenol Crosslinked Dialylphthalate 8% as a Carrier in Phenol and Pb(II) Metal Transport

A A Kiswandono, S Hadi, Mudasir, F Sinjia, M Y Sari and M Irfan

[+ Open abstract](#) [View article](#) [PDF](#)

OPEN ACCESS

012005

Adsorption of Polycyclic Aromatic Hydrocarbons using Low-Cost Activated Carbon Derived from Rice Husk

Rinawati, D Hidayat, R Supriyanto, D F Permana and Yunita

[+ Open abstract](#) [View article](#) [PDF](#)

OPEN ACCESS

012006

Optimization of Total Anthocyanin Extraction from Brown Rice (*Oryza nivara*)

V J Anggraeni, L Ramdanawati and W Ayuantika

[+ Open abstract](#) [View article](#) [PDF](#)

OPEN ACCESS

012007

Fatty Acid Analysis of Marine Microalgae *Chlorella vulgaris* in Modified Medium Used GC-FID

D Kurnia, A Yuliantini, I S Cendana and Z Nurachman

[+ Open abstract](#) [View article](#) [PDF](#)

OPEN ACCESS

012008

Characterization of Fe, Ni, Pb Standard Solution using One-point Calibration Methods

E M Handayani, I Komalasari, O Zuas, C Elishian and R Ketrin

[+ Open abstract](#) [View article](#) [PDF](#)

OPEN ACCESS

012009

Docking Interaction of Chromium(III) Phenylalanine with Protein Tyrosine Phosphatase

Y Ambarwati, M A Martoprawiro, I Mulyani, Ismunandar and D Onggo

[+ Open abstract](#) [View article](#) [PDF](#)

OPEN ACCESS

012010

Synthesis 4-Piperomorpholine from Piperine

S Bahri, Y Ambarwati, M Iqbal and A A Baihaqy

[+ Open abstract](#) [View article](#) [PDF](#)

This site uses cookies. By continuing to use this site you agree to our use of cookies. To find out more, see our [Privacy and Cookies policy](#).



OPEN ACCESS

012011

Utilization of Jernang Resin (*Daemonorops draco*) as the Basic Material for Making Liquid Wound Medicine

Yusnelti and Muhaimin

[+ Open abstract](#) [View article](#) [PDF](#)

OPEN ACCESS

012012

The Potency Study of Organotin(IV) 3-Nitrobenzoate Compounds as Antimalarial Agents

Sutopo Hadi, Noviany, Hardoko Insan Qudus and Pakorn Wattana-Amorn

[+ Open abstract](#) [View article](#) [PDF](#)

OPEN ACCESS

012013

The Effect of Sugarcane Bagasse to Rubber Seed Oil Ratios on The Chemical Composition of Liquid Fuels Produced by Zeolite- γ Catalyzed Pyrolysis

A Simanjuntak, W Simanjuntak, K D. Pandiangan and Z Sembiring

[+ Open abstract](#) [View article](#) [PDF](#)

OPEN ACCESS

012014

The potential of derivatives of organotin(IV) benzoate compounds in medicinal chemistry

Samsuar, Wasinton Simanjuntak, Hardoko Insan Qudus and Sutopo Hadi

[+ Open abstract](#) [View article](#) [PDF](#)

OPEN ACCESS

012015

Characteristics and catalytic activity of zeolite-a synthesized from rice husk silica and aluminium metal by sol-gel method

K D Pandiangan, W Simanjuntak, E Pratiwi and M Rilyanti

[+ Open abstract](#) [View article](#) [PDF](#)

Physics

OPEN ACCESS

012016

The Deposition of Silver (Ag) on a Glass Substrate (SiO_2) using Direct Current Sputtering Method

L Rumiyantri, E S B Ginting, I Aziz, S Sembiring and Warsito

[+ Open abstract](#) [View article](#) [PDF](#)

OPEN ACCESS

012017

Improvement of Electrical Characteristics of Electrochemical Cells made from Sea Water Using Electroplating Method of Cu (Ag)-Zn Electrode as Renewable Energy Source

G A Pauzi, K C Riski, S W Suciyantri, Junaidi, A Surtono, A Supriyanto and Warsito

This site uses cookies. By continuing to use this site, you agree to our use of cookies. To find out more, see our Privacy and Cookies policy.



-
- OPEN ACCESS** 012018
Flow Rate and Volume Control of Fluid Based on Arduino for Synthesis of Silver Nanowires
Junaidi, A S Yusuf, P Y D Iffah, G A Pauzi, A Surtono, S W Suciya, Warsito, K Triyana and Khairurrijal
[+ Open abstract](#) [View article](#) [PDF](#)
-
- OPEN ACCESS** 012019
Measuring of Cassava Starch Content by Using Strain Gauge
A Surtono, P Aprilliana, A Supriyanto, G A Pauzi, Junaidi, S W Suciya and Warsito
[+ Open abstract](#) [View article](#) [PDF](#)
-
- OPEN ACCESS** 012020
Concentration Effect on The Thin Films of Silver Nanowires Fabricated Using Meyer-rod Coating
Junaidi, P A Pontoh, K Triyana and Khairurrijal
[+ Open abstract](#) [View article](#) [PDF](#)
-
- OPEN ACCESS** 012021
Initial Sticking Coefficient Attenuation of Gases in Carbon Monoxide Sensing on Pt₈₀Au₁₄Ti₆
R Marjunus
[+ Open abstract](#) [View article](#) [PDF](#)
-
- Biology**
-
- OPEN ACCESS** 012022
Mammals Biodiversity in Balik Bukit and Balai Kencana Resort, Bukit Barisan Selatan National Park
E Fitria, A A Efendi, I Nurarifin, Sugeng, J Charles and E L Rustiati
[+ Open abstract](#) [View article](#) [PDF](#)
-
- OPEN ACCESS** 012023
Smart Patrol as Monitoring System In Resort Way Nipah Bukit Barisan Selatan National Park
A A Efendi, E Fitria, S P Haryanto, Y Charles and E L Rustiati
[+ Open abstract](#) [View article](#) [PDF](#)
-
- OPEN ACCESS** 012024
Technical Review of Land Usage of Former Limestone Mine for Rubber Plantation in PT Semen Baturaja Tbk for Sustainable Mining Environment
R Juniah, D Susetyo and H Rahmi
[+ Open abstract](#) [View article](#) [PDF](#)



OPEN ACCESS

012025

The Analysis of E-Learning Model with Technology of Acceptance Model (TAM) Method in Faculty of Computer Science Sriwijaya University

A Ibrahim, D Cahyani, M M Nursalim, M Arsita, M Suparman, S Indriyani and Yusmaniarti

[+ Open abstract](#) [View article](#) [PDF](#)**OPEN ACCESS**

012026

The Analysis of Glucose and Vitamin C on Papaya (*Carica papaya L.*) with Different Time Storage

M Kamelia, Supriyadi, N Widiani, Farida and I Damayanti

[+ Open abstract](#) [View article](#) [PDF](#)**OPEN ACCESS**

012027

Cytotoxic Activity Assay of N-Hexane Extract of *Solanum nigrum L.* Fruits Fermented by Kombucha against MCF-7 Breast Cancer Cell Line

R Ziska, A Agustina and Supriadi

[+ Open abstract](#) [View article](#) [PDF](#)**OPEN ACCESS**

012028

Effect of Tapioka Liquid Waste on Growth of *Ipomoea Reptans Poir* Using Floating Raft Hydroponic Technique

N Widiani, N Ulfa, O P Winandari and M Kamelia

[+ Open abstract](#) [View article](#) [PDF](#)**OPEN ACCESS**

012029

Comparative Study on DNA Extraction's Qualitative Analysis of Captive Sumatran Elephant in Elephant Training Center, Way Kambas National Park

E L Rustiati, Priyambodo, T Novianasari, D N Pratiwi, E A Srihanto and L Angeliya

[+ Open abstract](#) [View article](#) [PDF](#)**OPEN ACCESS**

012030

Genome Changes in Multi Drug Resistant Tuberculosis

T U Soleha, Sutyarso and A Sukohar

[+ Open abstract](#) [View article](#) [PDF](#)**OPEN ACCESS**

012031

Analysis of Critical Thinking Skills of Senior High School Students in Biological Learning

R I Sari, P Karyanto and Muzzazinah

[+ Open abstract](#) [View article](#) [PDF](#)

This site uses cookies. By continuing to use this site you agree to our use of cookies. To find out more, see our Privacy and Cookies policy.

012032



Analysis of Argumentation Skills in Biological Learning in Senior High School Students

S Astira, Sajidan and S Dwiastuti

[+ Open abstract](#) [View article](#) [PDF](#)

Mathematics**OPEN ACCESS**

012033

The Locating-Chromatic Number for Certain Operation of Generalized Petersen Graphs $sP(4,2)$

A Irawan, Asmiati, Suharsono and K Muludi

[+ Open abstract](#) [View article](#) [PDF](#)

OPEN ACCESS

012034

Computational Aspects of Some Algorithms for The Multiperiod Degree Constrained Minimum Spanning Tree Problem

Wamiliana, Mustofa Usman, Warsono and Warsito

[+ Open abstract](#) [View article](#) [PDF](#)

OPEN ACCESS

012035

The Locating Chromatic Number of a Disjoint Union of Some Double Stars

Asmiati, L Yulianti, Aldino, Aristoteles and A Junaidi

[+ Open abstract](#) [View article](#) [PDF](#)

OPEN ACCESS

012036

Characteristics of Hazard Rate Functions of Log-Normal Distributions

D Kurniasari, R Widayarni, Warsono and Y Antonio

[+ Open abstract](#) [View article](#) [PDF](#)

OPEN ACCESS

012037

Forecasting of Bandar Lampung's Population Using Growth Mathematical Models

A Nuryaman, M A A F Pamungkas and S Saidi

[+ Open abstract](#) [View article](#) [PDF](#)

OPEN ACCESS

012038

Comparison of Milne-Simpson Method and Hamming Method in Logistic Equation Settlement on Pert Prediksi the People of Bandar Lampung City

D Azis and M Napitupulu

[+ Open abstract](#) [View article](#) [PDF](#)

OPEN ACCESS

012039

Bootstrap Method in Estimation of Mean Squared Error of Beta-Bernoulli Model

This site uses cookies. By continuing to use this site you agree to our use of cookies. To find out more, see our [Privacy and Cookies Policy](#)



[+ Open abstract](#) [View article](#) [PDF](#)

OPEN ACCESS

012040

Dynamics of Temperature and Concentration on Oxidation Reaction Using Reverse Flow Reactor With Periodic Feed Gas Like Square Wave Function: a Numerical Approach

A Nuryaman, R Riyanto and S Saidi

[+ Open abstract](#) [View article](#) [PDF](#)

OPEN ACCESS

012041

The Implementation of Digital Text Coding Algorithm Through A Three Dimensional Mapping Derived From Generalized $\Delta\Delta$ -mKdV Equation Using Mathematica

Notiragayu and L Zakaria

[+ Open abstract](#) [View article](#) [PDF](#)

OPEN ACCESS

012042

On the Comparison of the Methods of Parameter Estimation for Pareto Distribution

Warsono, E Gustavia, D Kurniasari, Amanto and Y Antonio

[+ Open abstract](#) [View article](#) [PDF](#)

OPEN ACCESS

012043

Determining the Number of Connected Vertices Labelled Graph of Order Five with Maximum Number of Parallel Edges is Five and Containing No Loops

Wamiliana, A Nuryaman, Amanto, A Sutrisno and N A Prayoga

[+ Open abstract](#) [View article](#) [PDF](#)

Informatics

OPEN ACCESS

012044

Dijkstra's Algorithm to Find Shortest Path of Tourist Destination in Bali

A Fitriansyah, N W Parwati, D R Wardhani and N Kustian

[+ Open abstract](#) [View article](#) [PDF](#)

OPEN ACCESS

012045

Ethnomathematics batik design Bali island

A Irawan, M Lestari, W Rahayu and R Wulan

[+ Open abstract](#) [View article](#) [PDF](#)

OPEN ACCESS

012046

A Development of Assessment Instruments Analysis Learning Style and Creativity of Elementary School Based on Forward Chaining Method















A A R Awaludin, R Wulan, A Sarwandianto and N Alamsyah

This site uses cookies. By continuing to use this site you agree to our use of cookies. To find out more,

[+ Open abstract](#) [View article](#) [PDF](#)

See our Privacy and Cookies policy.



-
- OPEN ACCESS** 012048
Prediction of Wind Power Model Using Hybrid Method Based on WD-SVM Algorithm: Case Study Pandansimo Wind Farm
 A Prasetyowati, D Sudiana and H Sudibyو
 + Open abstract  View article  PDF
-
- OPEN ACCESS** 012049
Structural Equation Modeling Technique for Social Application of Information Technology User Requirements' Identification
 M I Jambakr, A F Yuzaherdi, J Jauhari, A Putra and R Efendi
 + Open abstract  View article  PDF
-
- OPEN ACCESS** 012050
Implementation of Dynamic Mutual Information and Support Vector Machine for Customer Loyalty Classification
 H Sulistiani, K Muludi and A Syarif
 + Open abstract  View article  PDF
-
- OPEN ACCESS** 012051
E-crm Information System for Tapis Lampung SMEs
 Damayanti, Warsito, Meilinda, P Manurung and S Sembiring
 + Open abstract  View article  PDF
-
- OPEN ACCESS** 012052
Expert System for Pregnant Mothers Treatment and Early Disease Detection for Infants and Toddlers Based on Android (Kasih Ibu)
 B A Sitorus, Aris, P Pribowo and A R Irawati
 + Open abstract  View article  PDF
-
- OPEN ACCESS** 012053
Evaluation of Commercial Feed Replacement Fermented Local Food Mixed on Performance of Male Local Duck
 D Septinova, F fathul and P E Santosa
 + Open abstract  View article  PDF
-
- OPEN ACCESS** 012054
The Implementation of Simple Additive Weighting (SAW) Method in Decision Support System for the Best School Selection in Jambi
 A Ibrahim and R A Surya
 + Open abstract  View article  PDF
-
- OPEN ACCESS** 012055
See our Privacy and Cookies policy.

This site uses cookies. By continuing to use this site you agree to our use of cookies. To find out more,

See our Privacy and Cookies policy.



Analysis of Internet Service Quality Using Internet Control Message Protocol

A Hafiz and D Susianto

[+ Open abstract](#) [View article](#) [PDF](#)

OPEN ACCESS

012056

Semantic SLA for Selecting SAAS ERP

A Hijriani and R Sarno

[+ Open abstract](#) [View article](#) [PDF](#)

OPEN ACCESS

012057

Implementation of Geographic Information System for Micro, Small, and Medium Enterprises (MSMEs) in Lampung Province using Android Platform

A R Irawati, D Kurniawan, M Yusman and M R F Ibrahim

[+ Open abstract](#) [View article](#) [PDF](#)

OPEN ACCESS

012058

Geographic Information System Design for Alumni of Information System Department, Faculty of Computer Science, Sriwijaya University

A Ibrahim, Y Pratomo, E Lestari, Famuhantara, R Adi and Yusmaniarti

[+ Open abstract](#) [View article](#) [PDF](#)

OPEN ACCESS

012059

Perceptions of Online Taxi Utilization In Bandar Lampung Using UTAUT Model (Unified Theory Of Acceptance And Use Of Technology)

Tristiyanto, Y Fiska and Ardiansyah

[+ Open abstract](#) [View article](#) [PDF](#)

OPEN ACCESS

012060

IT Governance Audit at Lampung University Using COBIT 5 Framework Focus on EDM Domain

Tristiyanto and C Octaria

[+ Open abstract](#) [View article](#) [PDF](#)

OPEN ACCESS

012061

k-Nearest Neighbor (k-NN) Classification for Recognition of the Batik Lampung Motifs

R Andrian, M A Naufal, B Hermanto, A Junaidi and F R Lumbanraja

[+ Open abstract](#) [View article](#) [PDF](#)

OPEN ACCESS

012062

The Implementation of Backpropagation Artificial Neural Network for Recognition of Batik Lampung Motifs

R Andrian, B Hermanto and R Kamil

This site uses cookies. By continuing to use this site you agree to our use of cookies. To find out more, see our [Privacy and Cookies policy](#)



[+ Open abstract](#)[View article](#)[PDF](#)

OPEN ACCESS

012063

A New Approach of Steganography Using Center Sequential Technique

D Darwis, A Junaidi and Wamiliana

[+ Open abstract](#)[View article](#)[PDF](#)

JOURNAL LINKS

[Journal home](#)

[Journal Scope](#)

[Information for organizers](#)

[Information for authors](#)

[Contact us](#)

[Reprint services from Curran Associates](#)

Peer review statement

All papers published in this volume of *Journal of Physics: Conference Series* have been peer reviewed through processes administered by the proceedings Editors. Reviews were conducted by expert referees to the professional and scientific standards expected of a proceedings journal published by IOP Publishing.



PAPER • OPEN ACCESS

Initial Sticking Coefficient Attenuation of Gases in Carbon Monoxide Sensing on Pt₈₀Au₁₄Ti₆

To cite this article: R Marjunus 2019 *J. Phys.: Conf. Ser.* **1338** 012021

View the [article online](#) for updates and enhancements.



IOP | ebooksTM

Bringing you innovative digital publishing with leading voices to create your essential collection of books in STEM research.

Start exploring the collection - download the first chapter of every title for free.

Initial Sticking Coefficient Attenuation of Gases in Carbon Monoxide Sensing on Pt₈₀Au₁₄Ti₆

R Marjunus

University of Lampung, Jl. Prof. Dr. Soemantri Brodjonegoro No.1, Bandar Lampung 35145, Indonesia

roniyus.1977@fmipa.unila.ac.id

Abstract. It has been proved that Pt₈₀Au₁₄Ti₆ can give proper signals as a CO sensitive layer in air at room temperature. Unfortunately, there is no signal anymore from this sample, if it is kept in air more than 24 hours. To overcome this problem, we carried out dry etching technic. The atmosphere testing also has been done in technic etcher chamber by keeping the samples separately in Ar, N₂, CO, and O₂ with pressure 1 atm for 24 hours without taking out the samples after etching process from the chamber. These experiments found that oxygen causes this loss signal problem. Oxygen can diffuse up to 170 Angstrom under the Pt surface to be subsurface oxygen. This diffusion changes the surface structure of Pt(100)(1x1) to hex-Pt(100) which impacts the attenuating of the initial sticking coefficient of gases. Simulations which have been conducted in this research produced the attenuating factor, i.e., $1 - 0.00585 \exp(5.76664 O_{\text{sub}})$, where O_{sub} is the concentration of subsurface oxygen.

1. Introduction

Carbon monoxide (CO) is a gas species which is present in the earth atmosphere with a natural concentration of less than 0.001 % [1]. CO is also produced by human activities such as from vehicles, fires, explosions and cigarette smoking. Especially in a fire accident, CO is always created as a first product due to incomplete combustion of hydrocarbon [1]. Above a concentration of 30 ppm, CO is toxic to human health [2]. On the other hand, CO is colorless and odorless. Therefore, a sensor is needed to detect the existence of CO, to provide a warning on a dangerous level of CO to the human being, CO emission control for an internal combustion engine, etc.

A good sensor is a sensor that has four "high" and three "low" criteria, i.e., high sensitivity, high selectivity, high stability, high signal/noise ratio, low power consumption, low weight and low price [3]. These criteria are being tried to be achieved in gas sensor's world using some categories of gas sensors. Among the many existing categories of gas sensors, one of them is solid state sensor. Two subtypes of the solid state sensor are resistance based sensors and work function change based sensors [4]. There are disadvantages of resistance based sensors [5], i.e.:

1. It cannot use metal as the sensitive material because metal has low resistivity.
2. It cannot detect neither chemisorbed nor weakly bound physisorbed species at ambient up to slightly elevated temperatures.
3. Heating is required. If there are some sensitive layers used at room temperature, normally it will be compensated with the high of the gas concentration. It means criteria as a good sensor, i.e., high sensitivity, is not satisfied. In the case for CO sensor, some reports which claim their sensitive



material can be used at room temperature but only for high CO concentration such as at 100 ppm [6], 500 ppm [7], 1000 ppm [8][9], and 20000 ppm [10].

4. Elevated temperatures imply high power consumption.

Instead of facing the disadvantages of resistance based sensor, the second subtype of solid state sensor can be an alternative. It is field effect gas sensor or work function change based sensor [4], which needs a Floating Gate Field Effect Transistor (FGFET) as the transducer [3]. Some advantages of work function change based sensor [5] are:

1. It can use a wide variety of sensitive materials.
2. It can detect both chemisorbed and weakly bound physisorbed species at ambient up to slightly elevated temperatures.
3. Heating is not obligatory.
4. Low power consumption.
5. Freedom in choice of sensing material [11]

Many materials can be used as a candidate for a CO sensitive layer, one of them is platinum (Pt). Since 1922, Pt-CO and Pt-O interactions were known by Langmuir [12]. Pt as a sensing material was used as a detection layer in work function change based sensor, e.g., for ozone [13] or hydrogen [14]. It was also applied as a catalyst on Ga₂O₃ semiconductor work function change based sensors to decrease the operation temperature as a CO sensor to near room temperature [15], while metal oxides such as Ga₂O₃ and SnO₂ can only be used at high operation temperatures [16]. Even though Pt can decrease the operation temperature of metal oxide CO sensors but pure Pt is already known not good as CO sensitive layer in work function change based sensor, as reported by Leu et al. [17]. They obtained the average work function change 60 mV for 1000 ppm, 1700 ppm, and 2500 ppm CO in the air at room temperature. Although it was achieved at room temperature, it could not be applied for allowed maximum CO concentration in a workplace, i.e., 30 - 35 ppm. It was also tried to mix Pt with other metal such Cu which had been performed by Kiss et al., [18]. Kiss et al. reported Pt (<1 nm) which was sputtered on Cu plate (1 cm²) then annealed at 200°C for 1 hour in air could give work function change 6 mV (with good back response) for 2000 ppm CO at room temperature. The Pt/Cu layer was also able exhibiting work function change until 55 mV after the layer was heat-treated at 200°C for 2 hours in air, but the signals had a very small back response (2 mV). Then, other metal which has a chance also to be mixed with Pt is gold (Au). Investigation of CO interaction with Au was known since 1925 by Bone and Andrew [19]. Researches about the interaction of Pt-CO and Au-CO also have been done by many researchers, e.g., by Ertl et al. [20]. Not only interaction of pure Pt or pure Au with CO which was studied, but the interaction of PtAu alloy with CO was also investigated such by Bouwman and Sachtler by using photoelectric work function determination in 1970 [21]. Bouwman and Sachtler reported no significant work function change of Au, while Pt and other alloys such as Pt₈₄Au₁₆ showed a work function change of about 0.04 eV in 10⁻⁵ - 10⁻⁴ Torr CO in a vacuum chamber at ambient temperature after one day. Though report of Bouwman and Sachtler was promising, it is needed improvement in the normal air because their experiment had been done in vacuum condition. Besides regarded the response of PtAu alloy to CO, Simon et al. also reported that Pt₉₀Au₁₀ can detect CO in the hydrogen atmosphere as a work function change based sensor [22]. As the report of Bouwman and Sachtler, and the information from Simon et al. should also be tested in normal air at room temperature because the PtAu alloy in their report was used in the hydrogen atmosphere.

Marjunus (2014) reported that Pt₈₀Au₁₄Ti₆ samples with 5 nm Ti as adhesive layer is also able to give good signals to 30, 60, and 120 ppm of CO in air with Relative Humidity (*RH*) = 42% at room temperature (25°C) as presented in figure 1 [23].




Figure 1. The CPD signals of $\text{Pt}_{80}\text{Au}_{14}\text{Ti}_6$ samples with 5 nm Ti as adhesive layer to 30, 60, and 120 ppm of CO in air with $RH = 42\%$ at room temperature (25°C) [23].

Although $\text{Pt}_{80}\text{Au}_{14}\text{Ti}_6$ can give good signals as a CO sensitive layer, unfortunately there is no signal anymore from these PtAuTi samples if they are kept in air for long time, e.g. 7 months (figure 2) [23].




Figure 2. Signals of $\text{Pt}_{80}\text{Au}_{14}\text{Ti}_6$ samples with 5 nm Ti as adhesive layer to 30 ppm of CO in air with $RH = 42\%$ at room temperature (30°C) after 7 months produced [23].

To find the way how to refresh the samples, etching the samples by Technic Planar Etcher II AMPEL Nanofabrication Facility had been tried. The etching rate is about 0.5 nm/minute. After the samples were etched in argon plasma with 300 W, base pressure 5×10^{-2} mbar, and working pressure 2.6×10^{-1} mbar, for 20 minutes, samples can give their responses as before. But, when the samples are kept in air for 24 hours in Technic Planar Etcher II chamber, there is no response anymore to CO pulses, it has been proved for three times on three $\text{Pt}_{80}\text{Au}_{14}\text{Ti}_6$ samples. To find out the root of this problem, the atmosphere testing with Ar, N_2 , CO and O_2 have been done. The atmosphere testing was done in technic etcher chamber by keeping the samples with a specific gas without taking out the samples after etching process from the chamber then keeping the gas flow for 24 hours (it means the pressure chamber was always 1 atm). The results from this test show that the samples still can give their responses at room temperature (30°C) after they were etched in argon plasma with 300 W, base pressure 5×10^{-2} mbar, and working pressure 2.6×10^{-1} mbar, for 20 minutes then kept them either in Ar, N_2 or CO atmosphere with pressure

1 atm for 24 hours but there is no response anymore when they are kept in O₂. It proves that oxygen causes this problem. It has been proved for three Pt₈₀Au₁₄Ti₆ samples [23].

Oxygen is suspected playing behind the lost signal phenomenon. It is supported by some scientific reports, started by Schmiedl et al. who reported that oxygen is detected at a level significantly above the noise, up to 170 Angstrom under the Pt surface [24]. It occurs because oxygen can diffuse from the surface of Pt as chemisorbed oxygen to under the Pt surface as subsurface oxygen [25], with its diffusion constant $D = 10^{-19}$ cm²/s. The diffusion process from chemisorbed oxygen to be subsurface oxygen changes the Pt(100) structure from (1x1)-phase to hex-phase as illustrated in figure 3(a) and (b) [26].




Figure 3(a). Changing of surface structure from Pt(100) (1x1) to hex-Pt (100). **(b).** Process of chemisorbed oxygen to be subsurface oxygen [26].

The concentration of subsurface oxygen will attenuate the value of initial sticking coefficient. In order to calculate the attenuation of the initial sticking coefficient, a reaction mechanism model is built based on its state of the art. Many articles had reported regarding the interaction between CO and Pt. It is started from the Ph.D. Thesis of Callaghan [27]. Callaghan reported that many reactions were already reported regarding the kinetics and catalysis of the Water-Gas-Shift Reaction (WGS). The WGS reaction as given in Equation 1.



This reaction provides a method for extracting the energy from the toxic CO by converting it into usable H₂ along with CO₂ which can be tolerated by the fuel cell. Although Water-Gas-Shift Reaction only occurs at high-temperature range (350°C – 600°C) or low-temperature range (150°C – 300°C) not at room temperature, the chemical reactions which are used in Callaghan’s thesis are important to be used in this research, to complete all of the reaction possibilities. Perhaps, some reactions are not necessary, but simulation will decide it whether some reactions are essential or not. According to Callaghan, there were already 60 reactions which were reported by the scientists. From all reactions, only 18 reactions which were adopted by Callaghan for WGS reaction, because of some reasons [27]. The reactions are as presented in table 1.

This research uses also Reaction No. 45/Equation 2, Reaction No. 45/Equation 3 and other reaction which is also important i.e. Equation 4,



Table 1. Water-gas shift reactions mechanisms, filtered by Callaghan [27]

No.	Reaction
1.	$\text{CO}^{(g)} + \text{S} \rightleftharpoons \text{CO}^{(s)}$
2.	$\text{H}_2\text{O}^{(g)} + \text{S} \rightleftharpoons \text{H}_2\text{O}^{(s)}$
3.	$\text{H}_2\text{O}^{(s)} + \text{S} \rightleftharpoons \text{OH}^{(s)} + \text{H}^{(s)}$
4.	$\text{CO}^{(s)} + \text{O}^{(s)} \rightleftharpoons \text{CO}_2^{(s)} + \text{S}$
5.	$\text{CO}^{(s)} + \text{OH}^{(s)} \rightleftharpoons \text{HCOO}^{(s)} + \text{S}$
6.	$\text{OH}^{(s)} + \text{S} \rightleftharpoons \text{O}^{(s)} + \text{H}^{(s)}$
7.	$\text{CO}^{(s)} + \text{OH}^{(s)} \rightleftharpoons \text{CO}_2^{(s)} + \text{H}^{(s)}$
8.	$\text{HCOO}^{(s)} + \text{S} \rightleftharpoons \text{CO}_2^{(s)} + \text{H}^{(s)}$
9.	$\text{HCOO}^{(s)} + \text{O}^{(s)} \rightleftharpoons \text{CO}_2^{(s)} + \text{OH}^{(s)}$
10.	$\text{H}_2\text{O}^{(s)} + \text{O}^{(s)} \rightleftharpoons 2\text{OH}^{(s)}$
11.	$\text{H}_2\text{O}^{(s)} + \text{H}^{(s)} \rightleftharpoons \text{OH}^{(s)} + \text{H}_2^{(s)}$
12.	$\text{OH}^{(s)} + \text{H}^{(s)} \rightleftharpoons \text{O}^{(s)} + \text{H}_2^{(s)}$
13.	$\text{HCOO}^{(s)} + \text{OH}^{(s)} \rightleftharpoons \text{CO}_2^{(s)} + \text{H}_2\text{O}^{(s)}$
14.	$\text{HCOO}^{(s)} + \text{H}^{(s)} \rightleftharpoons \text{CO}_2^{(s)} + \text{H}_2^{(s)}$
15.	$\text{CO}_2^{(s)} \rightleftharpoons \text{CO}_2^{(g)} + \text{S}$
16.	$\text{H}^{(s)} + \text{H}^{(s)} \rightleftharpoons \text{H}_2^{(s)} + \text{S}$
17.	$\text{H}_2^{(s)} \rightleftharpoons \text{H}_2^{(g)} + \text{S}$
18.	$2\text{H}^{(s)} \rightleftharpoons \text{H}_2^{(g)} + 2\text{S}$

Then, in order to calculate the coverage change rate of a gas on a surface in adsorption process (r_a in atoms/s or molecules/s), it is started from the rate of adsorption, as given in Equation 5, as follows [28],

$$r_a = \frac{dN_{ads}}{dt} \quad (5)$$

where N_{ads} is the amount of adsorbed atoms or molecules on the surface which can be defined as in Equation 6,

$$N_{ads} = \sigma\theta \quad (6)$$

where σ is the surface atom density of the layer (atoms/m²) and θ is the coverage of the gas on the sample surface (in mono layer or ML). On the other hand, r_a depends on the incident molecular flux (F , in molecules.m⁻²s⁻¹) which is called Hertz-Knudsen Law [29], as given by Equation 7,

$$F = \frac{P}{\sqrt{2\pi mkT}} \quad (7)$$

and the sticking probability (S , dimensionless) which is exhibited in Equation 8,

$$S = S_0(1-\theta)^z \exp\left(-\frac{E_a}{kT}\right) \quad (8)$$

where P is partial pressure of the gas (in Pa), m is mass of the gas molecule (in kg), k is Boltzmann constant = 1.38×10^{-23} JK⁻¹, T is temperature (in K), S_0 is initial sticking coefficient or sticking coefficient when the coverage is still zero (dimensionless), and z is factor 1 for undissociated gas and 2 for

dissociated gas. If Equation 5 – 8 are combined, it is obtained the coverage change rate of a gas on a surface in adsorption process as shown in Equation 9,

$$\frac{d\theta}{dt} = \frac{S_0(1-\theta)^2}{\sqrt{2\pi mkT}} \exp\left(-\frac{E_a}{kT}\right). \quad (9)$$

When an adsorbed atom or molecule gas A reacts with an adsorbed atom or molecule of gas B on the surface to be molecule AB, based on the Langmuir-Hinshelwood mechanism, the coverage change rate of AB can be calculated as given in Equation 10, [30][31],

$$\frac{d\theta_{AB}}{dt} = v_r \exp\left(-\frac{E_r}{kT}\right) \theta_A \theta_B \quad (10)$$

where v_r is the pre-exponential factor/Arrhenius coefficient which determines the frequency of reaction A and B (in reaction/s), E_r is activation energy of reaction between atom/molecule gas A and B (in eV), θ_A and θ_B are the coverage of gas A dan gas B respectively (dimensionless).

Then, if an adsorbed molecule gas (e.g. AB) dissociates into A and B, the coverage change rate of A can be calculated as presented in Equation 11 [31],

$$\frac{d\theta_A}{dt} = v_{diss} \exp\left(-\frac{E_d}{kT}\right) \theta \quad (11)$$

where v_{diss} is the pre-exponential factor/Arrhenius coefficient which determines the frequency of AB dissociation (in dissociation/s), E_{diss} is activation energy of gas AB dissociation (in eV) and θ_{AB} is the coverage of molecule AB (dimensionless).

Afterward, when an adsorbed atom or molecule will be desorbed, the coverage change rate the atom or molecule on the sample surface can be calculated as revealed in Equation 12 [31],

$$\frac{d\theta}{dt} = v_d \exp\left(-\frac{E_d}{kT}\right) \theta \quad (12)$$

where v_d is the pre-exponential factor/Arrhenius coefficient which determines the frequency of desorption (desorption/s).

2. Data/Materials and Methods

The concentration of subsurface oxygen can be calculated using diffusion equation which is given in Equation 13 [32],

$$\frac{\partial \theta}{\partial t} = D\nabla^2 C \quad (13)$$

Equation 13 will be solved with numerical method for one dimension as given in Equation 14,

$$C_{i,j+1} = C_{i,j} + D\Delta t \left(\frac{C_{i+1} - 2C_{ij} + C_{i-1,j}}{\Delta y^2} \right) \quad (14)$$

Then, the simulation calculates the amount of O_{chem} and O_{sub} in Mono Layer (ML) with/without considering the surface reaction (adsorption, reaction, and desorption). Considering/not considering the surface reaction are aimed to know whether there is a significant role or not of the surface reaction, or which is responsible for the amount of O_{chem} and O_{sub} .

Afterward, experiments for 24 hours on $Pt_{80}Au_{14}Ti_6$ with 5 nm Ti as adhesive layer to 30 ppm which are exposed to CO in air with $RH = 42\%$ at room temperature (30°C) after etched in argon plasma with 300 W with base pressure 5×10^{-2} mbar, and working pressure 2.6×10^{-1} mbar would be done. The Signal

Attenuation (SA) would be formulated as percentage of the signal to the initial signal. Afterward, the data of SA from these experiments were plotted together with the result from experiment.

3. Results and Discussion

The model in this research uses the Callaghan's reaction (Reaction No. 1 - 18 in table 1) and Equation 1 – 3. Then, based on (a) all reactions, (b) the coverage change rate of a gas on a surface in adsorption process (Equation 9), (c) the coverage change rate of reaction between element A and B (Equation 10), (d) the coverage change rate of dissociation AB (Equation 11) and (e) the coverage change rate the desorbed atom or molecule on the sample surface (Equation 12), it can be developed the Surface Coverage Differential Equations for θ_{CO} , θ_O , θ_{CO_2} , θ_{H_2O} , θ_{OH} , θ_H , θ_{HCOO} , θ_{H_2} and θ_C as presented in Equation 15 – 23,

$$\frac{d\theta_{CO}}{dt} = r_{f1}F_{CO} - r_{f4}\theta_{CO}\theta_O + r_{r4}\theta_{CO_2} - r_{f5}\theta_{CO}\theta_{OH} + r_{r5}\theta_{HCOO} - r_{f7}\theta_{CO}\theta_H + r_{r7}\theta_{CO_2}\theta_H - r_{f61}\theta_{CO} + r_{r61}\theta_C\theta_O - r_{r1}\theta_{CO} \tag{15}$$

$$\frac{d\theta_O}{dt} = 2r_{f45}F_{O_2} - r_{f4}\theta_{CO}\theta_O + r_{r4}\theta_{CO_2} + r_{f6}\theta_{OH} - r_{r6}\theta_O\theta_H - r_{f9}\theta_{HCOO}\theta_O + r_{r9}\theta_{CO_2}\theta_{OH} - r_{f10}\theta_{H_2O}\theta_O + r_{r10}\theta_{OH}^2 + r_{f12}\theta_{OH}\theta_H - r_{r12}\theta_O\theta_{H_2} + r_{f61}\theta_{CO} - r_{r61}\theta_C\theta_O - 2r_{f45}\theta_O^2 \tag{16}$$

$$\frac{d\theta_{CO_2}}{dt} = r_{r15}F_{CO_2} + r_{f4}\theta_{CO}\theta_O - r_{r4}\theta_{CO_2} + r_{f7}\theta_{CO}\theta_H - r_{r7}\theta_{CO_2}\theta_H + r_{f8}\theta_{HCOO} - r_{r8}\theta_{CO_2}\theta_H + r_{f9}\theta_{HCOO}\theta_O - r_{r9}\theta_{CO_2}\theta_{OH} + r_{f13}\theta_{HCOO}\theta_{OH} - r_{r13}\theta_{CO_2}\theta_{H_2O} + r_{f14}\theta_{HCOO}\theta_H - r_{r14}\theta_{CO_2}\theta_{H_2} - r_{f9}\theta_{HCOO}\theta_O + r_{r9}\theta_{CO_2}\theta_{OH} - r_{f15}\theta_{CO_2} \tag{17}$$

$$\frac{d\theta_{H_2O}}{dt} = r_{f2}F_{H_2O} - r_{f3}\theta_{H_2O} + r_{r3}\theta_{OH}\theta_H - r_{f10}\theta_{H_2O}\theta_O + r_{r10}\theta_{OH}^2 - r_{f11}\theta_{H_2O}\theta_H + r_{r11}\theta_{OH}\theta_{H_2} + r_{f13}\theta_{HCOO}\theta_{OH} - r_{r13}\theta_{CO_2}\theta_{H_2O} - r_{r2}\theta_{H_2O} \tag{18}$$

$$\frac{d\theta_{OH}}{dt} = r_{f46}F_{OH} + r_{f3}\theta_{H_2O} - r_{r3}\theta_{OH}\theta_H - r_{f5}\theta_{CO}\theta_{OH} + r_{r5}\theta_{HCOO} - r_{f6}\theta_{OH} + r_{r6}\theta_O\theta_H - r_{f7}\theta_{CO}\theta_H + r_{r7}\theta_{CO_2}\theta_H + r_{f9}\theta_{HCOO}\theta_O - r_{r9}\theta_{CO_2}\theta_{OH} + 2r_{f10}\theta_{H_2O}\theta_O - 2r_{r10}\theta_{OH}^2 + r_{f11}\theta_{H_2O}\theta_H - r_{r11}\theta_{OH}\theta_{H_2} - r_{f12}\theta_{OH}\theta_H + r_{r12}\theta_O\theta_{H_2} - r_{f13}\theta_{HCOO}\theta_{OH} + r_{r13}\theta_{CO_2}\theta_{H_2O} + r_{f8}\theta_{HCOO} - r_{r8}\theta_{CO_2}\theta_H - r_{f46}\theta_{OH} \tag{19}$$

$$\frac{d\theta_H}{dt} = 2r_{r18}F_H + r_{f3}\theta_{H_2O} - r_{r3}\theta_{OH}\theta_H + r_{f6}\theta_{OH} - r_{r6}\theta_O\theta_H + r_{f7}\theta_{CO}\theta_H - r_{r7}\theta_{CO_2}\theta_H + r_{f8}\theta_{HCOO} - r_{r8}\theta_{CO_2}\theta_H - r_{f11}\theta_{H_2O}\theta_H + r_{r11}\theta_{OH}\theta_{H_2} - r_{f12}\theta_{OH}\theta_H + r_{r12}\theta_O\theta_{H_2} - r_{f14}\theta_{HCOO}\theta_H + r_{r14}\theta_{CO_2}\theta_{H_2} - r_{f16}\theta_H^2 + r_{r16}\theta_{H_2} - 2r_{r18}\theta_H^2 \tag{20}$$

$$\begin{aligned} \frac{d\Theta_{\text{HCOO}}}{dt} = & r_{15}\Theta_{\text{CO}}\Theta_{\text{OH}} - r_{15}\Theta_{\text{HCOO}} - r_{18}\Theta_{\text{HCOO}} + r_{18}\Theta_{\text{CO}_2}\Theta_{\text{H}} - r_{19}\Theta_{\text{HCOO}}\Theta_{\text{O}} + r_{19}\Theta_{\text{CO}_2}\Theta_{\text{OH}} - r_{113}\Theta_{\text{HCOO}}\Theta_{\text{OH}} \\ & + r_{113}\Theta_{\text{CO}_2}\Theta_{\text{H}_2\text{O}} - r_{114}\Theta_{\text{HCOO}}\Theta_{\text{H}} + r_{114}\Theta_{\text{CO}_2}\Theta_{\text{H}_2} \end{aligned} \quad (21)$$

$$\begin{aligned} \frac{d\Theta_{\text{H}_2}}{dt} = & r_{117}F_{\text{H}_2} + r_{111}\Theta_{\text{H}_2\text{O}}\Theta_{\text{H}} - r_{111}\Theta_{\text{OH}}\Theta_{\text{H}_2} + r_{112}\Theta_{\text{OH}}\Theta_{\text{H}} - r_{112}\Theta_{\text{O}}\Theta_{\text{H}_2} + r_{114}\Theta_{\text{HCOO}}\Theta_{\text{H}} - r_{114}\Theta_{\text{CO}_2}\Theta_{\text{H}_2} \\ & + r_{116}\Theta_{\text{H}}^2 - r_{116}\Theta_{\text{H}_2} - r_{117}\Theta_{\text{H}_2} \end{aligned} \quad (22)$$

$$\frac{d\Theta_{\text{C}}}{dt} = r_{161}\Theta_{\text{CO}} - r_{161}\Theta_{\text{C}}\Theta_{\text{O}} \quad (23)$$

where

$$F_X = (1 - \Theta_X)^2 \frac{P}{\sigma \sqrt{2\pi mkT^c}} \quad (24)$$

where X in F_X the symbol of the gas, n is 1 or 2 for undissociated or dissociated gas respectively, P is partial pressure of the gas (Pa) and m is the atom mass of the gas (kg), k is Boltzmann constant, T is temperature (in K) and σ is surface density of atom on the sensitive layer surface (surface density of Pt, Au and Ti are 1.3×10^{19} atoms/m², 1.2×10^{19} atoms/m² and 2.3×10^{19} atoms/m² respectively) [23]. Afterward, in Equation 15 – 23, it is found also reaction rate ($r_{f \text{ or } r, N}$) where

$$r_{f \text{ or } r, N} = v_{f \text{ or } r, N} \exp\left(-\frac{E_{f \text{ or } r, N}}{kT}\right) \quad (25)$$

where subscript f, r and N in $r_{f \text{ or } r, N}$ mean forward reaction, reverse reaction and number of reaction respectively, $v_{f \text{ or } r, N}$ is Arrhenius Coefficient (s⁻¹) and $E_{f \text{ or } r, N}$ is activation energy (eV) [31]. There is an exception of Equation 25 for forward Reaction No. 1, 2, 15, 17, 18, 45 and 46 as given in Equation 26 [31],

$$r_{f, N} = S_{0X} \exp\left(-\frac{E_{f, N}}{kT}\right) \quad (26)$$

where S_{0X} in $r_{f, N}$ is the initial sticking coefficient of gas X. Afterward, since the sensitive layer is a mixture of more than one material, the total of gas atom/molecule coverage on the surface is proposed as given in Equation 27,

$$\frac{d\Theta_j}{dt} = \sum_{i=\text{Pt}}^{\text{Ti}} \%i \frac{d\Theta_{ji}}{dt} \quad (27)$$

where j is index for the element symbol of the gas, %i is the percentage of Pt, Au or Ti on the sample and $\frac{d\Theta_{ji}}{dt}$ is the coverage rate of every gas which is already given in Equation 15 – 23. The coverage of every gas will be found in the simulation from Equation 27. Then, the work function of the sensitive layer during exposed with the gases is determined as function of the gas coverages in Equation 28,

$$\Phi(\Theta) = \sum_{i=\text{Pt}}^{\text{Ti}} \sum_{j=\text{CO}}^{\text{C}} \%i \Phi_{ji}(\Theta_i) \quad (28)$$

where $\Phi_{ji}(\theta_{ji})$ is the work function of gas j on material i as already given in Marjunus (2018) [23]. Finally, the CPD is calculated by substituting $\Phi(\theta)$ which is obtained from Equation 28 to Equation 29 [23],

$$CPD \approx \frac{\Phi_s}{|e|} \quad (29)$$

where $|e|$ is the elementary charge.

Then, experiments for 24 hours on $Pt_{80}Au_{14}Ti_6$ with 5 nm Ti as adhesive layer to 30 ppm which are exposed to CO in air with $RH = 42\%$ at room temperature ($30^\circ C$) after etched in argon plasma with 300 W with base pressure 5×10^{-2} mbar, and working pressure 2.6×10^{-1} mbar, has been done as presented in figure 4. According to the figure 4, the average signals show that the signal of samples attenuates by the time.




Figure 4. Average of experiment CPD signals from three samples of $Pt_{80}Au_{14}Ti_6$ with 5 nm Ti as adhesive layer to 30 ppm of CO in air with $RH = 42\%$ at room temperature ($30^\circ C$) after etched in argon plasma with 300 W, base pressure 5×10^{-2} mbar, and working pressure 2.6×10^{-1} mbar, then measured for 24 hours.

To find the relationship between the concentration of subsurface oxygen and the sticking coefficient of O on Pt, the simulation uses:

1. the original values of all parameters for Pt in Reaction No. 1 – 18, 45, 46 and 61, which have been mentioned in Marjunus (2018) [23],
2. room temperature ($30^\circ C$),
3. the relative humidity of the chamber (42%),
4. standard pressure (1 atm) of synthetic air (consists of 80% of N_2 and 20% of O_2), and
5. measurement time for 24 hours.

The simulation calculates the amount of O_{chem} and O_{sub} in Mono Layer (ML) with/without considering the surface reaction (adsorption, reaction, and desorption). Considering/not considering the surface reaction are aimed to know whether there is a significant role or not of the surface reaction, or which is responsible for the amount of O_{chem} and O_{sub} . The first result is as given in figure 5.




Figure 5. Chemisorbed (O_{chem}) and subsurface oxygen (O_{sub}) on Pt surface with $RH = 42\%$ at room temperature (30°C) in synthetic air (consists of 80% of N_2 and 20% of O_2), measured for 24 hours, with/without considering the surface reaction.

According to figure 5, by considering the surface reaction, it is shown that at the beginning, $\text{O}_2^{(\text{g})}$ will be adsorbed slowly but O_{chem} will reach about 1 ML after 7 hours. It effects to the growing of O_{sub} . On the other hand, without considering the surface reaction, of course, the amount of O_{chem} is perfectly 1 ML started from the beginning. It is looked like that there is no different behavior of O_{sub} with/without considering the surface reaction because the amount of O_{chem} for these two conditions do not also give a big difference. It sounds that the surface reaction does not play a role in the amount of O_{sub} , although its role is intended.

Since figure 5 does not give a clear hint whether the surface reaction plays its role or not for the occupation of O_{sub} , the second simulation has been done as presented in figure 6.




Figure 6. Chemisorbed and subsurface oxygen on Pt surface with $RH = 42\%$ at room temperature (30°C) in synthetic air (consists of 80% of N_2 and 20% of O_2), exposed by 1 atm of synthetic air for the first 12 hours and in vacuum condition for the last 12 hours, by considering the surface reaction.

In this simulation, Pt surface is exposed by 1 atm of synthetic air for the first 12 hours and conditioned in vacuum for the last 12 hours. This condition was hoped that it can show the role of the surface reaction. Unfortunately, according to the Figure 6, it was hoped, after $\text{O}_2^{(\text{g})}$ is switched off, the amount of O_{chem} will decrease automatically which will be followed by decreasing of O_{sub} . This intention finally

cannot be proved. It can be understood, because the huge amount of $O_2^{(g)}$ molecules in the air above the Pt surface and O_{chem} on the surface from the first 12 hours is still enough for covering the Pt surface and diffusing to be O_{sub} . Afterward, since there is still no proof that the surface reaction influences the amount of O_{sub} , the third simulation which is similar to the second simulation has been done. In this simulation, the desorption energy of $2O^{(s)}$ on Pt is used only 10% of its original value [23]. The decreasing of this energy is aimed, that the adsorbed/chemisorbed O on Pt surface is easy to be desorbed. It is hoped, this treatment can show that the surface reaction plays the role of the O_{sub} . Finally, this idea gives the proof that surface reaction especially desorption, controls the amount of O_{sub} as presented in figure 7.




Figure 7. Chemisorbed and subsurface oxygen on Pt surface with $RH = 42\%$ at room temperature ($30^\circ C$) in synthetic air (consists of 80% of N_2 and 20% of O_2 , exposed by 1 atm of synthetic air for the first 12 hours and in vacuum condition for the last 12 hours, by considering the surface reaction but using only 10% of desorption energy of $2O^{(s)}$ on Pt.

Afterward, the Signal Attenuation (SA) can be formulated as percentage of the signal to the initial signal as revealed in figure 8. Based on figure 8, the trend line of SA gives the dependency of SA to the time (t in hour) with error ($\chi^2 = 0.008$) as written in Equation 30,

$$SA = 0.98343 \exp(-0.08981t). \tag{30}$$




Figure 8. Signal Attenuation (SA), its trendline and the increasing of subsurface oxygen (O_{sub}) in 24 hours measurement.

Then, the data of SA from these experiments are plotted together with the result from figure 5 which considers the surface reaction, as presented in figure 9.




Figure 9. Signal Attenuation (SA) versus the increasing of subsurface oxygen (O_{sub}).

According to the figure 9, the relationship between SA and O_{sub} is obtained by fitting their data with error ($\chi^2 = 9 \times 10^{-5}$) as given in Equation 31,

$$SA = 1 - 0.00585 \exp(5.76664 O_{sub}). \tag{31}$$

where O_{sub} is the amount of O_{sub} . This relationship (Equation 31) is also called as the adjustment factor for initial sticking coefficient.

Finally, figure 10 presents the comparison of the simulated CPD signal with and without SA for loss signal simulation phenomenon on $Pt_{80}Au_{14}Ti_6$ to 30, 60 and 90 ppm CO in air with $RH = 42\%$ at room temperature ($30^\circ C$).




Figure 10. Simulation of loss signal phenomenon with and without SA on $Pt_{80}Au_{14}Ti_6$

to 30, 60 and 90 ppm CO in air with $RH = 42\%$ at room temperature ($30^\circ C$). From this figure, it can be seen that the signals are not completely vanished after samples are exposed in the air (as experimented results) when simulation does not use SA. The simulated CPD signals will be smaller, even almost zero,

when SA is employed in the simulation. It proves that SA is needed for every sticking coefficient parameter.

4. Conclusions

There is no CPD signals from PtAuTi samples after exposed 24 hours in the air because of oxygen (O) occupation. O can diffuse into Pt (also applied for Au and Ti in simulations) with diffusion constant 10^{-19} cm²/s forming subsurface oxygen. The process from chemisorbed oxygen to be subsurface oxygen attenuates the sticking coefficient of every gas (O₂, CO, CO₂, H₂O, OH, and H₂) with simulated factor $SA = 1 - 0.00585 \exp(5.76664O_{\text{sub}})$.

Acknowledgment

The author would like to thank to Ministry of Research and Higher Education, Republic of Indonesia and also to Institut für Physik, Fakultät Elektrotechnik und Informationstechnik, Universität der Bundeswehr München, Germany, for supporting this research.

References

- [1] Ernst and Zibrak J D 1998 Carbon monoxide poisoning *J. of Medicine* **339** (22) p 1603–08
- [2] Goldstein M 2008 Carbon monoxide poisoning *J. of Emergency Nursing* **34** (6) p 538–42
- [3] Senft, Iskra P, Eisele I and Hansch W 2011 Work function - based sensor: Schottky - and FET-based devices (in *Chemical Sensors: Comprehensive Sensor Technologies* ed G Korotchenkov) chap 5 p 180-228
- [4] Capone S, Forleo A, Francioso L, Rella R, Siciliano P, Spadavecchia J, Presicce S and Taurino A M 2004 Solid state gas sensors: State of the art and future activities *ChemInform* **35** (29) p 1335-48
- [5] Eisele I and Burgmair W 2000 Work function based field effect devices for gas sensing *Proc. Conference on Optoelectronic and Microelectronic Materials and Devices* p 285–91
- [6] Friedberger A, Kreisl P, Rose E, Müller G, Kühner G, Wöllenstein J and Böttner H 2003 Micromechanical fabrication of robust low-power metal oxide gas sensors *Sens. Actuators B Chem.* **93** (1-3) p 345–9
- [7] Zhou X, Xu Y, Cao Q and Niu S 1997 Metal-semiconductor ohmic contact of SnO₂-based ceramic gas sensors *Sens. Actuators B Chem.* **41** (1-3) p 163–7
- [8] Salehi A and Nikfarjam A 2004 Room temperature carbon monoxide sensor using ITO/n-GaAs Schottky contact *Sens. Actuators B Chem.* **101** (3) p 394–400
- [9] Kang K S and Lee S P 2003 CO gas sensors operating at room temperature», *J. of Material Scie.* **38** p 4319–23
- [10] Ivanovskaya M, Lutynskaya E and Bogdanov P 1998 The influence of molybdenum on the properties of SnO₂ ceramic sensors *Sens. Actuators B Chem.* **48** (1-3) p 387–91
- [11] Pohle R, Von S O, Fleischer M, Frerichs H P, Wilbertz Ch and Freund I 2010 Gate pulsed readout of floating gate FET gas sensors *Proc. Engineering* **5**(0) p 3–16
- [12] Langmuir I 1922 The mechanism of the catalytic action of platinum in the reactions $\text{CO} + \text{O}_2 \rightarrow 2\text{CO}_2$ and $2\text{H}_2 + \text{O}_2 \rightarrow 2\text{H}_2\text{O}$ *Trans. Faraday Soc.* **17** p 621–54
- [13] Zimmer M, Burgmair M, Scharnagl K, Karthigeyan A, Doll T and Eisele I 2001 Gold and platinum as ozone sensitive layer in work-function gas sensors *Sens. Actuators B Chem.* **80** (3) p 174–8
- [14] Galonska T, Senft C, Widanarto W, Senftleben O, Frerichs H P and Wilbertz Ch 2007 Cross sensitivity and stability of FET - based hydrogen sensors *SENSORS, 2007 IEEE* p 1036-39
- [15] Fleischer M, Hoefler U, Pohle R and Stegmeier R 2012 Selective detector for carbon monoxide (US Patent: US2012/0047995 A1)
- [16] Lampe U, Simon E, Pohle R, Fleischer M, Meixner H, Frerichs H P, Lehmann M and Kiss G 2005 Gas FET for the detection of reducing gases *Sens. Actuators B Chem.* 111 - 112 p 106 – 10

- [17] Leu M, Doll T, Flietner B, Lechner J and Eisele I 1994 Evaluation of gas mixtures with different sensitive layers incorporated in hybrid FET structures *Sens. Actuators B Chem.* **19** (1-3) p 678–81
- [18] Kiss G, Várhegyi E B, Mizsei J, Krafcsik O H, Kovács K, Négyesi G, Ostrick B, Meixner H and Réti F Examination 2000 of the CO/Pt/ Cu layer structure with Kelvin probe and XPS analysis *Sens. Actuators B Chem.* **68** (1-3) p 240–3
- [19] Bone W A and Andrew G W 1975 Studies upon catalytic combustion. Part I: The union of carbon monoxide and oxygen in contact with a gold surface *Proc. of the Royal Society of London Series A* **109** (751) p 459–76
- [20] Ertl G, Neumann M and Streit K M 1977 Chemisorption of CO on the Pt(111) surface *Surface Science* **64** (2) p 393 – 410
- [21] Bouwman R and Sachtler W M H 1970 Photoelectric determination of the work function of gold-platinum alloys *J. of Catalysis* **19** (2) p 127–39
- [22] Simon S, Marjunus R, Stimpel T, Lindner, Wilbertz Ch, Schmidt I, Wartmann J and Hansch W 2012 Pt/Au based sensor with a PMMA–film for detecting CO in a hydrogen atmosphere», In IMCS 2012 – The 14th Inter. Meet. on Chem. Sensors p 327–30
- [23] Roniyus M 2018 *Development of Pt-based Sensitive Layer for Carbon Monoxide Work Function Change Based Sensor in Air at Room Temperature* Ph D Thesis (München: Universität der Bundeswehr)
- [24] Schmiedl R, Demuth V, Lahnor P, Godehardt H, Bodschwinn Y, Harder C, Hammer L, Strunk H P, Schulz M and Heinz K 1996 Oxygen diffusion through thin Pt films on Si(100) *J. App. Phys* **62** 3 p 223–30
- [25] Rotermund H H, Lauterbach J and Haas G 1993 The formation of subsurface oxygen on Pt(100) *J. App. Phys.* **57** 6 p 507–11
- [26] Lauterbach J, Asakura K and Rotermund H H 1994 Subsurface oxygen on Pt(100): Kinetics of the transition from chemisorbed to subsurface state and its reaction with CO, H₂ and O₂ *J. Surf. Scie.* **313** 1-2 p 52–63
- [27] Callaghan C A 2006 *Kinetics and Catalysis of the Water-Gas-Shift Reaction: A Microkinetic and Graph Theoretic Approach* Ph D Thesis (Worcester: Worcester Polytechnic Institute)
- [28] Nix R M 2014 *An Introduction to Surface Chemistry* (London: Queen Mary, University of London)
- [29] Yan X T and Xu Y 2010 *Chemical Vapor Deposition* (London: Springer-Verlag)
- [30] Somorjai G A and Li Y 2010 *Introduction to Surface Chemistry and Catalysis 2nd Edition* (New York : Wiley & Sons)
- [31] Senft C 2009 *Austrittsarbeitsbasierte Wassertofdetektion für Fahrzeuge mit Brennstoffzellenantrieb* Ph D Thesis (München : Universität der Bundeswehr)
- [32] Massman W J 1998 A review of the molecular diffusivities of H₂O, CO₂, CH₄, CO, O₃, SO₂, NH₃, N₂O, NO, and NO₂ in air, O₂ and N₂ near STP Atmospheric Environment **32** (6) p 1111–27