Volume 14 • Number 10

PUBLISHERS

Journal of Computational and Theoretical NANOSCIENCE

For all Computational and Theoretical Aspects of Nanoscience and General Mathematical Procedures

www.aspbs.com/ctn

Editor-in-Chief: Prof. Rui-Hua Xie, China



JOURNAL OF COMPUTATIONAL AND THEORETICAL NANOSCIENCE Vol. 16 No. 7, Pages: 3054–3065, 2019

	MEDIC	AN SCIENT		ICUEDO	Order Form	Authors			
		AN SCIENT		LISHEKS	Shopping Cart	Librarians			
	Nanotechnology	Materials Science	Engineering		E-mail Alerts	Booksellers			
AMERICAN	Chemistry	Polymer Science	Computer Science		Book Proposals	Agencies			
SCIENTIFIC PUBLISHERS	Physics	Biosciences	Medicine		Special Offers	ASP Partners			
Home	Journals 🗼 Books	Encyclopedias 🚶 New and	Forthcoming Titles / Cont	act ASP Search Keyword -		<u></u>			
Aims and Scor	•								
Editorial Board		Journal of Comp	utational and Tl	neoretical Nanoso	cience				
Instructions for	Authors	ISSN: 1546-1955 (Print): EISSN: 1546-1963 (Online)							
Contact Inform	ation	Copyright © 2000-2021 American Scientific Publishers. All Rights Reserved.							
Subscription In	formation	Aims and Scope							
Copyright Trans	fer Agreement	Journal of Computational and Theoretical Nanoscience is an international peer-reviewed journal with a wide-ranging coverage, consolidates research activities in all aspects of computational and theoretical nanoscience into a single reference source. This journal offers scientists and engineers peer-reviewed research papers in all aspects of computational and theoretical nanoscience and nanotechnology in chemistry, physics, materials science, engineering and biology to publish original full papers and timely state-of-the-art							
Indexed/Abstra	cted								
Cover Library									
Contents		reviews and short communications encompassing the fundamental and applied research.							
	-	RESEARCH TOPICS COVERE	D (alphabetical listing)						
٥		Assemblers, basic physics, biological systems, biochemical systems, bionics, biophysics, CAD, carbon systems, cellular mechanisms, chaotic systems, circuits, clusters, cluster systems, complex aggregates, computer codes, crystal growth, data analysis, defined chain length molecules, devices, diffusion processes, DNA, drug design, dynamics, electronics, electronic properties, enzyme reactivity and reactions, equation of state, friction, computational genomics, gene technology, genetics, holistic views, information theory, interactions, ion channelling, kinetics, macromolecules, molecular interactions, large scale simulations, liquids, liquid crystals, luminescence, magnetic structures, manufacturing, many-particle systems, metallurgy, materials, material properties, mechanical models, metals, mathematical methods, molecule design, molecular dynamics, noble gases, nonlinear optics, numerical algorithm, numerical procedures, oligomers, optoelectronics, phase transitions, phenomenological theory, philosophical implications and positions, photonic crystals, polymers, potential development, protein folding, quantum chemistry, quantum computers, guantum dots, quantum deteronics and optics, quantum technology, replicators, RNA, semiconductors, superconductors, solid state physics, structural chemistry, structures, structures on surfaces, surfaces, technological applications, theoretical biosciences, theoretical physics, thermodynamics thought experiments, wear, and much more							
		Authors should submit manuscript or	nline to the <u>Manuscript Tracking s</u>	<u>System</u> .					
		EDITOR-IN-CHIEF Professor Dr. Rui-Hua Xie Department of Applied Physics Xi'an Jiaotong University Xi'an Jiaotong University Xi'an 710049, People's Republic of China							
		Book for Review Publications should be sent the Editor	orial Office.						
		Subscription American Scientific Publishers 26650 The Old Road, Suite 208 Valencia, California 91381-0751, US Tel. (661) 799-7200 Email: grder@aspbs.com	A						

Aims and Scope
Editorial Board
Instructions for Authors
Contact Information
Subscription Information
Copyright Transfer Agreement
Indexed/Abstracted
Cover Library
Contents



Journal of Computational and Theoretical Nanoscience

ISSN: 1546-1955 (Print): EISSN: 1546-1963 (Online) Copyright © 2000-2021 American Scientific Publishers. All Rights Reserved.

EDITOR-IN-CHIEF

Professor Dr. Rui-Hua Xie Department of Applied Physics Xi'an Jiaotong University Xi'an 710049, People's Republic of China

ASSOCIATE EDITORS

Asen Asenov (Device Modeling, Atomistic Simulations), University of Glasgow, UK. Markus J. Buehler (Atomistic and Mesoscopic Modelling, Biological Materials), Massachusetts Institute of Technology (MIT), USA Xiaoshuang Chen (Nanomaterials Modeling/Simulation), Shanghai Institute of Technical Physics, Chinese Academy of Sciences, China Dimiter S. Dimitrov (Computational Biophysics, Protein Interactions), National Cancer Institute, NIH, USA. Dimitris Drikakis (Nano-fluidics, Materials Modeling), University of Strathclyde, Glasgow, UK. Christian Hafner (Nano-optics, Materials Science), ETH Zürich, Switzerland. Tomoya Ono (Nanostructures, First-Principles Treatments), Osaka University, Osaka, Japan Hans De Raedt (Quantum Computation, Nano-particles), University of Groningen, The Netherland. Asok K. Ray (Nano-electronics, Computational Methods), University of Texas, Arlington, USA. San-Qiang Shi (Nanomaterials Modeling), The Hong Kong Polytechnic University, China. Karl Sohlberg (Physical and Materials Chemistry), Drexel University, USA. Jijun Zhao (Computational Nanoscience), Dalian University of Technology, China

EDITORIAL BOARD

Alexei A. Abrikosov, Argonne National Laboratory, USA Vladimir Basiuk, Universidad Nacional Autonoma de Mexico, Mexico Sotiris Baskoutas, University of Patras, Greece Artur Baumgaertner, Forschungszentrum Juelich, Germany Estela Blaisten-Barojas, George Mason University, USA Donald W. Brenner, North Carolina State University, USA Felix A. Buot, George Mason University, USA Roberto Car. Princeton University USA Gang Chen, Massachusetts Institute of Technology (MIT), USA Shin-Ho Chung, Australian National University, Canberra, Australia Ioana Cozmuta, NASA Ames Research Centre, USA Peter T. Cummings, Vanderbilt University, USA K. Eric Drexler, Nanorex, Inc., USA Sakir Erkoc, Middle East Technical University, Ankara, Turkey Robert A Freitas Jr., Institute for Molecular Manufacturing, Los Altos, USA Yuri Galperin, University of Oslo, Oslo, Norway Nasr M. Ghoniem, University of California at Los Angeles, USA William A. Goddard III, California Institute of Technology (Caltech), USA James Hickman, University of Central Florida, Orlando, USA Yonggang Young Huang, Univiversity of Illinois at Urbana-Champaign, USA David Hui, University of New Orleans, USA Jeong-Won Kang, Chungju National University, Chungju, Republic of Korea Nicholas Kioussis, California State University Northridge, USA Aatto Laaksonen, Stockholm University, Stockholm, Sweden Charles Lieber, Harvard University, USA Bin Liu, Tsinghua University, China Feng Liu, University of Utah, Salt Lake City, USA Yi Luo, Roval Institute of Technology, Stockholm, Sweden Constantinos Mavroidis, Rutgers University, USA Majid Monajjemi, Islamic Azad University, Tehran, Iran Dima Mozyrsky, Los Alamos National Laboratory, USA Jun Ni, University of Iowa, USA Risto Nieminen, Helsinki University of Technology, Finland Abraham Nitzan, Tel Aviv University, Israel Zhong-can Ou-Yang, Chinese Academy of Sciences, Beijing, China Wounjhang Park, University of Colorado at Boulder, USA A. John Peter, Faculty of Physics, Govt.Arts College, Madurai, India Umberto Ravaioli, University of Illinois at Urbana-Champaign, USA lan Snook, RMIT University, Australia Dragica Vasileska-Kafedziska, Arizona State University, USA Hongyun Wang, University of California, Santa Cruz, USA Jingbo Wang, University of Western Australia, Australia Lin-Wang Wang, Lawrence Berkeley National Laboratory, USA Yan Alexander Wang, University of British Columbia, Canada Toshishige Yamada, NASA Ames Research Center, USA Jie Yan, National University of Singapore, Singapore Svetlana Yanushkevich, University of Calgary, Canada Chuck Zhang, Florida A & M University, USA Liangchi Zhang, University of Sydney, Australia

Volume 16, Number 7 (July 2019) pp.263

RESEARCH ARTICLES Compressed Sensing Matrix Optimisation for Vision Applications Yongshi Zhang and Jianpei Zhang J. Comput. Theor. Nanosci. 16, 2635–2643 (2019) [Abstract] [Full Text - PDF] [Purchase Article]

Automated Classification of Tribological Faults of Alternative Systems with the Use of Unsupervised Artificial Neural Networks Marco Antonio Leandro Cabral, Efrain Pantaleón Matamoros, José Alfredo Ferreira Costa, Antonio Paulo Vieira Pinto, Andreyvis Silva de Souza, André Dantas Freirei, Carlos Eduardo Filgueira Bezerra, Eric Lucas dos Santos Cabral, Wilkson Ricardo Silva Castro, Ricardo Pires de Souza, and Eurico Augusto Rodrigues Seabra J. Comput. Theor. Nanosci. 16, 2644–2659 (2019) [Abstract] [Full Text - PDF] [Purchase Article]

Secure Cloud Data Deduplication with User Revocation and Public Auditing Dynamically Kapilesh S. Swami and P. Sai Kiran J. Comput. Theor. Nanosci. 16, 2660–2665 (2019) [Abstract] [Full Text - PDE] [Purchase Article]

Thermodynamics Properties of Nanowire Matrices (Si, Pt, Au and Ni) by Molecular Dynamics and Finite-Difference José F. S. Costa, Rômulo C. Lima, Manuel J. S. Costa, Sebastião M. S. Cordeiro, Antonio M. J. C. Neto, and Abel F. G. Ne J. Comput. Theor. Nanosci. 16, 2666–2672 (2019) [Abstract] [Full Text - PDF] [Purchase Article] e Meth

Evaluation of Computational Method from Crystallographic Structure of Galantamine for Molecular Modeling of Drug Candidates Anti-Alzheimer's Disease Priscilla Farias Ozela, Leide Caroline dos Santos Picanço, Lucilene Rocha de Souza, Robson Carvalho Barbosa, Jaderson Vieira Ferreira, Carlos Henrique Tomich de Paula da Silva, Cleydson Breno Rodrigues dos Santos, and Lorane Izabel da Silva Hage-Melim J. Comput. Theor. Nanosci. 16, 2673–2686 (2019) [Abstract] [Full Text - PDF] [Purchase Article]

A New Heteroscedasticity Consistent Covariance Matrix Estimator and Inference Based on Robust Methods Moustafa Salem, Amal A. Fattah, and EL Houssainy A. Rady J. Comput. Theor. Nanosci. 16, 2687–2694 (2019) [Abstract] [Full Text - PDF] [Purchase Article]

Design and Numerical Investigation of Porous Nanocrystalline Silicon Membrane Filtration Device for Artificial Kidney Muhammad Fahmi Jaafar, Wan Ammar Fikri Wan Ali, Burhanuddin Yeop Majlis, Jumril Yunas, and Rhonira Latif J. Comput. Theor. Nanosci. 16, 2695–2703 (2019) [Abstract] [Full Text - PDE] [Purchase Article]

Generalized Main Theorem of Spectral Relationships for Logarithmic Kernel and Its Applications M. A. Abdou and F. M. Alharbi J. Comput. Theor. Nanosci. 16, 2704–2711 (2019) [Abstract] [Full Text - PDE] [Purchase Article]

New Design of All-Optical Logic Universal NAND Gate Formed by NOT (A AND B) Gates Using Michelson Interferometer Based on Semiconductor Optical Amplifier Jackson Moreira Oliveira, Hudson Afonso Batista da Silva, Lelis Araujo de Oliveira, Fabio Barros de Sousa, Jorge Everaldo de Oliveira, Fiterlinge Martins de Sousa, Marcio Benedito Caldas Costa, Fabricio Pinho da Luz, and Marcos Benedito Caldas Costa J. Comput. Theor. Nanosci. 16, 2712–2719 (2019) [Abstract] [Full Text - PDF] [Purchase Article]

ERRATUM

Computing Data Quality Issues in Process Mining to Maximize Valuable Customer Service (Journal of Computational and Theoretical Nanoscience, Vol. 16(5/6), pp. 2259–2264 (2019)) S. Sathyalakshmi, S. Ramamoorthy, and V. N. Rajavarman J. Comput. Theor. Nanosci. 16, 2720 (2019) [Abstract] [Full Text - PDF] [Purchase Article]

A SPECIAL SECTION

A SPECIAL SECTION Selected Peer-Reviewed Articles from the First International Conference on Engineering, Innovation Technology and Applied Sciences (ICEITAS2018), Liptsek University, Russia, 14–15 June, 2018—Part II Guest Editor: Mahdi Mahmoudi J. Comput. Theor. Nanosci. 16, 2721–2722 (2019) [Abstract] [Full Text - PDF] [Purchase Article]

REVIEW

An Overview on Wireless Sensor Networks and Finding Optimal Location of Nodes Osamah Ibrahim Khalaf and Bayan Mahdi Sabbar J. Comput. Theor. Nanosci. 18, 2723–2726 (2019) [Abstract] [Full Text - PDF] [Purchase Article]

RESEARCH ARTICLES

Mechanical Investigation of Dental Fillings Polymethylmethacrylate-ZnTiO3 Shahlaa J. Ashour, Fadhil K. Farhan, Zainab F. Nazal, and Osama N. Abood J. Comput. Theor. Nanosci. 16, 2727–2731 (2019) [Abstract] [Full Text - PDE] [Purchase Article]

Hydrothermal Growth of ZnO Nanostructures Deposited on Si Substrate at Room Temperature and Microwave Conditions (Preparation and Morphology) Ishraq Abboodi Fadhil J. Comput. Theor. Nanosci. 16, 2732–2735 (2019) [Abstract] [Full Text - PDF] [Purchase Article]

Atmosphere Distribution Assessment of Volatile Organic Compounds Concentration Using Factor Analysis in a Refinery Plant Ching-Lin Ho and Shu-Lung Kuo J. Comput. Theor. Nanosci. 16, 2736–2741 (2019) [Abstract] [Full Text - PDE] [Purchase Article]

Atmosphere Distribution Assessment of Volatile Organic Compounds Concentration Using Factor Analysis in a Refinery Plant Ching-Lin Ho and Shu-Lung Kuo J. Comput. Theor. Nanosci. 16, 2736–2741 (2019) [Abstract] [Full Text - PDE] [Purchase Article]

Cylindrical Linear Induction Motor with Intermittent Phase Switching Used in the Borehole Plunger Pump Drive with Mechanical Energy Storage Elements Rustam S. Aipov, Ildar I. Gabitov, Denis E. Valishin, Vyacheslav S. Vokhmin, Andrey V. Linenko, Dmitriy S. Leontev, Elena I. Mukhortova, Yaroslav D. Osipov, Salavat V. Akchurin, and Vladimir Y. Kabashov J. Comput. Theor. Nanosci. 16, 2742–2749 (2019) [Abstract] [Full Text - PDE] [Purchase Article]

Joint Polymerization of Epoxides with Carbon Dioxide for Synthesis of Alternating Copolymers Riflat Kudashey, Razida Ishberdina, Ramil Zaripov, Nail Nigmatullin, Ekaterina Ganieva, and Guzel Shabaeva Sont Polymerization of Epoxides with Carbon L Rifkat Kudashev, Razida Ishberdina, Ramil Zaripov J. Comput. Theor. Nanosci. 16, 2750–2755 (2019) [Abstract] [Full Text - PDF] [Purchase Article]

Selection of Optimal Parameters of the Composite Shallow Shell with the Anchor Layer Connection S. V. Yakubovskaya, E. Yu. Ivanova, and N. Yu. Silnitskaya J. Comput. Theor. Nanosci. 16, 2756–2760 (2019) [Abstract] [Full Text - PDE] [Purchase Article]

Intellectual Property in the Orbit of Economic Analysis: Some Aspects Ksenia Michailovna Belikova J. Comput. Theor. Nanosci. 16, 2761–2766 (2019) [Abstract] [Full Text - PDF] [Purchase Article]

Information and Scientific Information in the Orbit of the Economy: Technical and Legal Aspects Ksenia Michailovna Belikova J. Comput. Theor. Nanosci. 16, 2767–2771 (2019) [Abstract] [Full Text - PDF] [Purchase Article] Interaction of Residential House Administrators and Apartment Owners in the Process of Residential Houses' Administration J. Comput. Theor. Nanosci. 16, 2772–2775 (2019) [Abstract] [Full Text - PDF] [Purchase Article] A Methodological Framework for Rationalization of Building Information Systems Nikita Alexandrovich Ryndin, Sergey Vladimirovich Sapegin, and Alexander Alexeevich Ryndin J. Comput. Theor. Nanosci. 16, 2776–2779 (2019) [Abstract] [Full Text - PDE] [Purchase Article] Spectral Properties of the Cauchy Problem for Some Linear Systems of Partial Differential Equations J. Comput. Theor. Nanosci. 16, 2780–2789 (2019) [Abstract] [Full Text - PDF] [Purchase Article] Pour Point Depressants for Transportation of Paraffinic Oil K. S. Nadirov, B. T. Marenov, R. K. Nadirov, G. Zh. Bimbetova, and A. K. Tulekbayeva J. Comput. Theor. Nanosci. 16, 2790–2798 (2019) [Abstract] [Full Text - PDE] [Purchase Article] Methods of Theoretical Researches the Properties of Electrotechnical Materials Class of Dielectrics with Hydrogen Bonds V. A. Kalytka, A. V. Bashirov, A. V. Taranov, G. G. Tatkeyeva, Y. G. Neshina, and Y. A. Sidorina J. Comput. Theor. Nanosci. 16, 2799–2804 (2019) [Abstract] [Full Text - PDF] [Purchase Article] Lighting System for Greenhouses Based on Light Emitting Diode Phytoradiators with Adjustable Radiation Spectrum Sergei S. Kapitonov, Anastasia V. Kapitonova, Sergei Yu. Grigorovich, Sergei A. Medvedev, and Dmitry V. Vilgelm J. Comput. Theor. Nanosci. 16, 2806–2809 (2019) [Abstract] [Full Text - PDF] [Purchase Article] Strengthening of Concrete Structures with Composite Based on Carbon Fiber S. V. Klyuev, S. N. Bratanovskiy, S. V. Trukhanov, and H. A. Manukyan J. Comput. Theor. Nanosci. 16, 2810–2814 (2019) [Abstract] [Full Text - PDF] [Purchase Article] Development and Research of a Multi-Phase Pump for Oil and Gas Production at a High Content of Mechanical Impurities in the Flow M. A. Mokhov, I. A. Sazonov, M. A. Frankov, Kh. A. Tumanyan, and S. V. Kruglov J. Comput. Theor. Nanosci. 16, 2815–2821 (2019) [Abstract] [Full Text - PDE] [Purchase Article] Phytocoenotic Structure and Stocks of Main Medical Plants in Southern Part of Altai Mountain System (East Kazakhstan) S. A. Kubentayev, Yu. A. Kotukhov, A. N. Danilova, A. N. Suleimenov, and A. A. Sumbembayev J. Comput. Theor. Nanosci. 16, 2822–2834 (2019) [Abstract] [Full Text - PDF] [Purchase Article] About Correct Measurement of Bactericidal Lamp Radiation Flow T. A. Chuvatkina, A. V. Kazakov, and A. A. Ashryatov J. Comput. Theor. Nanosci. 16, 2835–2838 (2019) [Abstract] [Full Text - PDF] [Purchase Article] The Current State of the Rheum Wittrockii Lundstr. (Polygonaceae Juss.) Population in the Northern Tien Shan (Kazakhstan) N. A. Saparbaeva, M. O. Aytzhanova, A. Zh. Bozhbanov, I. B. Dzhakupova, G. S. Sultangazieva, and A. S. Berkinbaeva J. Comput. Theor. Nanosci. 16, 2839–2846 (2019) [Abstract] [Full Text. - PDF] [Purchase Article] Reporting a Case of Acute Leukemia in Pregnancy Maryam Hashemnejad, Sahar Mehrabi, Banafsheh Tajbaksh, Sara Esmaelzadeh, Mina Ataei, and Ali Faraji J. Comput. Theor. Nanosci. 16, 2847–2850 (2019) [Abstract] [Full Text - PDE] [Purchase Article] Designing a Compressor Unit for Gas Compression at Sequential Work of an Ejector and a Power Pump Yu. A. Sazonov, M. A. Mokhov, Kh. A. Tumanyan, M. A. Frankov, and V. V. Voronova J. Comput. Theor. Nanosci. 16, 2851–2857 (2019) [Abstract] [Full Text - PDE] [Purchase Article] Building Claddings Thermal Efficiency, Its Comparative Estimation Based on the Small Pieces Wall Materials and Determined by Different Methods Svetlana Yu. Samohodova, Askar M. Gajsin, Igor V. Nedoseko, Igor B. Ryzhkov, Radik F. Mustafin, Samat Z. Insafuddinov, Damir N. Kutiyarov, Bulat G. Bulatov, and Murat T. Sultanov J. Comput. Theor. Nanosci. 16, 2858–2863 (2019) [Abstract] [Full Text - PDF] [Purchase Article] The Quality Test of White Rat Spermatozoa (Rattus norvegicus) Strain Sprague-Dawley by Given of Black Nightshade Juice (Solanum nigrum L.) Prasetyorini, Mulyati Effendi, and Dinda Dwi Cahyani J. Comput. Theor. Nanosci. 16, 2864–2868 (2019) [Abstract] [Full Text - PDE] [Purchase Article] Issues in Ecology of Production and Applicatio Boris Kasaev and Vyacheslav Rusin J. Comput. Theor. Nanosci. 16, 2869–2879 (2019) [Abstract] [Full Text - PDF] [Purchase Article] ion of Mineral Fertilizers The Relationship on University Basketball Coach's Emotional Intelligence, Leadership Behavior, Leadership Effectiveness and Athletic Performance Chih-Chien Shen, Chin-Cheng Yang, Ching-Te Lin, and Ting-Hsiang Chang J. Comput. Theor. Nanosci. 16, 2880–2886 (2019) [Abstract] [Full Text - PDE] [Purchase Article] Factors That Influence Immunity Status in PLWHA (People with HIV/AIDS) in Kuningan District, 2018 Dewi Laelatul Badriah, Cecep Heriana, and Nurwulan Dewi Laelatul Badriah, Cecep Heriana, and Nurwu J. Comput. Theor. Nanosci. 16, 2887–2891 (2019) [Abstract] [Full Text - PDF] [Purchase Article] Adsorption Kinetic of Mn(II) lons in Synthetic Acid Mine Water Using Calcium Carbide Residue as an Adsorbents Muhammad Arief Karim, Subriyer Nasir, Susila Arita Rachman, and Novia Muhammad Arief Karim, Subriyer Nasir, Susila Arit J. Comput. Theor. Nanosci. 16, 2892–2899 (2019) [Abstract] [Full Text - PDF] [Purchase Article] Field-Programmable Gate Arrays: Application in the Digital Signal Processing N. N. Portniagin, Y. V. Repina, and V. N. Portniagin J. Comput. Theor. Nanosci. 16, 2900–2906 (2019) [Abstract] [Full Text - PDF] [Purchase Article] Variability, Heritability and Yield Test of Various Paddy Genotypes (Oryza sativa L.) in Majalaya Sub-District Ai Komariah, Noertjahyani, and Soleh Prihadi Nugraha J. Comput. Theor. Nanosci. 16, 2907–2913 (2019) [Abstract] [Full Text - PDF] [Purchase Article] Biodiesel from Jelantah Oil with Catalyst FCCU Base Chemical Al₂O₃ Based Speed of Statement and Comparison of Reaction Kiagus Ahmad Roni, Atika Dewi, and Muhammad Arief Karim J. Comput. Theor. Nanosci. 16, 2914–2925 (2019) [Abstract] [Full Text - PDE] [Purchase Article]

Prospects of Plasma Technology in Cross-Cutting Technologies Used in Functional Food Production and Seed Germination for Reforestation I. R. Shegelman, A. S. Shtykov, K. V. Gostev, O. I. Gavrilova, and A. S. Vasilev J. Comput. Theor. Nanosci. 16, 2926–2933 (2019) [Abstract] [Full Text - PDF] [Purchase Article] An Energy-Efficient Optimization Based Scheme for Low Power Devices in Wireless Body Area Networks Dalal Abdulmohsin Hammood, Hasliza A. Rahim, Ahmed Alkhayyat, R. Badlishah Ahmad, M. Abdulmalek, Dalal Abdulmohsin Hammood, Hasliza A. Rahim, A Sarah Yahya Ali, and Ibtehal Shakir Mahmoud J. Comput. Theor. Nanosci. 16, 2934–2940 (2019) [Abstract] [Full Text - PDF] [Purchase Article] Elemental Composition of Humica Cidsburied in Sapropel's Bog M. P. Sartakov, E. M. Osnitsky, A. A. Novikov, M. V. Efanov, and I. D. Komissarov J. Comput. Theor. Nanosci. 16, 2941–2944 (2019) [Abstract] [Full Text - PDF] [Purchase Article] Novel Adaptive Segmentation Based Forgery Detection Method R. Dhanya and R. Kalai Selvi J. Comput. Theor. Nanosci. 16, 2945–2949 (2019) (Abstract) [Full Text. – PDF] [Purchase Article] Building Constructions Optimization According to Genetic Algorithm S. V. Klyuev, A. V. Klyuev, A. J. Abakarov, V. F. Danilov, and E. Ph. Chubenko J. Comput. Theor. Nanosci. 16, 2950–2953 (2019) [Abstract] [Full Text - PDF] [Purchase Article] The Role of Educational Intervention Based on the Health Belief Model in Colorectal Cancer Screening of Teachers in Fasa Mostafa Bijani, Afsaneh Ghasemi, Shahnaz Karimi, Zhila Freidooni, Najimeh Beygi Mostafa Bijani, Afsaneh Ghasemi, Shahnaz Karimi J. Comput. Theor. Nanosci. 16, 2954–2958 (2019) [Abstract] [Full Text - PDF] [Purchase Article] Determinants of Supply Chain Employees Safety Behaviours Kitisak Jermsittiparsert, Thanaporn Sriyakul, Jutamat Sutduean, and Ayoruethai Singsa J. Comput. Theor. Nanosci. 16, 2959–2966 (2019) [Abstract] [Full Text - PDF] [Purchase Article] Effect of Cultural Traits, Leadership Styles and Commitment to Change on Supply Chain Operational Excellence Thanaporn Sriyakul, Ayoruethai Singsa, Jutamat Sutduean, and Kittisak Jernsittiparsert J. Comput. Theor. Nanosci. 16, 2967–2974 (2019) [Abstract] [Full Text - PDE] [Purchase Article] Supply Chain Integration, Enterprise Resource Planning, and Organizational Performance: The Enterprise Resource Planning Implementation Approach Jutamat Sulduean, Ayoruethai Singsa, Thanaporn Sriyakul, and Kittisak Jernsittiparsert J. Comput. Theor. Nanosci. 16, 2975–2981 (2019) [Abstract] [Full Text - PDE] [Purchase Article] Willingness of Supply Chain Employees to Support Disability Management at Workplace: A Case of Indonesian Supply Chain Companies Ayoruethai Singsa, Thanaporn Sriyakul, Jutamat Sutduean, and Kittisak Jernsittiparsert J. Comput. Theor. Nanosci. 16, 2982–2989 (2019) [Abstract] [Full Text - PDE] [Purchase Article] The Influence of Growth Regulators on In-Vitro Culture of Rosa Hybrida Kazem Kamali Aliabad, Amir Rezaee, Farhad Homayoonfar, and Elahe Zama J. Comput. Theor. Nanosci. 16, 2990–2994 (2019) [Abstract] [Full Text - PDF] [Purchase Article] Research Design to Construct Prototype Arc Type Neodymium Magnets Generator Priagung Wahyudi, Sri Haryati, and Muhammad Djoni Bustan J. Comput. Theor. Nanosci. 16, 2995–3001 (2019) [Abstract] [Full Text - PDF] [Purchase Article] The Evaluation of Stress Prevalence Among Iranian Emergency Staff Maryam Kia, Seyed Ali Ahmadi Abhari, Mohammad Vaseie, and Seyed Mojtaba Aghili J. Comput. Theor. Nanosci. 16, 3002–3006 (2019) [Abstract] [Full Text - PDE] [Purchase Article] Development and Research of Multi-Phase Reversible Pump M. A. Mokhov, I. A. Sazonov, M. A. Frankov, Kh. A. Tumanyan, S. V. Kruglov, and A. V. Muradov M. A. Mokhov, I. A. Sazonov, M. A. Frankov, Kh. A. J. Comput. Theor. Nanosci. 16, 3007–3012 (2019) [Abstract] [Full Text - PDF] [Purchase Article] Fabrication and Characterization of TiO2 Nanowires as Photoanode Electrode of the Dye-Sensitized Solar Cell Qahtan A. Yousif and Noura H. Haran J. Comput. Theor. Nanosci. 16, 3013–3017 (2019) [Abstract] [Full Text - PDF] [Purchase Article] Experimental Investigation of Anisotropy of the Strength Properties of the Sand-Polymer Casting Moulds, Which Were Manufactured in Accordance with the Method of the Layered Synthesis Peter I. Galinov and Aleksandr G. Netkachev J. Comput. Theor. Nanosci. 16, 3018–3025 (2019) [Abstract] [Full Text - PDF] [Purchase Article] Evaluation Performance of Disc Plow with a Notched Disc Mahmood N. Al-Irhayim, Khalid E. Al-Mistawi, and Ahmed M. Amen Said J. Comput. Theor. Nanosci. 16, 3028–3029 (2019) [Abstract] [Full Text - PDF] [Purchase Article] An Intelligent Decision Support System for Performance Evaluation of Research Institutes Mahdi Nakhaie Kohan and Ali Moeini J. Comput. Theor. Nanosci. 16, 3030–3039 (2019) [Abstract] [Full Text - PDF] [Purchase Article] Experimental Study of a Reconfigurable System with Hardware Task Manager and a Distributed Queue I. Martyshkin Alexey and S. Martens-Atyushev Dm J. Comput. Theor. Nanosci. 16, 3040–3045 (2019) [Abstract] [Full Text - PDF] [Purchase Article] Development of Methods for Multiprocessor System Analysis Based on Common Bus During the Stage of System Configuration Synthesis I. Martyshkin Alexey, I. Salnikov Igor, and A. Bashveev Yuri J. Comput. Theor. Nanosci. 16, 3046–3053 (2019) [Abstract] [Full Text - PDF] [Purchase Article] The Maturity Estimation of Material Organic in CaCO $_3$ with Determining $T_{
m max}$ and Energy Activation Using Pyrolysis Method Ordas Dewanto, Sri Rizky, Bagus S. Mulyanto, and Rustadi J. Comput. Theor. Nanosci. 16, 3054–3065 (2019) [Abstract] [Full Text - PDF] [Purchase Article] The Process of Production and Operation of Turbomachines and Numerical Optimization of Its Performance Behzad Ranihar Behzad Ranjbar J. Comput. Theor. Nanosci. 16, 3066–3075 (2019) [Abstract] [Full Text - PDF] [Purchase Article] Using the Knowledge Base as a Tool for Improving Forestry Technology (By Example, Harvester Head) A. S. Vasilev, I. R. Shegelman, O. N. Galaktionov, A. V. Kuznetsov, Y. V. Sukhanov, and A. S. Shtykov A. S. Vasilev, I. R. Shegelman, O. N. Galaktionov, A. J. Comput. Theor. Nanosci. 16, 3076–3086 (2019) [Abstract] [Full Text - PDE] [Purchase Article] Development of Technologies for Increase the Ejector Units' Efficiency I. A. Sazonov, M. A. Mokhov, Kh. A. Tumanyan, M. A. Frankov, V. A. Mun, and L. V. Osicheva J. Comput. Theor. Nanosci. 16, 3087–3093 (2019) [Abstract] [Full Text - PDF] [Purchase Article]

Ways to Improve Production Efficiency Problems and Ways of Their Solution P. M. Kosianov J. Comput. Theor. Nanosci. 16, 3094–3097 (2019) [Abstract] [Full Text - PDF] [Purchase Article]

Investigating the Incidence of Instruments Fall During Surgery in Alzahra Medical Educational Center of Isfahan in 2017 Amin Sedigh, Soheila Mojdeh, Mehdi Rasti Ardekani, and Sara Bagheri J. Comput. Theor. Nanosci. 16, 3098–3102 (2019) [Abstract] [Full Text - PDF] [Purchase Article]

Development and Research of Means for the Collection and Reporting of Open-Source Information for Use in Decision-Making Systems I. Martyshkin Alexey and V. Pashchenko Dmitry J. Comput. Theor. Nanosci. 16, 3103–3114 (2019) [Abstract] [Full Text - PDF] [Purchase Article]

Automated Portable Installation to Determine the Thermo Physical Properties of the Object Kabanov Oleg Vladimirovich, Panfilov Stepan Aleksandrovich, Prokin Alexander Alexandrovich, and Sergushina Elena Sergeevna J. Comput. Theor. Nanosci. 16, 3115–3120 (2019) [Abstract] [Full Text - PDF] [Purchase Article]

Measuring the Thermo Physical Properties of Construction Projects Kabanov Oleg Vladimirovich, Panfilov Stepan Aleksandrovich, Prokin Alexander Alexandrovich, and Sergushina Elena Sergeevna J. Comput. Theor. Nanosci. 16, 3121–3127 (2019) [Abstract] [Full Text - PDF] [Purchase Article]

Statistical Inference for Parameters of the Beta Exponentiated Gompertz Distribution According to Type-II Censoring Hana H. Abu-Zinada and Nouf M. Hajar J. Comput. Theor. Nanosci. 16, 3128–3135 (2019) [Abstract] [Full Text - PDF] [Purchase Article]



The Maturity Estimation of Material Organic in $CaCO_3$ with Determining T_{max} and Energy Activation Using Pyrolysis Method

Ordas Dewanto*, Sri Rizky, Bagus S. Mulyanto, and Rustadi

Geophysics Engineering, Engineering Faculty, University of Lampung, Bandar Lampung, 35145, Indonesia

Shale material is shale oil that is clay or carbonate material contain excessively immature organic. When heated to a certain temperature, the organic content changed to mature and changed in physics and chemistry, so it can produce energy materials such as oil and gas. The testing of TOC that produced carbonates-organic showed excellent quality as shale oil (TOC \geq 12.0%). The results of thermogravimetric analysis showed activation energy of carbonates was 749–1339 kJ/mol and the temperature of the reaction process was 75–740 °C. Organic composition that was larger than carbonate can caused a smaller activation energy. The carbonate content of OD7-Asl2 had $E_a = 1083.7$ kJ/mol smaller than OD7-Asl1 with $E_a = 1338.1$ kJ/mol. A very large TOC value affected the activation energy to be smaller, as the carbonate of OD7-Asl2 was smaller than OD7-Asl1. The maturity of the OD7-Asl2 shale occurred at T = (380-445) °C, $E_a = 1083.7$ kJ/mol and $T_{max} = 415$ °C, better than OD7-Asl1. The Rock Eval Pyrolisis test results showed shale carbonate had a high potential to produce oil and gas. Shale material heating result reinforced by FTIR testing that the compounds with specific functional groups apart and a new peak appeared at wavenumber 2900 cm⁻¹ which indicate the presence of hydrocarbons single bonds.

Keywords: Oil Shale, TOC, Activation Energy, Pyrolysis.

1. INTRODUCTION

Oil shale is a kind of clay or carbonate shale material that contains a lot of organic materials, and an energy source that can produce oil and gas [10] (Kantsler and Cook, 1980). The result of oil shale processing is very useful in the agricultural sector and property industry [1–3]. A research on the oil shale becomes a main research in Soviet Union [21]. Berraja et al. [5] started the research on thermal analysis study at the combustion of oil shale in Tafaya.

From the results of research by Mulyanto et al. [26]: Organic substances that are in sedimentary rocks or carbonate will undergo chemical and physical changes, caused by temperature, heat, pressure and age. Such changes can lead to the formation of oil or gas. To predict the properties of rock containing organic matter, inquiry can be done by looking the chemical and physical properties. To determine the chemical and physical properties, can be used petrophysical and geochemical technology, supported by geological data, seismic technology and technology geothermal (heat). The *Rock-Eval Pyrolysis* method has been initiated by Katz [19] to analyze the organic material. Bartis et al. [4] did the oil shale exploitation that was gathered and sent to the processing place by burning the oil shale to be utilized as a source of electrical energy. Then Burnham et al. [6] did the extraction on the result of shale material processing which was done on the ground (*ex-situ* processing), and there were some new technologies which carried out the extraction on the shale material underground (*in situ* processing).

The processing of carbonate or clay shale material has not been done in Indonesia, but the reserve of shale material in Indonesia has been mapped. Geological Resource Centre has conducted the research on the oil shale material in 53 locations in Indonesia. The processing of shale material by heating requires some appropriate parameters, so that the changing reaction (maturation) in physics, chemistry and biology can occur in accordance with the desire. Some of the parameters associated with the variation or organic maturity level is the temperature, the energy activation (inversely proportional to the velocity of the reaction) and the material type. In this case, the maturation is defined as maturation of the organic material in the

^{*}Author to whom correspondence should be addressed.

carbonate material, or often referred to shale material or oil shale.

From the results of Dewanto et al. [11] research: The time to change the immature organic clay and organic carbonate material into oil and gas (energy source), is determined by the characteristics of the shale material, which are: the immature hydrocarbon substance has API gravity and and boiling point which is close to petroleum's boiling point; the heating process at temperature of 200 °C to 400 °C changes the substance into shale material with low boiling point, this is due to the high degree of its API so it contains more light fractions such as gasoline, thus its boiling point is low.

In this research, the production of carbonate shale material is by compounding the organic material and CaCO₃. The compounding is done using the way of weight percentage ratio variation, mixing, mixing time and the last is the result of TOC testing (pyrolysis), where the value of TOC is >12.0% [32] as a requirement of good oil shale material. The material mixture is modified by the ratio of: organic = calcite and organic > calcite. The TOC testing that produces carbonate shale material shows an excellent quality of oil shale (TOC $\geq 12.0\%$), which is confirmed by the result of SEM analysis (morphology and composition) and XRD (the interaction of two materials). By determining the level of organic maturation in CaCO₃, then the task will be more structured and accurate. Reaction stage-1 is *immature*, which is the immature organic material; reaction stage-2 is *mature-1*, which is the mature organic material or starting to crack material; reaction stage-3 is mature-2 and over mature-1, which is the organic material turning into hydrocarbon and some generating the gas; reaction stage-4 the release of all gases.

The reaction stages are closely related to the energy activation (including temperature and reaction velocity), and the type of shale material (carbonate-organic). By knowing the parameter value (from the result of the energy activation) and the type of material, then the shale material processing in term of temperature setting can be determined, so that no error occurs in the heating process.

The *Rock-Eval Pyrolisis* testing is not only used to determine the total organic carbon (TOC), but also to determine the value of T_{max} (maximum temperature). Then to determine the maturity of organic material, detect oil and gas reserve and to reidentify the type of some material mixture.

The TGA testing is conducted to determine the value of the energy activation. By conducting a series of tests to obtain a pair of dY/dt and T_{solid} , so the chart of $\ln(dY/dt)$ with $1/T_{solid}$ can be made. Then the straight-line equation of the chart is searched by using linear regression, so the value of the energy activation can be determined from: E = -aR, the value of pre-exponential factor (A) is found when the chart of y = ax + c intersects the y axis or $1/T_{solid} = 0$ [7, 15, 31].

The formulation and analysis on the energy activation is based on some previous researchers, namely: Pogaku et al. [27] conducted a research on the energy activation and the velocity enzyme-catalyzed reaction. There are several researchers conducting research on the activation of SiO_2 energy which depends on the input power. Indrati et al. [15] conducted a research on the energy activation of pellet (Th, U)Oz at the stage of pellet growth using a dilatometer and Scanning Electrone Microscope (SEM). Cahyadi et al. [7] conducted a research on the behavior of Indonesia's coal particle ignition using Thermogravimetric Analysis at the condition of O_2/N_2 and O_2/CO_2 . Sato et al. [28] conducted a research on the activation free energy that has a dependence on the temperature. The temperature dependence is found greater for the calculation. The determination of the energy activation, pre-exponential factor and reaction velocity from TGA analysis refers to several researchers, they are: Katarzyna et al. [18], Himawanto [13], Himawanto et al. [14], Emam [12], Marnoto [23], Yan and Zhang [33], Sugondo [29], Sukma [30], Malika et al. [22], Martono et al. [24], Cantrell et al. [8], Suyitno [31], Kholisoh [20], Minarsih [25], Jiang et al. [16].

Through this research, it is expected that the shale material (Carbonate-Organic) which has been characterized by a variety of methods, can be obtained its physics and chemistry property information to understand the detail of mechanism and the active site on both shale materials, then compare and determine the best one, so that the parameter of laboratorium test can be determined for making the convertion model on the reaction of shale material into crude oil. Further, it is hoped that it can be used as the raw material of the oil shale processing, as the raw material which is excessively available in Indonesia and ready to be used as one of the alternative energy resources.

2. METHOD OF RESEARCH

The Selection of Carbonate and Organic

The stage of determining material type is the most important stage in the material selection. Firstly, choose the material from the result of coring drilling, then the material is grouped, namely the carbonate material group type calcite (CaCO₃). The carbonate material must be completely clean from fluid and natural hydrocarbon, therefore prior to the measurement of porosity and permeability, the material should be in dry condition (dry sample). Secondly, determine the material organic cyclic group, namely salicylic acid (C₇H₆O₃).

The Characterization of Carbonate and Organic

The tools used for the characterization of clay and carbonate are SEM and XRD, in order to know the identity of the material. SEM is used to know the type of elements, distribution, topography and the surface shape. The XRD technique can show the type and compound percentage as well as the characteristic of the crystallography.

The Making of Shale Material (Carbonate-Organic) and TOC Testing

The forming method of carbonate shale material is by stirring for a long time, then pressing slowly and leaving to stand for a moment (72 hours) and stirring again and also pressing slowly again, the purpose is to make the organic material fills all pores of the carbonate material. Furthermore, the shale material is left to stand at least 48 hours, the purpose is to make the trapped organic material (fills) the pores and be more binding and cohessive. Then the TOC is tested and made like an oil shale, with the same characteristic, which is TOC $\geq 12\%$.

The Characterization of Carbonate Shale Material

The carbonate shale material that has been made is characterized by using SEM. The purpose is to know the morphology, the particle size, the content of the material, the pores of the material and the elements. Whereas the characterization using XRD has a purpose to know the compound type, the compound percentage and the crystallography, in addition to know the distance of basal area (d_{001}) from natural CaCO₃ that has been mixed with the organic material (salicylic acid).

The TGA Testing on the Carbonate Shale Material

Thermogravimetry is a technique to measure the weight change of a compound as a function of temperature or time. The result is a continuous diagram recording; the schematic single stage decomposition reaction. The two types of main thermal analysis are thermogravimetry analysis, which automatically records the weight change of the sample as a function of temperature or time, and differential thermal analysis (DTA), which measures the difference of *T* temperature between the sample and the referen inert material as a function of temperature.

The Determination of Temperature and Energy Activation

The calculation of the energy activation in this research uses the formula of kinetics calculation of order one reaction or commonly called as *global kinetic*. The determination of energy activation quantity is using graphical method with the formula that is based on Arrhenius equation. The reason in choosing *global kinetic* method is since this research does not consider the elementary reaction that occurs, but only considers the velocity of shale material in reacting, so it can turn into hydrocarbon. The formulation used in global kinetic is:

$$\frac{dx}{dt} = Ae^{-E_{a}/RT}(1-x) \tag{1}$$

where; dx: The loss in mass fraction; dt: The change of time (dt); A: the pre-exponential factor; e: The natural

number (2, 72); *E*: The energy activation (J/mol) or E_a ; *R*: The gas constant (8, 31 J/mol °K); *T*: The material temperature (°K).

x is the mass fraction, which is calculated by the formula of,

$$x = \frac{m_0 - m_f}{m_0 - m_f}$$
(2)

where *m* is the mass of the sample when the time is ke-t, m_0 is the initial mass of the sample and m_f is the final mass of the sample. The heating rate is defined,

$$\beta = \frac{dT}{dt} \tag{3}$$

By combining the Eqs. (1)–(3), so the Eq. (1) becomes,

$$\frac{dx}{dT} = \frac{A}{\beta} e^{-E_a/RT} (1-x) \tag{4}$$

$$\frac{dx}{(1-x)} = \frac{A}{\beta} e^{-E_a/RT} dT$$
(5)

If both sides are integrated, so the Eq. (5) will be,

$$-\ln(1-x) = \frac{A}{\beta} \int e^{-E_a/RT} dT$$
(6)

In the Eq. (6), the term $\int e^{-E_a/RT} dT$, is an inexact integral but it can be expressed in the *asymptotic series*, so that the Eq. (6) can be integrated to be,

$$-\ln(1-x) = \frac{ART^{2}}{\beta E_{a}} \left(1 - \frac{2RT}{E_{a}}\right) e^{-E_{a}/RT}$$
(7)

$$-\ln\frac{(1-x)}{T^{2}} = \frac{AR}{\beta E_{a}} \left(1 - \frac{2RT}{E_{a}}\right) e^{-E_{a}/RT}$$
(8)

$$\ln\left[-\frac{\ln(1-x)}{T^2}\right] = \ln\left[\frac{AR}{\beta E_a}\left(1-\frac{2RT}{E_a}\right)\right] - \frac{E_a}{RT} \quad (9)$$

In the fact, the term of:

$$\frac{2RT}{E_{\rm a}} \ll 1$$

So it can be ignored and the equation becomes,

$$\ln\left[-\frac{\ln(1-x)}{T^2}\right] = \ln\left(\frac{AR}{\beta E_a}\right) - \frac{E_a}{RT}$$
(10)

By making the connection chart between $\ln[-\ln(1-x)/T^2]$ and 1/T, the straight line can be obtained where the slope of the line is $-E_a/R$, so that the value obtained is E_a . The delineation chart of the relationship between $\ln[-\ln(1-x)/T^2]$ and 1/T heating process as a basis for calculating the energy activation on the shale material heating.

Determining the Maximum Temperature (T_{max}) by Pyrolysis Testing

 $T_{\rm max}$ is the maximum temperature to release the hydrocarbon from the cracking process of the material mixture that occurs during the pyrolysis. $T_{\rm max}$ is an indication of organic maturation stage in the shale-carbonate. The $T_{\rm max}$ value is one of the geochemical parameters used to determine the maturity level of shale-carbonate. The value $T_{\rm max}$ that recorded is influenced by several types of material mixtures mentioned above. Some of the material mixtures will form the different hydrocarbons at the same temperature condition. The $T_{\rm max}$ value as an indicator of maturity also has some limitations such as it can not be used for some types of materials that have low TOC.

3. RESULTS AND DISCUSSION

Figure 1 shows the description of determination of material type to the processing step in the laboratorium, starting from the coring process, the material selection, the production of carbonate-organic material sample, and also the tests.

The Selection of Carbonate and Organic

The carbonate material that has been formed as pellet with a variety of diameter sizes is shown at Figure 2, where the material is already in dry condition.

Some of carbonate materials used is the material with the sample number OD7, while the organic material choosen is group of cyclic compound such as salicylic acid.

The Determination of TOC (Total Organic Carbon) and $T_{\rm max}$ on Carbonate Shale Material

The result of shale material manufacture $(CaCO_3 - C_7H_6O_3)$ shows a very good result as oil shale, because it has a value of TOC $\geq 12\%$ and the characteristic is the same as oil shale. The TOC testing is successfully performed on the sample of carbonate-organic material (OD7-Asl). This TOC value is used as one of the parameters for initial selection stage on the material selection in order that can be used as shale material (oil shale), so that the bad and good material can be separated to be the raw material of further processing.

The carbonate-organic shale material has shown the excellent quality, which has a value of TOC $\geq 12.0\%$. Table I shows the value of TOC and T_{max} from the result of pyrolysis that is used as an initial indicator of the thermal maturity level of carbonate-organic shale material. The material maturity shows a varied value, and the carbonate shale of OD7-As11 requires a greater temperature than the carbonate shale of OD7-As12. The combination between TOC and T_{max} indicates that the carbonate shale material that acts as oil shale is likely more potential as oil and gas.

The SEM Analysis on the Organic Material

Figure 3 shows the SEM image and Edax on the salicylic acid $(C_7H_6O_3)$ organic material.

From the result of Edax, the organic material has a dominant content of C and O. The organic material infiltrates into the Kerogen type II which can be formed from some different sources, namely the marine algae, pollen and spore, wax layer of plant, resin fossil, beside that it also derives from the plan fat. This occurs due to the mixing



Fig. 1. The coring process, the determination of material type to the processing step in the laboratorium.



Fig. 2. The carbonate material is formed as pellet.

of organic material *autochton* with *allochton* material that dominated by material from plants such as pollen and spore. Its SEM image looks like the bonded white blobs.

The SEM Analysis on the Carbonate Material

Figure 4 shows the result of SEM analysis on the carbonate material (OD7). The carbonate material (OD7) has many pores. Some areas of the pore cavity can be filled with other material (C–E, 2–4). The carbonate material is dominated by *calcite* (D–E, 2–3; B–D, 2–4) and a little dolomite (C–D, 5–6). Besides the carbonate material is dominated by the carbonate, it also has little clay material (illite dan kaolinite) that is situated around the pores. The type of the pore is secondary pore, where the distribution of the secondary pore is caused by the dissolution of planktonic (C–D, 2). From the result of Edax SEM on the carbonate CaCO₃, it has a great content of Ca and O (dominant).

The SEM Analysis on the Carbonate Shale Material (Carbonate-Organic)

The surface area of the shale material that has been filled by the organic is smaller, so it can be indicated that the place of the carbonate has been filled by the organic, because the pores becomes smaller. The SEM image of the carbonate shale (calcite) has the dominant secondary pores. At a certain time, the porosity will change and cause the organic material exits and enters the pores. The calcite material is success as a place of perfect maturation of organic material.

Figure 5 shows the carbonate shale material OD7-Asl2 (33% CaCO₃ and 67% salicylic acid). From the result of Edax SEM on the carbonate shale OD7-Asl2, it contains

Table I. The result of TOC (total organic carbon) testing.

No.	Sample name	TOC (%)	T_{\max} (°C)
1.	OD7-Asl1 (50% CaCO ₃ + 50% C ₇ H ₆ O ₃)	12.01	432
2.	OD7-Asl2 (33% CaCO ₃ + 67% $C_7H_6O_3$)	12.89	415
3.	OD7-Asl3 (67% $CaCO_3 + 33\% C_7H_6O_3$)	9.14	493



Fig. 3. The image of SEM on salicylic acid.

some elements with (wt, %) dominated by Ca, O and C, as follows Carbon (43.65%), Oxygen (40.81%) and Calcium (11.78%).

The Measurement of X-ray Diffraction (XRD)

The result of the carbonate OD7 characterization is in the form of diffraction patterns which are the peaks characteristic of crystal CaCO₃ structure. Figure 6 shows the chart of the XRD result on the shale material (carbonate-organic) OD7, OD7-Asl1, OD7-Asl2, and OD7-Asl3. The diffraction patterns of CaCO₃ are identified at the angle of 2θ . If the peaks of CaCO₃ characteristic appear, so the compound phase can be identified. The X-ray diffraction pattern that formed is the result of atoms scattering that is located on the *hkl* plane in the crystal. The carbonate OD7 has five high peaks and the intensity will change when there is an organic addition. The angle 2θ position is at the angle of 26.66° , 29.48° , 36.05° , 39.50° and 43.27° with the intensity values captured by the X-ray detector are 779 cts,



Fig. 4. The result of SEM and Edax OD7 (calcite).

20383 cts, 3477 cts, 4172 and 3252 cts. The peaks that formed are the peak of crystal Graphite C_1H_2 and Calcite CaCO₃ and Caron. The crystal planes or Miller indices *hkl* are (011), (104), (110), (161) and (202).

The carbonate shale material OD7-Asl1 has five highest peaks at the same angle position of 2θ as shale material OD7-Asl2, which are at the angle of 10.94°, 17.21°, 25.23°, 28.70° and 29.41°, with the intensity values captured by the X-ray detector are 47282, 44513, 18466, 8361 and 12199 cts. The peaks that formed are the peak of crystal Carbon Dioxide, Fichtelite C₁₉H₃₄, Calcium, Carbon and Calcite CaCO₃, and it can be identified that the crystal planes or Miller indices *hkl* are (100), (200), (110), (231) and (104). The shale material (carbonate-organic) OD7-Asl3 has 5 highest peaks at the position of 2θ , which are 10.96°, 17.23°, 25.24°, 26.61° and 29.43°, with the intensity values captured by the X-ray detector are 12771, 13314, 4687 and 18095. From the result, it can



Fig. 5. The image of SEM on the material of OD7-Asl2.

be concluded that the peaks that formed are the peak of crystal Fullerite, Nitrammite N₂H₄O₃ and Calcite CaCO₃, and it can be identified that the crystal planes or Miller indices *hkl* are (111), (101), (002), (003) and (104). The addition of organic material (C₇H₆O₃) is performed on the natural carbonate (OD7) with a particular composition. At the angle of 2 theta = 29° with the same *hkl* plane, the calcite (104) condition experienced on the shale material is the intensity of OD7 \ge OD7-Asl3 > OD7-Asl1 > OD7-Asl2. While at the angle of 2 theta = 25° and the angle of 2 theta = 17°, the condition experienced on the carbonate material is the intensity of OD7 \le OD7-Asl3 < OD7-Asl1 < OD7-Asl2. The result of XRD characterization on the carbonate shale material which has the highest intensity is shown on the Figure 6 and Table II.

The organic addition causes the *preferred orientation* on the specific crystal planes, it leads the crystal planes having the higher intensity than before. While the angle of 2 theta and its hkl plane do not change. Based on the image, it can be seen that the intensity of X-ray that absorbed by



Fig. 6. The XRD characterization on the carbonate and shale material (carbonate-organic).

Table II. The XRD characterization on the carbonate shale material which has the highest intensity.

No.	Material name	Pos. [°2Th.]	Height [cts]	d-spacing [Å]	hkl	Compound
1.	OD7	29.48	20383	3.03	104	Calcite, CaCO
2.	OD7-Asl1	10.94	46314	8.08	100	Carbon dioxide
3.	OD7-Asl2	10.94	47282	8.08	100	Carbon dioxide
4.	OD7-Asl3	29.43	18095	3.03	104	Calcite, CaCO



Fig. 7. The chart of thermogravimetry (TGA) analysis result on the shale material (OD7-As11).

the detector on every sample, has different value. High or low the X-ray intensity that captured by the X-ray detector is influenced by the level of the regularity of atom formation in the crystal that is diffracted by X-ray. The more atoms are structured regularly, the higher the intensity that captured by the detector. When the intensity is greater means the sample has the greater crystal regularity or more well arranged atoms in the layers. The X-ray diffraction patterns that formed are the result of atoms scattering that located at the *hkl* plane in the crystal. Any difference or change in the compound and *hkl* plane at the same angle of 2 theta at every organic addition, it means the reaction occurs between CaCO₃ material and organic.

The Result of TGA Testing on the Shale Material (Carbonate-Organic)

The test is carried out on the carbonate shale material OD7-Asl1, with the composition of 50% CaCO₃ and 50% C₇H₆O₃. The result of TGA testing on the shale material OD7-Asl1 is shown on Figure 7. The first change occurs at the temperature of 75 °C–170 °C, this is where the loss of water molecules happens in the crystal structure. At the temperature of 225 °C–275 °C, the second weight change that significant occurs, and it is indicated as the change in the structure on the carbonate shale material and the loss of water molecules chemically.

When the calcination is reperformed, the weight loss occurs at the temperature of 325 °C–450 °C, then the molecules in the carbonate shale are released, so that it will affect the change on the pore size. The interval temperature of 325 °C–450 °C indicates the maximum temperature that required for carbonate shale to turn into oil. The last change phase occurs at the temperature about 650 °C–740 °C. This condition can be called as over mature, where the chart line has shown a tendency of straight horizontal. Physically, the material that



Fig. 8. The chart of thermogravimetry (TGA) analysis result on the shale material (OD7-Asl2).

RESEARCH ARTICLE

has been calcined at the temperature above 740 °C, the color becomes blackish. So the temperature that required at the process of the change (reaction) of oil shale material on the carbonate shale to be oil is about $\pm(325 \text{ °C}-450 \text{ °C})$.

Then the TGA testing is performed on the material OD7-Asl2 (calcite-salicylate), namely the test on the carbonate shale material where the composition is the mixture of 33% CaCO₃ and 67% $C_7H_6O_3$. This test is performed to know the structural damage when heating at the high temperature is carried out (over 400 °C), because it can provide the description of the change process in the substance mass. The result of TGA testing on the shale material OD7-Asl2 is shown on the Figure 8.

The first weight loss occurs at the temperature of ± 95 °C–205 °C, it indicates the water molecules apart from the crystal structure of OD7-Asl2. Then the second weight loss occurs at the temperature around 225 °C-285 °C. The second significant weight change indicates the change in the structure of the material OD7-Asl2 and the loss of water molecules chemically. Then the third weight loss occurs at the temperature of 380 °C-445 °C, where the molecules in OD7-Asl2 is apart. The interval of temperature indicates the maximum temperature that required by OD7-Asl2 (carbonate shale) to begin turning into oil. When the calcination is always performed to the last loss until becoming constant, which is at the temperature of 610 °C-720 °C, then many molecules in OD7-Asl2 (the carbonate shale) are apart, so that there is part of the shale in the pores is also apart. This condition can be called as over mature, where the line of the chart shows a tendency of straight horizontal along with the increasing of the temperature up to 720 °C. Physically, the material that has been calcined at the temperature above 720 °C, the color becomes blackish. So the temperature required for the maturation process of the oil shale OD7-Asl2 into crude oil is about ±(380 °C-445 °C).



Fig. 9. The chart of mass loss versus time of reaction on the shale material (carbonate-organic).

The Duration of Heating the Material

The carbonate shale material OD7-Asl2 undergoes the heating process faster than the material of OD7-Asl1.

Figure 9 shows the relationship between the mass loss versus the time on the carbonate shale material. The



Fig. 10. The chart of $\ln[-ln(1-x)/T^2]$ versus 1/T, for E_a and A determination on the OD7-As11 using TGA.

greater ratio of organic composition than calcite causes maturation reaction in the heating process becoming faster.

The Energy Activation and Pre Exponential Factor of Shale Material OD7-Asl1

The TGA gradual decomposition process that is used alone or combined with DTA can separate and determine each stage. On this shale material sample (carbonate-organic), the four-level decomposition occurs, it can be seen on Figure 7. The result of TGA shows that the decomposition level of shale material is divided into four levels of temperature, which are level I is between the temperature of 75 °C-170 °C, level II occurs between the temperature of 225 °C-275 °C, level III is between the temperature of 325 °C-450 °C and level IV occurs between the temperature of 670 °C-740 °C. Figure 10 shows the method of determining the energy activation (E_a) and the pre exponential factor of OD7-Asl1. In the process of heating the material OD7-Asl1, the decomposition goes through four stages. The TGA and DTA can be used in a variety of kinetic studies. The fast and accurate TGA method is used to study the decomposition reactions isothermally. This process can be repeated at other temperature and the result is analyzed to determine its energy activation.

The energy activation (E_a) values and pre exponential factor of each reaction stage at 4 levels reaction are shown in Table III.

The total value of the energy activation on the heating of the material OD7-Asl1 is $E_a = 1338.1$ kJ/mol and the pre exponential factor is A = 172.

The Energy Activation and Pre Exponensial Factor of Shale Material OD7-Asl2

The gradual decomposition process on the shale material OD7-Asl2 (carbonate-organic) occurs on four levels decomposition, it is shown on the result of TGA testing on Figure 8.

The decomposition level of shale material OD7-Asl2, from the result of TGA is divided into four levels of temperature, which are level I is between the temperature of 95 °C-205 °C, level II occurs between the temperature of 225 °C-285 °C, level III occurs between the temperature of 380 °C-445 °C and level IV occurs between the temperature of 610 °C-720 °C. The chart of the energy activation (E_a) and pre exponential factor determination of OD7-Asl2 is shown on Figure 11. The total value of the energy activation on this shale material (the organic ratio

Table III. The E_a and A values of OD7-Asl1 material.

Reaction level	$E_{\rm a}$ (kJ/mol)	A (%/s)	
75 °C–170 °C	102.89	17	
225 °C–275 °C	333.32	62	
325 °C-450 °C	200.79	22	
670 °C–740 °C	701.14	71	



Fig. 11. The chart $\ln[-\ln(1-x)/T^2]$ versus 1/T, for E_a and A determination on OD7-Asl2 using TGA.

is greater) has value of $E_a = 1083.7$ kJ/mol, and the pre exponential factor of A = 137.2, where the value of E_a and A is smaller than the OD7-Asl1 material, so that the velocity of the reaction is faster. The complete energy activation (E_a) values and pre exponential factors for each reaction stage on 4 levels temperature are shown in Table IV.

Reaction level	$E_{\rm a}$ (kJ/mol)	A (%/s)	
95 °C–205 °C	84.936	10.2	
225 °C–285 °C	271.93	47	
380 °C-445 °C	357.73	48	
610 °C-720 °C	369.09	32	

Table IV. The E_a and A of OD7-Asl2 material.

4. CONCLUSION

The energy activation of carbonate shale material is $E_a =$ 749–1339 kJ/mol and temperature for the process of carbonate shale material reaction is T = 75-740 °C.

The composition ratio (wt.%) of organic that is greater than carbonate causes the carbonate shale material (with TOC $\geq 12\%$) having a lower energy activation. The carbonate shale material of OD7-Asl2 (33% carbonate +67% organic) has $E_a = 1083.7$ kJ/mol lower than OD7-Asl1 (50% carbonate +50% organic) that has $E_a = 1338.1$ kJ/mol.

The TOC value that is so high, influences the energy activation becoming smaller (see number 2), namely carbonate shale material OD7-Asl2 is smaller than OD7-Asl1.

The maturity of shale material OD7-Asl2 occurs at T = (380-445 °C), $E_a = 1083.7 \text{ kJ/mol}$ and $T_{max} = 415 \text{ °C}$, it is better than OD7-Asl1 which occurs at T = (325-450 °C), $E_a = 1338.1 \text{ kJ/mol}$ and $T_{max} = 432 \text{ °C}$.

References

- Al-Hamaiedh, H., Maaitah, O. and Mahadin, S., 2010. Using oil shale ash in concrete binder. *EJGE*, 15, Bund. F., pp.601–608.
- AL-Hasan, N., 2006. Behavior of concrete made using oil shale ash and cement mixtures. *Oil Shale*, 23(2), pp.135–143.
- Barkia, H., Belkbir, L. and Jayaweera, S.A.A., 2004. Thermal analysis studies of oil shale residual carbon. *Journal of Thermal Analysis* and Calorimetry, 76(2), pp.615–622.
- 4. James T. Bartis, La Tourrette, T., Dixon, L., Peterson, D.J. and Cecchine, G., 2005. Oil Shale Development in the United States. Prospects and Policy Issues. Prepared for the National Energy Technology Laboratory of the U.S. Department of Energy. The RAND Corporation. ISBN: 978-0-8330-3848-7.
- Berraja, T., Barkia, H., Belkbir, L. and Jayaweera, S.A.A., 1988. Thermal Analysis Studies of the Combustion of Tarfaya Oil Shale. *Proceeding of an International Conference on Carbon, Carbon'88*, edited by B. McEnnaney and T. J. Mays, Univ. Newcastle Upon Tyne, UK. pp.18–23.
- Burnham, A.K. and McConaghy, J.R., 2006. Comparison of the Acceptability of Various Oil Shale Processes (https:// e-reports-ext.llnl.gov/pdf/341283.pdf), 26th Oil Shale Symposium. Golden, Colorado, Lawrence Livermore National Laboratory. UCRL-CONF-226717.
- Cahyadi and Yulianto, S.N., 2011. Studi Perilaku Penyalaan Partikel Batubara Indonesia Menggunakan Thermogravimetric Analysis Dalam Kondisi O₂/n₂ dan O₂/CO₂. Jurnal Ilmiah Teknologi Energi (JITE), 1(13), ISSN 1858-3466. Balai Besar Teknologi Energi-BPPT Jurnal Ilmiah Teknologi Energi.
- Cantrell, K.B., Hunt, P.G., Ro, K.S., Stone, K.C., Vanotti, M.B. and Burns, J.C., 2010. Thermogravimetric characterization of irrigated bermudagrass as a combustion feedstock. *Transactions of the ASABE*, 53(2), pp.413–420.

- Dewanto, O., 2008. Menentukan Kondisi Batuan Organik Di Daerah 'X' Sumatera Tengah, Berdasarkan Estimasi Kapasitas Termal Batuan Reservoar. *The Proceeding of National Seminar on Science and Technology-II*, Universitas of Lampung. pp.132–141, ISBN: 978-979-1165-74-7.
- 10. Dewanto, O., Bahri, S. and Atmojo, J.P., 2008. Analisis Perubahan Sifat-Sifat Fisika Batuan Organik terhadap Aliran Panas Bumi di Daerah 'X' Sumatera, untuk Menentukan Kandungan dan Daerah Oil Shale sebagai Sumber Energi Baru. *The Proceeding of the Annual Meeting, HAGI 33rd Annual Convention & Exhibition*, Hyatt Regency Bandung. ISBN: 978-979-8126-05-5.
- Dewanto, O., Mulyatno, B.S., Rustadi, and Wibowo, R.C., 2017. Determining the temperature of shale material conversion into crude oil based on organic clay and organic carbonate test outside reservoir. *International Journal of Mechanical & Mechatronics Engineering IJMME-IJENS*, 17(5), pp.84–89.
- Emam, E.A., 2013. Clays as Catalysts in Petroleum Refining Industry. ARPN Journal of Science and Technology, 3(4), pp.356–375.
- 13. Himawanto, D.A., 2013. Penentuan energi aktivasi pembakaran briket char sampah kota dengan menggunakan metoda thermogravimetry dan iso thermal furnace. *Jurnal Teknik Mesin Rotasi*, 15(3), pp.35–42.
- Himawanto, D.A., Indarto, Saptoadi, H. and Rohmat, T.A., 2013. Thermogravimetric analysis of single-particle RDF combustion. *Modern Applied Science*, 7(11), pp.33–42.
- 15. Indrati, T.Y., Hartati, P., and Murdani, 2000. Penentuan Energi Aktivasi Sinter Pelet (Th,U)O₂ Pada Tahap Pertumbuhan Butir. Prosiding Penemuan dan Presentasi Ilmiah Penelitian Dasar IImu Pengetahuan dan Teknologi Nuklir P3TM-BATAN Yogyakarta. 25.
- 16. Jiang, L., Liang, J., Yuan, X., Li, H., Li, C., Xiao, Z., Huang, H., Wang, H. and Zeng, G., 2014. Co-pelletization of sewage sludge and biomass: The density and hardness of pellet. *Bioresource Technol*ogy, 166(2014) pp.435–443.
- Kantsler, A.J., Cook, A.C. and Smith, G.C., 1978. Rank variation, calculated paleotemperatures in understanding oil, gas occurrence. *Oil and Gas Journal*, 20, pp.196–205.
- Slopiecka, K., Bartocci, P. and Fantozzi, F., 2011. Thermogravimetric Analysis and Kinetic Study of Poplar Wood Pyrolysis. *Third International Conference on Applied Energy*, Perugia, Italy. pp.1687–1698.
- Katz, B.J., 1983. Limitations of 'Rock-Eval' pyrolysis for typing organic matter. Organic Geochemistry, 4, pp.195–199.
- Kholisoh, S.D., 2011. Dasar-Dasar Kinetika Reaksi Kimia. Slide Kinetika Dan Katalisis. Jurusan Teknik Kimia. FTI UPN "VET-ERAN" Yogyakarta.
- 21. Kogerman, A., 2001. Ten years of oil shale. Oil Shale, 18(1), pp.1-4.
- 22. Malika, A., Mohammed, A. and Boukhlifi, A., 2014. Kinetic and energy study of thermal degradation of biomass materials under oxidative atmosphere using TGA, DTA and DSC. *Journal of Multidisciplinary Engineering Science and Technology (JMEST)*, 1(5), pp.74–78.
- 23. Marnoto, T. and Sulistyowati, E., 2012. Tinjauan Kinetika Pyrolysis Limbah Polystiren. *Prosiding Seminar Nasional Teknik Kimia*. Pengembangan Teknologi Kimia untuk Pengolahan Sumber Daya Alam Indonesia. Teknik Kimia, Fak Teknologi Industri, UPN Veteran Yogyakarta. ISSN: 1693-4393.
- 24. Martono, Y., Sari, Y.E.P. and Hidarto, J., 2012. Penggunaan Model Arrhenius Untuk Pendugaan Masa Simpan Produk Minuman Kemasan Berdasarkan Kandungan Vit C. Paper. Program Studi Kimia, Fakultas Sains dan Matematika. Universitas Kristen Satya Wacana.
- 25. Minarsih, T., 2011. Penentuan Energi Aktivasi Amlodipin Besilat Pada pH 1, 6 Dan 10 Dengan Metode Kromatografi Cair Kinerja Tinggi. PHARMACY. Vol.06 No.01 Agustus 2011. ISSN 1693-3591.
- 26. Mulyanto, B.S., Dewanto, O. and Rizky, S., 2018. Determining layer oil shale as new alternative energy sources using core analysis and

well log method. International Journal of Engineering & Technology, 7(4.36), pp.941–949.

- Pogaku, R., Raman, J.K. and Ravikumar, G., 2012. Evaluation of activation energy and thermodynamic properties of enzymecatalysed transesterification reactions. *Advances in Chemical Engineering and Science*, 2012(2), pp.150–154.
- 28. Sato, K., Takizawa, S. and Mohri, T., 2010. Theoretical calculation of activation free energy for self-diffusion in prototype crystal. *Materials Transactions*, 51(9), pp.1521–1525.
- Sugondo, 2012. Kinetika Pertumbuhan Butir Paduan Zry-4 Sn Rendah. Urania. Vol. 18 No. 3. Hal: 120–181. ISSN 0852-4777.
- 30. Sukma, H.L., 2012. Analisis Thermogravimetry Dan Pembuatan Briket Tandan Kosong Dengan Proses Pirolisis Lambat. Tugas Akhir Konversi Energi. Fakultas Teknologi Industri. Institut Teknologi Sepuluh Nopember Surabaya.
- **31.** Suyitno, **2009**. Perumusan laju reaksi dan sifat-sifat pirolisis lambat sekam padi menggunakan metode analisis termogravimetri. *Jurnal Teknik Mesin*, *11*(1), pp.12–18.
- **32.** Waples, D.W., **1985**. *Geochemistry in Petroleum Exploration*, Brown and Ruth Laboratories Inc., Denver Colorado, p.33.
- **33.** Yan, Y.F., Zhang, Z.E., Zhang, L. and Zhang, L., **2014.** Influence of coal properties on the co-combustion characteristics of low-grade coal and city mud. *Global NEST Journal*, *16*(2), pp.329–338.

Received: 1 January 2019. Accepted: 11 March 2019.